

# BID BULLETIN 01

Date: 12 December 2023

Project Title: Supply and Delivery of Office and IT Equipment and Supplies VSU Main and

Alang-Alang Campuses (VSU-GOODS-24-11)

**Location:** VSU Main, Visca, Baybay City, Leyte

Bidders are hereby informed/reminded of the following addendums/amendments/clarifications:

### I. LIST OF REQUIREMENTS

ENIS
CAL COMPONENT ENVELOPE
PhilGEPS Certificate of Registration (Platinum)
Statement of All On-Going Government & Private Contracts
Statement of Bidder's Single Largest Completed Contract (at least 25% of the ABC or Php 1,900,000.00)
Or
Statement of at least two (2) similar completed contracts w/ total amount of at least Php 1,900,000.00 and the largest of which should be at least PhP <b>950,000.00</b> .
Bid Security
Technical Specifications
SCHEDULE of Requirements/Production and delivery schedule
Manpower Requirements
After Sales service/parts from acceptance of delivered goods (at least 1 year for equipment),
Original Duly Signed Omnibus Sworn Statement
The Supplier's Audited Financial Statements
Net Financial Contracting Capacity (at least Php 3,800,000.00)
Or
Committed Line of Credit (at least Php 380,000.00)
AL COMPONENT ENVELOPE
Original of duly signed and accomplished Financial Bid Form
Original of duly signed and accomplished Price Schedule(s)



#### Please take note:

- 1. In the **Technical Specifications**, bidders must state either "Comply" or "Not Comply" <u>against each of the individual parameters of the specifications</u> per item stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in the **Bidders Bid** and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature (**Data Sheets**), unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data, and Brand and Model as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidders statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the provisions of **ITB** Clause 3.1(a)(ii) and/or **GCC** Clause 2.1 (a)(ii).
- 2. Bidders are advised to use the latest GPPB forms for the following documents:
  - a) Omnibus Sworn Statement
  - b) Performance Securing Declaration (if applicable)
  - c) Price Schedule for Goods Offered
  - d) Bid Form
  - e) Bid Securing Declaration

These forms can be accessed from the GPPB website: <a href="https://www.gppb.gov.ph/downloadables.php">https://www.gppb.gov.ph/downloadables.php</a>. Documents that are not in its updated/latest format shall be a ground for disgualification of the bidder.

- II. Preparation of Electronic Bid (for bidders who prefer electronic bid submission)
  - 1. Scan per document into Portable Document Format (PDF) and should be printable.
  - 2. Properly label all documents for prompt identification. Filename of documents, whichever are applicable to the bidder, should be as follows:

	Document	Filename (in PDF form)
1.	PhilGEPS Certificate of Registration (Platinum)	PhilGEPS
2.	Statement of On-Going Government & Private Contracts	Statement of On-Going Contracts
3.	Statement of Bidder's Single Largest Completed Contract	SLCC
4.	Statement of at least two (2) similar	Statement of Completed
	completed contracts	Contracts
5.	Bid Security	Bid Security
6.	Technical Specifications	Technical Specifications
7.	SCHEDULE of Requirements/	Schedule of Requirements
8.	Production and delivery schedule	Schedule of Requirements
9.	Manpower Requirements	Manpower Requirements
10.	After Sales service/parts	After Sales
11.	Omnibus Sworn Statement	Omnibus Sworn Statement
12.	Audited Financial Statements	Audited Financial Statements
13.	Net Financial Contracting Capacity	NFCC
14.	Committed Line of Credit	CLC
15.	Bid Form	Bid Form
16.	Price Schedule	Price Schedule



3. Create two (2) folders that are password-protected. The first folder should contain all requirements under Technical Component checklist as presented under Section VIII.

The second folder should contain all requirements under Financial Component checklist.

- 4. Compress the two (2) folders and name as follows: a) first folder: **Technical Documents**, b) second folder: **Financial Documents**.
- 5. Email the 2 compressed folders to Mr. Leopoldo S. Escala Jr at leopoldo.escala @vsu.edu.ph on or before the deadline.

# III. Changes in the Bidding Documents

# Original Section I. Invitation to Bid

5. A complete set of Bidding Documents may be acquired by interested Bidders on November 29 – December 20 2023 until 8:30 AM from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Five Thousand Pesos (PhP 5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means.

(Amendment)

A complete set of Bidding Documents may be acquired by interested Bidders on *November 29 – December 20 2023 until 8:30 AM* from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, The amount of applicable fee will depend on the total ABC quoted as shown below.

Total ABC Quoted	Applicable Fee
500,000.00 and below	500.00
Above 500,000.00 up to 1,000,000.00	1,000.00
Above 1,000,000.00	5,000.00

The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means:

The Bidders may deposit the payment for the bidding documents to the Visayas State University Landbank Account with the following details:

Account Name: Visayas State University Fund 164

Account Number: 3572-1000-13

Then send the deposit slip to leopoldo.escala @vsu.edu.ph



#### **Section II. Instructions to Bidders**

15. Sealing and Marking of Bids

(Additional Instructions)

Bidders are requested to submit three (3) copies of its bid – 1 Original, Copy 1, and Copy 2.

For filing purposes, the bidders are urged to use **Orange** envelopes for its Technical and Financial Component envelopes, including the Mother (outer) Envelope.

# IV. Revised List of Goods and Technical Specifications

- Some Specifications were added (in red font) and/or deleted (in blue font)
- Some Quantities and Unit Prices (ABC) were changed

Description	Unit	Qty	ABC/Unit (Pesos)	Total ABC (Pesos)
Delivery to VSU-Alang-alang Campus, Alangalang, Leyte				
Photocopier, 3 in1 ( Printer, Scanner and Copier)	units	3	63,000.00	189,000.00
General - Fax Type: Plain paper, Printing Technology: Laser - color, Display Diagonal Size: at least 4.3" Display Features: Touch screen, Connection Availability: Yes, Interface: USB 2.0, Gigabit LAN, Wi-Fi(n), USB host, AirPrint Enabled: Yes, Office Machine Features, Scan to e-mail, scan to folder, scan to FTP, scan to SMB, scan to USB host.				
Memory - Standard Memory: 512 MB, Max Supported Memory: 1.5 GB, Supported Flash Memory, SD Memory Card, SDHC Memory Card. Copying - Max Copying Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Max Copying Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),				
Max Document Enlargement: 400%, Max Document Reduction: 25%, Maximum Copies: 999. Scanning - Automatic Duplexing: Yes, Optical Resolution: 600 x 600 dpi and Printing - Max Printing Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),				
Max Printing Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Printer Drivers / Emulations: PCL 6, PCL 5c, KPDL3, PCL XL, PDF, XPS, PRESCRIBE, First Print Out Time B/W: 9.5 sec, First Print Out Time Color: 10.5 sec.				
With warranty, Free demonstration of the unit and preferably branded.				
Stencil Digital Duplicating Machine	unit	2	135,000.00	270,000.00
(Type: Digital, desktop, printing); Process: Fully-automatic one drum stencil, (System, original sheet only).  Original Size: at least 275x395mm may: Print Paper size:				
	Photocopier, 3 in1 ( Printer, Scanner and Copier)  General - Fax Type: Plain paper, Printing Technology: Laser - color, Display Diagonal Size: at least 4.3" Display Features: Touch screen, Connection Availability: Yes, Interface: USB 2.0, Gigabit LAN, Wi-Fi(n), USB host, AirPrint Enabled: Yes, Office Machine Features, Scan to e-mail, scan to folder, scan to FTP, scan to SMB, scan to USB host.  Memory - Standard Memory: 512 MB, Max Supported Memory: 1.5 GB, Supported Flash Memory, SD Memory Card, SDHC Memory Card. Copying - Max Copying Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Max Copying Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Document Enlargement: 400%, Max Document Reduction: 25%, Maximum Copies: 999. Scanning - Automatic Duplexing: Yes, Optical Resolution: 600 x 600 dpi and Printing - Max Printing Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Printing Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Printer Drivers / Emulations: PCL 6, PCL 5c, KPDL3, PCL XL, PDF, XPS, PRESCRIBE, First Print Out Time B/W: 9.5 sec, First Print Out Time Color: 10.5 sec.  With warranty, Free demonstration of the unit and preferably branded.  Stencil Digital Duplicating Machine  (Type: Digital, desktop, printing); Process: Fully-automatic	Photocopier, 3 in1 ( Printer, Scanner and Copier)  General - Fax Type: Plain paper, Printing Technology: Laser - color, Display Diagonal Size: at least 4.3" Display Features: Touch screen, Connection Availability: Yes, Interface: USB 2.0, Gigabit LAN, Wi-Fi(n), USB host, AirPrint Enabled: Yes, Office Machine Features, Scan to e-mail, scan to folder, scan to FTP, scan to SMB, scan to USB host.  Memory - Standard Memory: 512 MB, Max Supported Memory: 1.5 GB, Supported Flash Memory, SD Memory Card, SDHC Memory Card. Copying - Max Copying Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Max Copying Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Document Enlargement: 400%, Max Document Reduction: 25%, Maximum Copies: 999. Scanning - Automatic Duplexing: Yes, Optical Resolution: 000 x 600 dpi and Printing - Max Printing Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Printing Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Printer Drivers / Emulations: PCL 6, PCL 5c, KPDL3, PCL XL, PDF, XPS, PRESCRIBE, First Print Out Time B/W: 9.5 sec, First Print Out Time Color: 10.5 sec.  With warranty, Free demonstration of the unit and preferably branded.  Stencil Digital Duplicating Machine  (Type: Digital, desktop, printing); Process: Fully-automatic one drum stencil, (System, original sheet only).	Photocopier, 3 in1 ( Printer, Scanner and Copier)  General - Fax Type: Plain paper, Printing Technology: Laser - color, Display Diagonal Size: at least 4.3" Display Features: Touch screen, Connection Availability: Yes, Interface: USB 2.0, Gigabit LAN, Wi-Fi(n), USB host, AirPrint Enabled: Yes, Office Machine Features, Scan to e-mail, scan to folder, scan to FTP, scan to SMB, scan to USB host.  Memory - Standard Memory: 512 MB, Max Supported Memory: 1.5 GB, Supported Flash Memory, SD Memory Card, SDHC Memory Card. Copying - Max Copying Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Max Copying Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Document Enlargement: 400%, Max Document Reduction: 25%, Maximum Copies: 999. Scanning - Automatic Duplexing: Yes, Optical Resolution: 600 x 600 dpi and Printing - Max Printing Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color),  Max Printing Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Printer Drivers / Emulations: PCL 6, PCL 5c, KPDL3, PCL XL, PDF, XPS, PRESCRIBE, First Print Out Time B/W: 9.5 sec, First Print Out Time Color: 10.5 sec.  With warranty, Free demonstration of the unit and preferably branded.  Stencil Digital Duplicating Machine  (Type: Digital, desktop, printing); Process: Fully-automatic one drum stencil, (System, original sheet only).	Delivery to VSU-Alang-alang Campus, Alangalang, Leyte  Photocopier, 3 in1 ( Printer, Scanner and Copier)  General - Fax Type: Plain paper, Printing Technology: Laser - color, Display Diagonal Size: at least 4.3" Display Features: Touch screen, Connection Availability: Yes, Interface: USB 2.0, Gigabit LAN, Wi-Fi(n), USB host, AirPrint Enabled: Yes, Office Machine Features, Scan to e-mail, scan to folder, scan to FTP, scan to SMB, scan to USB host.  Memory - Standard Memory: 512 MB, Max Supported Memory: 1.5 GB, Supported Flash Memory, SD Memory Card, SDHC Memory Card. Copying - Max Copying Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Max Copying Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color), Max Document Enlargement: 400%, Max Document Reduction: 25%, Maximum Copies: 999. Scanning - Automatic Duplexing: Yes, Optical Resolution: 000 x 600 dpi and Printing - Max Printing Resolution: Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (color), Max Printing Speed: Up to 27 ppm (mono) / up to 27 ppm (color), Printer Drivers / Emulations: PCL 6, PCL 5c, KPDL3, PCL XL, PDF, XPS, PRESCRIBE, First Print Out Time B/W: 9.5 sec, First Print Out Time Color: 10.5 sec.  With warranty, Free demonstration of the unit and preferably branded.  Stencil Digital Duplicating Machine  (Type: Digital, desktop, printing); Process: Fully-automatic one drum stencil, (System, original sheet only).



	Minimum 90x140mm, maximum 275x395mm max; Print Paper weight: at least 35.0-127.9g/m2;				
	Print Speed: at least less than 45 seconds. resolution				
	300x300 dpi image mode; letter mode photo mode, photo/letter mode, image: position vertical 10mm,				
	horizontal 10mm;				
	Reproduction ratios: Pre-set reduction 71,82,87,93% Pper				
	feed/delivery table capacity: 500 sheets (80g/m2); Power				
	Consumption: Maximum: Master Making: Less than 175w (At 90 sheets per minute) standby: 35W.				
	With warranty, Free demonstration of the unit and				
	preferably branded.				
3	Air-conditioning unit, 4HP Split Type	unit	2	120,500.00	241,000.00
	3TR Floor Mounted Standing Inverter, branded, including				
	Accessories and with free Installations (includes at least 15 meter copper tube connections between condenser				
	and Indoor unit.)				
	DIMENSION Length 41.1cm Width 59.5cm Height				
	188.2cm-delete KEY FEATURES Digital LED Display Self Diagnosis Remote Holder Side Air Intake Auto Louvers				
	Energy Saving / Save Energy (SE) Wi-fi Controlled X-Fan				
	Function Compressor Low-Pressure Protection				
	TECHNICAL SPECIFICATIONS Power Supply 1 Ph / 230 V / 60 Hz Nominal Capacity 4.0 HP / 3 TR Cooling				
	Capacity at least 37,980 kJ/h				
	Rated Current 17.0 A Rated Power 3,550 W EER 10.7				
	Kj/hr-W s				
	Refrigerant (type/charge) R-410A / 2,450 g INDOOR UNIT Airflow (SH/Hi/Mi/Lo) 1,850 / 1,630 / 1,420 / 1,250 m³/hr				
	Sound Level (SH/Hi/Mi/Lo) 52 / 50 / 48 / 45 dB(A)				
	COPPER TUBE SIZE Low Side / High Side Ø 5/8" / Ø 3/8"				
	MAXIMUM PIPE DISTANCE BETWEEN INDOOR &				
	OUTDOOR Height / Length / Circuit Breaker 10 m / 30 m /				
	40 A Warranty 1-Year on Parts & Service 5 Years on				
	Motor				
4	Air Conditioning Unit 2.0 HP	unit	5	60,000.00	300,000.00
	Split type with free Installations, branded, including Accessories (includes at least 15 meter copper tube				
	connections between condenser and Indoor unit.)				
	Description: Product Overview,-delete with Silver Ion				
	Filter, - can remove dust and particles more than 90%-				
	delete Smart cooling, Auto select mode, on which mode the unit will run based on ID ambient. Easy Maintenance -				
	electronic control box and ID fan motor and placed				
	efficiently and easily accessible delete				
	Warranty: 5 years limited warranty on compressor; Parts: 1 year; Labor: 1 year,				
	General Specification, Nominal Size: 2.0 hp, with Remote				
	and Timer: Yes-delete				
	Cooling Capacity: at least-delete 6,500-19,000 kJ/h				
	Control Type: Timer, Cooling Area (sq. meters): 24 – 35 sqm, -delete				
	The Artifactor of the Control of the	i		i	



	Noise Level (Indoor) - High: approx. 44 dB(A), Noise Level (Indoor) - Low: approx. 34 dB(A),				
	With Speed Cooling,: Yes, Filter: HEPA Filter,-delete				
	Airflow Direction Control (Up & Down): Yes, Airflow Direction Control (Left & Right): No,-delete Temperature				
	Control: Digital, Energy Efficiency Ratio (MIN ~ MAX):				
	13.5 - 10.0, Mfd/ Assembled in the Philippines: No,-delete				
	Power Consumption: 1,750 (-delete 480 - 1,900 Watts)-				
	delete, Power Requirements: Voltage:-delete 230V, Other				
	Features: Blue Fin protection				
	Delivery to VSU Main Campus, Visca, Baybay City,				
	Leyte				
5	2 BURNER GAS STOVE	pcs	2	2,000.00	4,000.00
	■Heavy duty gas stove				
	■High quality fuel-efficient burner				
	■Durable metal gas ignition controls				
	■Stainless metal gasket and body				
	■Auto-ignition burner				
	o# of burners: 2				
	■Dimensions: must fit an area of at least (W x L ) 71 x 35.5 cm or 28 x 14 inches				
	■Burner diameter: 9 cm or 3.5 inches with Outer ring				
	diameter of 22.5cm or 8.9 inches				
	■Space in between outer rings: at least 20cm or 7.9				
	inches				
	■Warranty: 1 year				
6	Smart TV, at least 70"	unit	1	90,000.00	90,000.00
6	Specifications:	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K • Color: Dynamic Crystal Color	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED	unit	1	90,000.00	90,000.00
6	Specifications:  Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8	unit	1	90,000.00	90,000.00
6	Specifications:  Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"	unit	1	90,000.00	90,000.00
6	Specifications:  Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K  • PQI (Picture Quality Index): 2200	unit	1	90,000.00	90,000.00
6	Specifications:  Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K  • PQI (Picture Quality Index): 2200  • HDR (High Dynamic Range): HDR	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K  • PQI (Picture Quality Index): 2200  • HDR (High Dynamic Range): HDR  • HDR 10+: Support	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K  • PQI (Picture Quality Index): 2200  • HDR (High Dynamic Range): HDR  • HDR 10+: Support  • HLG (Hybrid Log Gamma): Yes  • Contrast: Mega Contrast  • Viewing Angle: N/A - delete	unit	1	90,000.00	90,000.00
6	Specifications: Picture Engine: Crystal Processor 4K  • Color: Dynamic Crystal Color  • Contrast: Mega Contrast  • Sound: Q-Symphony - delete  • Smart: Tap-View  • Design: AirSlim - delete  Specifications Detail  Product Type: LED  Series: 8  Display  • Screen Size:at least 70"  • Resolution: 3,840 x 2,160  • Screen Curvature: N/A - delete  Video  • Picture Engine: Crystal Processor 4K  • PQI (Picture Quality Index): 2200  • HDR (High Dynamic Range): HDR  • HDR 10+: Support  • HLG (Hybrid Log Gamma): Yes  • Contrast: Mega Contrast	unit	1	90,000.00	90,000.00



Auto Depth Enhancer: N/A - copy			
Contrast Enhancer: Yes			
Auto Motion Plus: Yes			
Film Mode: Yes			
Natural Mode Support: Yes			
Audio			
Dolby Digital Plus: Yes			
Dolby 5.1 Decoder: N/A – delete			
Object Tracking Sound: N/A -delete			
Q-Symphony: Q-Symphony			
Audio Pre-selection Descriptor: N/A -delete			
Hole Array Speaker: N/A - delete			
Sound Output (RMS): 20W			
Speaker Type: 2CH			
Woofer: N/A - delete			
Multiroom LinkYes			
Blutooth Audio: Yes			
Smart Service			
• SMART TV: Smart			
Operating System: Tizen™			
Bixby: US English, UK English, India English, Korean,			
French, German, Italian, Spanish, Portuguese (features			
vary by language)			
Voice Interaction: N/A - delete			
Far-Field Voice Interaction: N/A - delete			
• Alexa Built-in: N/A – delete			
Google Assistant Built-in: N/A - delete			
Works with Google Assistant: N/A -delete			
Works With Alexa: N/A -delete			
• TV Plus: N/A - delete			
Web Browser: Yes			
• Gallery: Yes			
Convergence			
TV to Mobile – Mirroring: N/A -delete			
Mobile to TV - Mirroring, DLNA: Yes			
NFC on TV: N/A - delete			
• Tap View: Yes			
• Digital Butler: N/A - delete			
Multi-View: N/A - delete			
Sound Wall: Yes			
Remote Access: Basic			
• 360 Video Player: N/A -delete	+ + + + + + + + + + + + + + + + + + + +		
360 Camera Support: N/A -delete     Plustooth Low Energy: Voc			
Bluetooth Low Energy: Yes     WiFi Direct: Yes	+	ļ	
• WiFi Direct: Yes			
TV Sound to Mobile: Yes     Sound Mirroring: Yes	1		
Sound Mirroring: Yes  Differentiation	+ + + -		
Differentiation Translation N/A state to	1 1		
• Tune Station: N/A - delete	1		
Auto Hotspot Connect: N/A - delete	1		
• S-Share: N/A - delete			
Auto Data Backup: N/A - delete	1		
Dongle Compatibility (3G / LTE / WiFi): N/A -delete			



	Analog Clean View: N/A - delete				
	Triple Protection: N/A - delete				
	Tuner/Broadcasting				
	Digital Broadcasting: ISDB-T				
	Analog Tuner: Yes				
	• 2 Tuner: N/A - delete				
	• CI (Common Interface): N/A - delete				
	Data Broadcasting: N/A - delete				
	TV Key Support: Yes				
	Connectivity				
	• HDMI: 3				
	• USB: 2				
	Component In (Y/Pb/Pr): N/A				
	Composite In (AV): 1				
	Ethernet (LAN): Yes				
	Audio Out (Mini Jack): N/A				
	Digital Audio Out (Optical): 1				
	• RF In (Terrestrial / Cable input): 1/1(Common Use for			1	
	Terrestrial)/0				
	• Ex-Link ( RS-232C ): N/A			1	
	• CI Slot: N/A				
	HDMI A / Return Ch. Support: Yes				
	• eARC: Yes				
	HDMI Quick Switch: Yes				
	Wireless LAN Built-in: Yes (WiFi5)      Plusteeths Yes (PTF 2)				
	Bluetooth: Yes (BT5.2)  Assert (UDM) 050) Yes				
	Anynet+ (HDMI-CEC): Yes				
7	Bread Toaster, 4 slots	unit	1	3,200.00	3,200.00
	4-slice Stainless Steel Toaster				
	Stainless Steel Body•Variable				
	Toast Control•Defrost & Reheat Functions				
	Slide-out Crumb Tray				
8					
	Conference Microphone, Gooseneck	unit	2	5,000.00	10,000.00
	Conference Microphone, Gooseneck  ©Acoustic Principle: Condenser Polar	unit	2	5,000.00	10,000.00
	■Acoustic Principle: Condenser Polar	unit	2	5,000.00	10,000.00
	Acoustic Principle: Condenser Polar     Pattern: Cardioid	unit	2	5,000.00	10,000.00
	■Acoustic Principle: Condenser Polar ■Pattern: Cardioid ■Frequency Response: 50-16000Hz	unit	2	5,000.00	10,000.00
	<ul> <li>Acoustic Principle: Condenser Polar</li> <li>Pattern: Cardioid</li> <li>Frequency Response: 50-16000Hz</li> <li>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> </ul>	unit	2	5,000.00	10,000.00
	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> </ul>	unit	2	5,000.00	10,000.00
	■Acoustic Principle: Condenser Polar  ■Pattern: Cardioid  ■Frequency Response: 50-16000Hz  ■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)  ■Signal to Noise Ratio: 80dB  ■Output connector: XLR Connector	unit	2	5,000.00	10,000.00
	■Acoustic Principle: Condenser Polar  ■Pattern: Cardioid  ■Frequency Response: 50-16000Hz  ■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)  ■Signal to Noise Ratio: 80dB  ■Output connector: XLR Connector  ■Power requirement: 48V Phantom Power	unit	2	5,000.00	10,000.00
	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> </ul>	unit	2	5,000.00	10,000.00
	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> <li>■Foam windscreen included</li> </ul>	unit	2	5,000.00	10,000.00
9	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> </ul>	unit	1	150,000.00	150,000.00
9	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> <li>■Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot</li> </ul>				
9	<ul> <li>Acoustic Principle: Condenser Polar</li> <li>Pattern: Cardioid</li> <li>Frequency Response: 50-16000Hz</li> <li>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>Signal to Noise Ratio: 80dB</li> <li>Output connector: XLR Connector</li> <li>Power requirement: 48V Phantom Power</li> <li>Built-in LED indicator shows Talk/Mute</li> <li>Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> </ul>				
9	<ul> <li>Acoustic Principle: Condenser Polar</li> <li>Pattern: Cardioid</li> <li>Frequency Response: 50-16000Hz</li> <li>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>Signal to Noise Ratio: 80dB</li> <li>Output connector: XLR Connector</li> <li>Power requirement: 48V Phantom Power</li> <li>Built-in LED indicator shows Talk/Mute</li> <li>Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> <li>Max printing size: 25*30cm</li> <li>Max printing thickness: 3cm</li> </ul>				
9	<ul> <li>Acoustic Principle: Condenser Polar</li> <li>Pattern: Cardioid</li> <li>Frequency Response: 50-16000Hz</li> <li>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>Signal to Noise Ratio: 80dB</li> <li>Output connector: XLR Connector</li> <li>Power requirement: 48V Phantom Power</li> <li>Built-in LED indicator shows Talk/Mute</li> <li>Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> <li>Max printing size: 25*30cm</li> <li>Max printing speed: 2cm - 5cm/s</li> </ul>				
9	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> <li>■Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> <li>Max printing size: 25*30cm</li> <li>Max printing speed: 2cm - 5cm/s</li> <li>Resolution: 300dpi</li> </ul>				
9	<ul> <li>Acoustic Principle: Condenser Polar</li> <li>Pattern: Cardioid</li> <li>Frequency Response: 50-16000Hz</li> <li>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>Signal to Noise Ratio: 80dB</li> <li>Output connector: XLR Connector</li> <li>Power requirement: 48V Phantom Power</li> <li>Built-in LED indicator shows Talk/Mute</li> <li>Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> <li>Max printing size: 25*30cm</li> <li>Max printing thickness: 3cm</li> <li>Max printing speed: 2cm - 5cm/s</li> <li>Resolution: 300dpi</li> <li>Printing method: Thermal printing</li> </ul>				
9	<ul> <li>■Acoustic Principle: Condenser Polar</li> <li>■Pattern: Cardioid</li> <li>■Frequency Response: 50-16000Hz</li> <li>■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</li> <li>■Signal to Noise Ratio: 80dB</li> <li>■Output connector: XLR Connector</li> <li>■Power requirement: 48V Phantom Power</li> <li>■Built-in LED indicator shows Talk/Mute</li> <li>■Foam windscreen included</li> <li>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</li> <li>Max printing size: 25*30cm</li> <li>Max printing speed: 2cm - 5cm/s</li> <li>Resolution: 300dpi</li> </ul>				



	O. fl	Ī	1		
	Software requirement: Most of softwares, Coreldraw,				
	photoshop, adobe illustrator, office word				
	Temperature requirement: 5°C to 40°C				
	Printer weight: 23kg				
	Printer size: 60cm*50cm				
	Warranty: 1year excluded printing head unless quality problem				
	Digital Duplicator Machine, Copy printer, 300x600				
10	DPI printing	set	1	150,000.00	150,000.00
	Master Making/Printing Methods: High-speed digital				
	master-making/Fully automatic printing				
	Scanning: 600 dpi × 600 dpi				
	Printing: 300 dpi × 600 dpi, Quick Master Making mode:				
	300 dpi × 400 dpi				
	Maximum Scanning Area: 297 mm × 432 mm				
	Print Paper Weight: 46 gsm to 157 gsm				
	Print Paper Size: 100 mm × 148 mm to 310 mm × 432 mm				
	Maximum Printing Area: 210 mm × 357 mm				
	Paper Feed Tray Stacking Capacity: 1000 sheets*2,				
	stacking height of 110 mm or lower				
	Paper Receiving Tray Stacking Capacity: 1000 sheets*2,				
	stacking height of 110 mm or lower				
	Print Speed: 5 levels: 60, 80, 100, 120 and 130 ppm				
	Functions: Original Scanning mode, Scanning Level,				
	Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink				
	Saving, Quick Master Making, ADF-Semi-Auto*3, Speed,				
	Density, Print Position, Program A/B, Job Separation*3,				
	Idling, Confidential, Meter Display, Count Report Output,				
	Proof, Direct Printing, USB Flash-via-Printing, Auto Sleep				
	Setting, Auto Power-OFF Setting, ECO mode, RISO				
	iQuality System				
	Ink Supply: Full automatic (1000 ml/cartridge)				
	Electric Floor Polisher, Vacuum Cleaner and				
11	Sound System	lot	1	86,000.00	86,000.00
	Item Specification				
	1.Wet and Dry Vacuum Cleaner - 1 unit				
	Item Specification				
	Super Suction Power				
	Wet and Dry Vacuuming				
	Blower Function			+	
	Accessory Storage	-		+	
	i i	-		+	
	Energy Efficient			+	
	Vacuum Cleaner Features: Bagged, Blower, Wheels	1		+	
	Warranty Type: Local Supplier Warranty	-		+	
	Warranty Period:1 Year	-			
	Actual suction power* (Air watts) 200	-			
	L L DOROV (1100 1771) 3 1 1 1 1 1 1				
	Energy use (W) 1000				
	Container capacity (I) 17				
	Container capacity (I) 17 Container material Stainless steel				
	Container capacity (I) 17 Container material Stainless steel Power cable (m) 4				
	Container capacity (I) 17 Container material Stainless steel Power cable (m) 4 Standard accessory ID (mm) 35				
	Container capacity (I) 17 Container material Stainless steel Power cable (m) 4				



	Weight incl. packaging (kg) 8,2				
	Dimensions (L x W x H) (mm) 388 x 340 x 525				
	1xSuction hose, 2 m, 35 mm; 2x Suction tubes, 0.5 m, 35				
	mm; 1x Wet and dry floor nozzle, Clips; 1x Cartridge filter,				
	Standard; 1x Crevice nozzle; 1x Paper filter bag				
	2. Electric Floor Polisher- 1 unit				
	Item Specification:				
	>Speed Switch-Speed Selection low (175 RPM) and High				
	(320 RPM)				
	>Handle Tube-All Chrome 1-1/2 inch				
	>Power Cord- 50ft, UL Listed 14/3 STW-A. Comes with				
	cord strain relief				
	>Transport Wheels- 5 inch non-marking self lubricated				
	wheels				
	>All Metal Housing-provides long lasting durability				
	3. Sound System- 1 unit				
	Item Specification				
	Specs	+			
	Type:Portable PA System	+			
	Speaker Drivers:1 x 8" woofer, 1.35" compression driver	+			
	Number of Mixer Channels:6	1			
	Number of Mic Preamps:2	+			
	EQ:Treble, Bass, 5-band Graphic				
	Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x stereo		-		
	pair), 2 x stereo RCA, 1 x 1/8" (aux in)				
	Outputs:2 x 1/4" (speaker out)				
	USB:1 x Type A (ULM wireless ready)				
	Bluetooth:Yes				
	Total Power:500W				
	Frequency Response:50Hz-22kHz				
	Microphone:1 x Behringer XM1800S				
	Power Source: Standard IEC AC cable				
	Height:25.9"				
	Width:13.9"				
	Depth:34.8"				
	Weight:44.7 lbs.				
			_		
12	Exhaust Fan	unit	1	2,500.00	2,500.00
	■Exhaust Fan 12 inch				
	■power input: 50w				
	■12 inch plastic blade				
	■wall-mounted				
	■reversible motor for desired air flow (Exhaust/Blower)				
	with pull cord switch				
	■detachable plastic panel & front grill				
	■metal shutters				
	■Air volume: 28.47/ 19.10 CMM				
	<b>■</b> Unit dimension: 39cm x 17cmx39cm				
	■Mounting Dimension: 35cm x 35cm				
13	Heavy Duty Combo Binding Machine	unit	1	18,000.00	18,000.00
	Maximum Punching Sheets: 25		_	,	- 3,000100
	■Max Size: LS, F4, A4, Extra Long	1			
	Selectable Punching Pins: 24 slots	1			
	ECONOCIONO I UNOTHING I IIIO. ET OIOIO	1	1	į	



14	-N ( ) M ( ) 1 ( 40 E)			1	
14	■Net Weight: 12.5kgs				
	Hot & Cold water dispenser	unit	1	14,500.00	14,500.00
	■Bottom load water dispenser				
	■3 Faucets: Hot, Cold and Normal water function				
	■3-Push Button dispensing control				
	Anti-scald safety lock switch				
	©Child Lock Safety feature on Hot Water Faucet				
	■Floater indicator to avoid water overflow				
	■Capacity: Hot - 1.2 Liters, Cold - 3.5 liters, Power Rating: Hot - 420 watts, Cold - 100 watts, R134a				
15	Laminator Machine, A3	unit	4	5,000.00	20,000.00
	■Heavy Duty, for A3 & A4 size, infrared heating system and adjustable temperature control with overheating protection				
16	Megaphone	unit	1	3,000.00	3,000.00
	■Bullhorn				
	■1000 yard range				
	■For indoor and outdoor use				
	■Built-in siren				
	■40 W amplifier				
	■Built-in mic				
	■10 seconds recording function				
17	Paper shredder machine, heavy duty	unit	3	12,000.00	36,000.00
	■Shred Type: Cross Cut				
,	■Maximum Sheet capacity(70gsm) : 10 Sheets				
	■Waste Container capacity: 21 Liters				
	■Power Source: 220 - 240 VAC				
18	Portable Trolley 15" Speaker with wireless microphone	unit	4	10,000.00	40,000.00
	■15" 2 Way 480 Watts Powered Portable Sound System				
	■Plastic Cabinet				
	■AC220V or DC12V (With built-in Rechargeable				
	Batteries)				
	■With 2 Wireless Microphone				
	■With 2 Mic Input (1 XLR, 1 PL55)				
	■With FM Radio, Bluetooth, Guitar Input (Shared with Mic				
	2 input), USB & SD Port				
	■With 5 Band Equalizer and LCD Display				
	■With Aux / Line In and Line Out				
	■With Remote Control, Handle and Wheel				
19	Sliding Paper Cutter	unit	4	3,000.00	12,000.00
	Working Area: A3 and A4				
	Cutting Capacity: 16 sheets				
	Packing Weight: 5 kg				
	Material: Metal				
	Available Size: A3 and A4				
	Available Size: A3 and A4 Packing Measurement: 56x34x11 cm				
	Available Size: A3 and A4				



	with wall bracket;				
	Resolution: 4K Ultra HD				
	Screen Size: at least 70"				
	Connectivity: 3x HDMI 2.1				
	2X USB				
	WIFI				
	BLUETOOTH				
	HDMI Ports: 3x HDMI 2.1				
	Voltage: AC100-240V - 59/69Hz				
21	Sound System, Speaker, 3 units	Lot	1	150,000.00	150,000.00
	All-in-one PA system with 10-channel powered mixer and full-range speakers				
	Bluetooth audio streaming	1			
	Sub output with automatic high-pass filter for powered	1			
	subwoofer use				
	with 2 microphone				
22	Speaker, for PC, 2.1 (Speaker with Subwoofer)	рс	1	1,500.00	1,500.00
	■Power Output : rms 4.5w×2 sw: 12w				-
	■Signal to noise ratio : 80dba				
	■Frequency Response : 80hz~20khz (±6db)				
	<b>©</b> R/l: 300±50mv sw: 100 ± 20mv				
	■Aux/USB/SD card				
	■Bass driver :4 inch				
	■Treble driver :2 3/4 inch				
23	Surge suppressor 6 outlets	unit	2	600.00	1,200.00
	■Maximum capacity: 2500W				
	■Voltage Surge Protector (protects appliances from voltage spikes)				
	■6 Neon Switch				
	■1 Circuit Breaker (protects appliance from overload or short circuit)				
	■3 Two-Prong Outlets				
	■3 Three-Prong Outlets w/ Grounding				
	■90 degree outlet orientation				
	■With line/noise filter				
	■Royal Cord #16/3 (5.00 meters)				
	■Metal casing				
24	Television, UHD, Smart TV	unit	1	32,000.00	32,000.00
	Display Size: at least 50"				
	Ports Input: OTHERS, HDMI, USB, Component in				
	(Y/PB/Pr), RF in (Terrestrial/Cable Input), Digital Audio				
	Out (Optical), Audio Out (Mini Jack), Ethernet (LAN),				
	Composite in (AV)				
	TV Features: Netflix, HDR, Cinema 3D, Wireless				
	Connectivity, Web Browser, Mobile Screen Mirroring,				
	Youtube, DTS Audio, Bluetooth Connectivity				
	TV Resolution: 4K UHD Smart TV OS: Android OS				
25		!4		45 000 00	45 000 00
25	Water Dispenser (top loading), with fridge	unit	1	15,000.00	15,000.00
	Fridge cabinet to cool additional drinks.				



	Three water spouts: hot, room temperature, cold.  LED indicators add to ease of use.			+	
	Durable/ good quality Size & Capacity				
	Gross weight (Kg): 17			+	
	Net weight (Kg): 15.46				
	Fridge cabinet capacity (L):19				
	Type & Setup				
	Type: Top load water dispensers				
	Control type: Manual				
	Product installation: Freestanding				
	Product dimensions				
	Depth: 372 mm			-	
	Height: 1003 mm				
	Width: 318 mm				
	Depth packed: 386 mm				
	Height packed: 1050 mm				
	Width packed: 358 mm				
	Power Supply				
	Voltage (V): 220-240				
	Total wattage (W): 520				
26	Wireless Dual Handheld Microphone	set	1	20,000.00	20,000.00
	Receiver				
	Power Consumption: 12w (Max)				
	Receiver Sensitivity: -95dbm				
	Mixing Output Socket: ø6.3mm Socket				
	Balanced Output Socket: XLR Socket				
	Transmitter				
	Carrier Frequency: Depends on regional frequency band				
	Transmit Power: 10dBm (±2dBm)				
	Microphone Capsule: Dynamic				
	Polar Pattern: Super Cardioid				
	Impedance: 600				
	Frequency Response: 80~12000Hz				
	Current Consumption: 120mA				
	Battery: Size AA x 2pcs				
	Operation Range: at least 90 meters (in open area)				
	Battery Life: Approximately 12 hours (uses alkaline batteries)				
	Each microphone has 100 selectable channels and				
	independent volume controls.				
	This UHF system features 6-axis gyroscope to				-
	automatically enter mute mode when idling for 5~10				
	seconds.				
27	Water Dispenser, Cabinet type	unit	2	10,000.00	20,000.00
	■Floor standing				
	■Hot and cold function				
	■plastic body, high efficiency compressor				
	■thermally protected				
28	Speaker, for PC, 2.1 (Speaker with Subwoofer)	рс	1	4,000.00	4,000.00
	■Power Output : rms 4.5w×2 sw: 12w	•			



	Scienal to naise ratio : 90dha				
	Signal to noise ratio: 80dba				
	■Frequency Response : 80hz~20khz (±6db)				
	©R/I: 300±50mv sw: 100 ± 20mv				
	■Aux/USB/SD card				
	Bass driver :4 inch		1		
	Treble driver :2 3/4 inch		1		
	Rebidding from VSU-GOODS-24-04 (delivered to VSU				
	Main Campus)				
29	3M RJ-45 Volition U.S. Faceplate face plate panel	рс	20	150.00	3,000.00
	double port 2-Port IO Information Outlet plate	P		100100	
	■Original 3M				
	■IO Information Outlet plate				
	■Ensure easy fitting and smart presentation of the RJ45				
	jacks				
	■The Keystone mounting feature of the Jack may allow				
	you to use other Keystone boxes or faceplates.				
	■High performance				
	■Brand new				
	©comes with 2 pcs screws				
	■Existing fleet of VSU Faceplate and should be				
	compatible with existing keystone				
	3M Volition Cat6 8-Way Female Tool-less IO				
30	Information Outlet RJ45 Connector Keystone	рс	38	350.00	13,300.00
	Mount				
	<b>©</b> Original 3M				
	<b>ID</b> Information Outlet				
	■Tool-less jack •				
	<b>⊠</b> Re-usable •				
	■Shallow Depth, Cable Entry from top or bottom •				
	■Keystone Mounting •				
	■Accepts both solid conductors from AWG 26 to 22 and				
	stranded conductors •				
	■Integral shutter Benefits •				
	■Easy and quick to install •				
	■Fast reliable connection in record time: 8 copper				
	conductor wired in a single connection •				
	■Quality of connection by design: not dependant on tool				
	condition or operator skills				
	■Easier cable management •				
	■No need to use a new jack if a wiring mistake is made •				
	■More space and flexibility to ensure the cable minimum			T	
	bend radius is never compromised •				
	■Compatibility between Volition copper and fiber jacks				
	and many other accessories on the market using the				
	standard keystone mounting •				
	■Compatible with all cables on the market and enables				
	'jack to plug' cables to be manufactured using stranded				
	conductors •				
	■Increased dust protection, especially during installation •				
	No additional shuttering required on faceplates •				
	■Higher port density •				
	■Allows direct mounting into floor boxes •				



	■An integral shutter protects the jack in the patch panel •				
	Should be compatible with the existing fleet of VSU				
	faceplates				
31	Battery Charger for 9 Volts Battery	рс	1	400.00	400.00
	For 9 volts rechargeable batteries *Charges 2x				
	rechargeable batteries (9 volts) at the same time\				
	*With 110v & 220v setting				
	Compatible with Nickel-Cadmium & Nickel-Metal Hydride rechargeable batteries				
32	Canon Cartridge 054 Toner - Black	рс	1	4,600.00	4,600.00
	For Canon Generic UFR II Printer Model: LBP621C				
	Color: Black				
33	Computer Keyboard USB-type	рс	4	400.00	1,600.00
	■Standard Keyboard with 104 Keys				
	<b>■</b> USB Connection				
	■Low Profile Key Caps				
	<b>◙</b> Minimum Key Noise				
	■Laser Printing for Key Layout				
	■Spill Resistant Design				
34	Computer Monitor 21.5", VA	unit	1	6,500.00	6,500.00
	Size: 21.5"				
	Panel Type: VA				
	Resolution: 1920x1080 (FHD)				
	Refresh Rate: 75Hz				
	Response Time: 5MS				
	Interface: VGA, HDMI				
	With a slim and 3-sided frameless design				
	Flicker Free and Low Blue Mode eye protection tech.				
	VESA mount compatibility				
35	DDR3 4GB SO - DIMM 2666 Mhz	unit	4	1,500.00	6,000.00
36	Desktop Computer, All-in-one (AIO), Pentium Silver, 4GB RAM	unit	1	27,000.00	27,000.00
	Intel Pentium Silver J5040 2.0GHz up to 3.20GHz				
	Processor or higher				
	4GB DDR4 Memory or higher				
	1TB 2.5" SATA HDD or higher				
	21.5" FHD 1920x1080 IPS Display (non-touch) or higher				
	Intel Graphics 802.11AC WiFi + BT   720P HD Camera				
	HDMI out 1.4 Port				
	Windows 10				
	DS3231 RTC High Precision Real-Time Clock				
37	Module	рс	2	200.00	400.00
38	DSLR Camera	unit	1	80,000.00	80,000.00
	24.5MP FX-Format BSI CMOS Sensor and EXPEED 6 Processor				
	51-Point Multi-CAM 3500 II AF Sensor				
	UHD 4K Video Recording				



	273-Point Hybrid AF System				
	Body Design				
39	DSLR Camera with lens and accessories	unit	1	42,000.00	42,000.00
	20.2MP APS-C 'Dual Pixel CMOS AF' sensor				
	DIGIC 5+ image processor				
	ISO 100-12800 standard, 25600 expanded				
	7fps continuous shooting, burst depth 65 JPEG / 16 Raw				
	'Silent' shutter mode				
	1080p30 video recording, stereo sound via external mic				
	19-point AF system, all points cross-type, sensitive to -0.5				
	63-zone iFCL metering system				
	98% viewfinder coverage, 0.95x magnification, switchable				
	gridlines and electronic level display				
	Fully-articulated touchscreen, 1040k dot 3" ClearView II				
	LCD, 3:2 aspect ratio				
	Single SD/SDHC/SDXC card slot				
	Built-in Wi-Fi				
	Single-axis electronic level				
	Built-in flash works as off-camera remote flash controller				
	AF microadjustment (can be set individually for up to 40				
	lenses, remembered by lens serial number)				
	In-camera High Dynamic Range and Multiple Exposure modes (JPEG-only)				
	'Creative Filter' image processing styles, previewed in live				
	view				
40	External Hard Drive, 1 TB	unit	10	3,500.00	35,000.00
	Capacity: 1TB				
	Connection interface: USB 2.0/3.0				
	Storage Media: 2.5" SATA HDD				
	Op. Voltage: USB DC 5V				
	Size :129.5mm x 82.4mm x 20.4mm				
	Weight: 216g				
41	Weight: 216g Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5	pcs	4	2,400.00	9,600.00
41	Hard Disk ST1000DM010 1TB 64MB Cache SATA	pcs	4	2,400.00	9,600.00
41	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5	pcs	4	2,400.00	9,600.00
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key Mic mute,	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  ©Line is equipped with a rotary volume controller, one key Mic mute,  ©Frequency Range: 20-20K(Hz)	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  ©Line is equipped with a rotary volume controller, one key Mic mute,  ©Frequency Range:20-20K(Hz)  ©Sensitivity:-52(dB)	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key Mic mute,  Frequency Range:20-20K(Hz)  Sensitivity:-52(dB)  Impedance:32(Ohm)	-	_		<u> </u>
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key Mic mute,  Frequency Range:20-20K(Hz)  Sensitivity:-52(dB)  Impedance:32(Ohm)  Speaker Diameter:40(mm)	-	_		
	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  ©Line is equipped with a rotary volume controller, one key Mic mute,  ©Frequency Range:20-20K(Hz)  ©Sensitivity:-52(dB)  ©Impedance:32(Ohm)  ©Speaker Diameter:40(mm)  ©Distortion Rate:0.8%	-	_		<u> </u>
42	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key Mic mute,  Frequency Range:20-20K(Hz)  Sensitivity:-52(dB)  Impedance:32(Ohm)  Speaker Diameter:40(mm)  Distortion Rate:0.8%  Plug Diameter:3.5mm	pc	1	500.00	500.00
42	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  Line is equipped with a rotary volume controller, one key Mic mute,  Frequency Range:20-20K(Hz)  Sensitivity:-52(dB)  Impedance:32(Ohm)  Speaker Diameter:40(mm)  Distortion Rate:0.8%  Plug Diameter:3.5mm  Headset, Over Ear, wired	pc	1	500.00	500.00
42	Hard Disk ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  ST1000DM010 1TB 64MB Cache SATA 6.0Gb/s 3.5  Headset (Wired), Generic Over the Ear with mic  ©Line is equipped with a rotary volume controller, one key Mic mute,  ©Frequency Range:20-20K(Hz)  ©Sensitivity:-52(dB)  ©Impedance:32(Ohm)  ©Speaker Diameter:40(mm)  ©Distortion Rate:0.8%  ©Plug Diameter:3.5mm  Headset, Over Ear, wired  ©Wearing Type: Over-ear	pc	1	500.00	500.00



	■Microphone: Omnidirectional				
	■Plug Type: 3.5mm				
	■Speaker Diameter: 50mm				
	■Receive Sensitivity: 101dB				
	<b>I</b> Impedance: 32Ω				
	■Frequency Response: 20-20kHz				
44	Ink Cartridge Pigment Ink For Epson WorkForce Pro WF-C878R, T05A1 T05A2 T05A3 T05A4, Printer Ink Bag	sets	2	7,500.00	15,000.00
	Ink Cartridge Pigment Ink For Epson WorkForce Pro WF- C878R				
	T05A1 (BLACK)				
	T05A2 (CYAN)				
	T05A3 (MAGENTA)				
	T05A4 (YELLOW)				
45	Ink Cartridge, HP704, black	рс	6	595.00	3,570.00
46	Ink Cartridge, HP704, tri color	рс	6	595.00	3,570.00
47	Ink, EPSON T9481 XL for WF-C878R Printer, Black	tube	5	1,500.00	7,500.00
48	Ink, EPSON T9481 XL for WF-C878R Printer, Cyan	tube	5	1,500.00	7,500.00
49	Ink, EPSON T9481 XL for WF-C878R Printer, Magenta	tube	5	1,500.00	7,500.00
50	Ink. EPSON T9481 XL for WF-C878R Printer, Yellow	tube	5	1,500.00	7,500.00
51	Laptop Stand Lifting Riser Holder Aluminum Height/Angle	рс	3	1,500.00	4,500.00
52	LCD Projector (XGA), 3LCD Technology	unit	5	27,000.00	135,000.00
	■Projection System Technology: RGB liquid crystal				
	shutter projection system (3LCD), 3-chip technology				
	White Light Output (Normal/Eco):3,600 Im				
	©Colour Light Output:3,600 Im				
	■Resolution XGA, at least 1024 x 768,				
	■Analog Input:D-Sub 15pin: 1				
	©Digital Input:HDMI: 1				
	■LCD:Native Resolution: XGA (1024 x 768)  ■Size: 0.55" (C2fine)				
	■Size: 0.05 (Czime) ■Lightsource:Type: 210W UHE				
	■Lightsource. Type: 210W of IE  ■Life (Normal / Eco): 6,000 / 12,000 hours				
	■Aspect Ratio:4:3				
	■USB Interface:USB Type B: 1 (For Firmware Update,				
	Copy OSD Settings)				
	■Analog Input:D-Sub 15pin: 1				
	■Digital Input:HDMI: 1				
53	LCD Projector, XGA (1024x768)	unit	1	27,000.00	27,000.00
	■Projection Method: Front/rear/ceiling mount				
	■Pixel Number: at least 786,432 dots (1024 x 768) x 3				
	©Color Brightness: 3.600 lumen- 2.235 lumen (economy)				
	In accordance with IDMS15.4				
	Aspect ratio: 4:3  Aspect ratio: 4:3  Aspect ratio: 4:3				
	■Lamp Life: ECO Mode up to 5000 hrs				



	■Normal Mode up to 4000 hrs				
	■Projection Distance Wide/Tele: 1,8 m - 2,17 m ( 60 inch				
	screen)				
	■Keystone Correction: Manual				
	■USB Plug 'n Play: Compatible w/ PC and MAC				
	computers				
	■Contrast Ratio: 15.000 : 1				
	■Color Reproduction: 16.77 million color				
54	LED Voltage Tester	unit	1	4,000.00	4,000.00
•	LED Voltage Tester	aint	•	1,000.00	1,000100
	600V AC/DC, Continuity Check, Battery Powered				
	CAT III 100V, CAT IV 600		-		
EE	,		_	E0 000 00	400 000 00
55	Mirrorless Camera, 24MP APS-C	unit	2	50,000.00	100,000.00
	■24.1MP APS-C CMOS Sensor				
	■Digital Imaging Integrated Circuit (DIGIC) 8 Image				
	Processor				
	■UHD 4K and HD 720p120 Video Recording				
	■Dual Pixel CMOS AF with Eye Detect AF				
	■2.36m-Dot OLED Electronic Viewfinder				
	■3.0" 1.04m-Dot Vari-Angle Touchscreen				
	■Wi-Fi and Bluetooth; Webcam Capability				
	■Extended ISO 51200, 10 fps Shooting				
	©Combination 5-Axis Image Stabilization				
	■Includes EF-M 15-45mm f/3.5-6.3 IS STM Lens				
56	Printer, Wi-Fi Duplex All-in-One Ink	unit	3	16,000.00	48,000.00
	Printer Type:Print, Scan, Copy				
	Print Method:On-demand inkjet (piezoelectric)				
	Printer Language:ESC/P-R, ESC/P Raster				
	Nozzle Configuration:180 x 1 nozzles Black, 59 x 1				
	nozzles per Colour (Cyan, Magenta, Yellow)				
	Maximum Resolution:5760 x 1440 dpi				
	Automatic 2-sided Printing: Yes (Up to A4)				
	Scanner Type:Flatbed colour image scanner				
	Sensor Type:CIS				
	Optical Resolution:1200 x 2400 dpi				
	USB:USB 2.0				
	Network:Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct				
	Network Protocol:TCP/IPv4, TCP/IPv6				
	LCD Screen:1.44" Colour LCD Screen				
57	Rechargeable Wireless Keyboard and Mouse Set	sets	2	1,000.00	2,000.00
	■Rechargeable Office Wireless Keyboard and Mouse Set				
	<b>■</b> Size: 284*121*16.mm				
	■Weight: 280g				
	■Connection method: USB receiver/Bluetooth				
58	Toner MP 2014H NRG Brand	btl	2	3,700.00	7,400.00
	MP2014H Series/MP2700/MP2701;				



60	UPS	unit	2	7,000.00	14,000.00
	■Output Power Capacity: 550 Watts/1100 VA				
	■Max Configurable Power: 550 Watts/1100 VA 2 years'				
	warranty				
	■Nominal Output Voltage: 230V				
	Output Connections:(2) IEC 320 C13 (Battery Backup)				
	(4) Universal Receptacle (Battery Backup)				
	■Nominal Input Voltage: 230V				
	■At most 4 hours charging time				
61	VOIP Phone	unit	2	12,000.00	24,000.00
	■1-Line PoE+ SIP VOIP Phone SPA MAC address (IEEE				
	802.3) with lifetime warranty				
	■IPv4 (RFC 791)Integrated web server provides web-				
	based administration and configuration				
	■Telephone keypad configuration via display				
	menu/navigation				
	■Automated provisioning and upgrade via HTTPS, HTTP,				
	TFTP				
	■Asynchronous notification of upgrade availability via				
	NOTIFY				
	■Nonintrusive in-service upgrades				
	■Report generation and event logging				
	■Statistics transmitted in BYE message				
	■Syslog and debug server records: configurable per line				
	■Address Resolution Protocol (ARP)				
	■DNS: A record (RFC 1706), SRV record (RFC 2782)				
	■Dynamic Host Configuration Protocol (DHCP) client				
	(RFC 2131)				
	■Internet Control Message Protocol (ICMP) (RFC 792)				
	■TCP (RFC 793)				
	■User Datagram Protocol (UDP) (RFC 768)				
	■Real-Time Transport Protocol (RTP) (RFC 1889, 1890)				
	■Real-Time Control Protocol (RTCP) (RFC 1889)				
	■Differentiated Services (DiffServ) (RFC 2475)				
	■Type of service (ToS) (RFC 791, 1349)				
	■VLAN tagging 802.1p/Q: Layer 2 quality of service (QoS)				
	Simple Network Time Protocol (SNTP) (RFC 2030)SIP				
	version 2 (RFC 3261, 3262, 3263, 3264)				
	SPCP with the Cisco Unified Communications 500 Series				
	SIP proxy redundancy: dynamic via DNS SRV, A records				
	■Reregistration with primary SIP proxy server				
	■SIP support in NAT networks (including STUN)				
	©SIPFrag (RFC 3420)				
	Secure (encrypted) calling via SRTP				
	©Codec name assignment				
	Voice algorithms:				
	■G.711 (A-law and μ-law)				
	■G.776 (16/24/32/40 kbps)				
	<b>©</b> G.729 A				
	<b>⊚</b> G.722				
	■ Dynamic payload support				
	Adjustable audio frames per packet				
	🗷 mujustavie audio irailies pei packet	l		1	



	■Dual-tone multifrequency (DTMF), in-band and out-of-				
	band (RFC 2833) (SIP INFO)				
	Flexible dial plan support with interdigit timers				
	■IP address/URI dialing support				
	©Call progress tone generation				
	■ Jitter buffer: adaptive				
	■Frame loss concealment				
	■Comfort Noise Generation (CNG)				
	■Voice activity detection (VAD) with silence suppression				
	■Attenuation/gain adjustments				
	■VMWI - Voicemail Waiting Indicator, via NOTIFY, SUBS				
	<b>©</b> Caller ID support (name and number)				
	■Third-party call control (RFC 3725)				
	■Should be compatible with existing fleet of VSU IP				
	Phones				
62	VoIP, Telephone	unit	2	15,000.00	30,000.00
	Display: White backlit, greyscale, 3.5-inch (396x162				
	pixels) display				
	Call Appearance:16 voice lines				
	Fixed Feature Buttons: Messaging, Service, Directory,				
	Hold/Resume, Transfer, Conference, Volume Control,				
	Speakerphone, Headset, and Mute				
	Navigation Keys: Two-way navigation and select keys				
	Programmable Line/Feature Keys: 16 programmable keys				
	that support either lines (such as directory numbers), or				
	call features (such as speed dialing).				
	Programmable Softkeys: 4 buttons				
	Button Module Expansion: No				
	Speakerphone: Includes high-quality, 2-way				
	_ · · · · · · · · · · · · · · · · · · ·				
	speakerphone Audio: Wideband audio enhances clarity with the handset,				
	speaker, or headset				
	1 '				
	Codecs: G.711 (A-law and m-law), G.722.2, G.722,				
	G.729ab, ILBC, iSAC, OPUS, Narrowband Opus DTMF:				
	In-band, out-of-band (RFC 2833), and SIP INFO Early				
	Media and Preconditions MOS Score Reporting				
	(Telchemy)				
	Wall-Mountable Kit				
	Ethernet Connectivity: Dual Ethernet (10/100) line				
	interface (PC Pass Through & Network Connection)	-			
	Headset Port: Includes RJ9 headset port with EHS support				
	Message Waiting Indicator: Yes				
	Network Security: Certificates, Image authentication,				
	Device authentication, File authentication, Signaling				
	authentication, Media encryption using Secure Real-Time				
	Transfer Protocol (SRTP) using AES-128, Signaling				
	encryption using Transport Layer Security (TLS) Protocol				
	using AES-128 or AES-256, Encrypted configuration files,				
	802.1X authentication, Cryptography				
	POWER REQUIREMENTS				
	Supports 802.3af Power-over-ethernet (PoE)				
	MUST have with Multiplatform Phone Firmware				
	Compatible with existing VSU fleet				



63	Wifi Access Point (Existing fleet of VSU Access Points)	unit	3	12,000.00	36,000.00
	UAP-nanoHD				
	Dimensions: 160 x 160 x 32.65 mm (6.30 x 6.30 x 1.29")				
	Weight: 300 g (10.6 oz)				
	With Mounting Kits: 315 g (11.1 oz)				
	Networking Interface: (1) 10/100/1000 Ethernet Port				
	Buttons: Reset				
	Power Method: 802.3af PoE				
	Power Supply: UniFi Switch (PoE)				
	Power Save: Supported				
	Beamforming: Supported				
	Maximum Power Consumption: 10.5W				
	Supported Voltage Range: 44 to 57VDC				
	TX Power				
	2.4 GHz: 23 dBm				
	5 GHz: 26 dBm				
	MIMO				
	2.4 GHz: 2x2				
	5 GHz: 4x4				
	Radio Rates				
	2.4 GHz: 300 Mbps				
	5 GHz: 1733 Mbps				
	Antennas				
	2.4 GHz: (2) Single-Port, Single-Polarity Antennas, 2.8				
	dBi each				
	5 GHz: (2) Single-Port, Dual-Polarity Antennas, 3 dBi ea				
	Wi-Fi Standards: 802.11 a/b/g/n/r/k/v/ac/ac-wave2				
	Wireless Security: WEP, WPA-PSK, WPA-Enterprise				
	(WPA/WPA2, TKIP/AES), 802.11w/PMF				
	BSSID: 8 per Radio  Mounting: Mol/Coiling (Kito Included)				
	Mounting: Wall/Ceiling (Kits Included) Operating Temperature: -10 to 70 C (14 to 158 F)				
	Operating Temperature: -10 to 70 C (14 to 136 F) Operating Humidity: 5 to 95% Noncondensing				
	Certifications: CE, FCC, IC				
	Advanced Traffic Management				
	VLAN: 802.1Q				
	Advanced QoS: Per-User Rate Limiting				
	Guest Traffic Isolation: Supported				
	WMM: Voice, Video, Best Effort, and Background				
	Concurrent Clients: 200+				
	Supported Data Rates (Mbps)				
	Standard Data Nates				
	802.11a 6,9,12,18,24,36,48,54 Mbps				
	802.11n 6.5 Mbps to 300 Mbps (MCS0-	<u> </u>			
	MCS15, HT 20/40				
	802.11ac 6.5 Mbps to 1.7 Gbps (MCS0-MCS9				
	NSS1/2/3/4, VHT 20/40/80)				
	58 Mbps to 1.7 Gpbs (MCS0-MCS9 NSS1/2, VHT 160)				
	802.11b 1, 2, 5.5, 11 Mbps				
	802.11g 6, 9, 12, 18, 24, 36, 48, 54 Mbps				



64	Drone (Professional Quadcopter With 5.5" Screen)	unit	2	260,000.00	520,000.00
	Ready To Fly.				
	Obstacle sensing: 5-way.				
	Obstacle avoidance: 4-way.				
	Redundant sensors: obstacle avoidance, dual compasses,				
	dual IMUs.				
	Range: 4.3 miles.				
	Maximum flight time: 30 minutes.				
	Top speed: 45 mph.				
	Big 1-inch sensor.				
	5.5-inch video monitor for controller.				
	4K video @ 60fps.				
	20MP stills, up to 14fps bursts.				
	Mechanical shutter that eliminates rolling distortion.				
	Wireless compatibility				
	Active-Track for locking onto and tracking subjects.				
65	Thermal Receipt Printer	unit	1	5,500.00	5,500.00
	Receipt Ticket Thermal Printer				
66	Window speaker intercom system	рс	3	3,300.00	9,900.00
	■Dual-way anti-interference intercommunication				
	<b>©</b> Connection cable length: at least 8m / 26.25ft				
	■Working voltage: DC12V / 500mA				
	■Adapter: AC 110/220V 50/60Hz				
	■Main sound (sub sound): 3W+3W				
	■Microphone sensitivity: -48db 20Hz-16KHz				
	■Material: aluminum alloy shell				
67	UPS Battery Backup, 1500VA	unit	2	10,000.00	20,000.00
	■ Capacity: at least 1500VA/900w				
	Output voltage: 220				
	Output frequency: 57-63 Hz for 60 Hz (or 50/60 Hz ± 3 Hz Sync to mains)				
	Input: 200 – 240 V, 50/60 HZ, 16.0 A maximum				
	Input frequency: 50/60 Hz +/- 3 Hz Auto-sensing				
	■6 battery backup sockets				
	■USB, coax, phone/network, and serial ports				
	■ with Automatic Voltage Regulation (AVR)				
	■LCD screen				
	■at most 4 hours charging time				
68	Monitor, 27" IPS, 4K (3840 x 2160)	unit	2	20,000.00	40,000.00
	Size (Inch): 27 Inch				
	<b>©</b> Resolution: 3840 x 2160				
	■Panel Type: IPS				
	■Aspect Ratio: 16:9				
	<b>⊚</b> Pixel Pitch: 0.1554 x 0.1554 mm				
	■Brightness (Typ.): 300 cd/m²				
	■Color Gamut (Typ.): sRGB 98% (CIE1931).				
	■Color Depth (Number of Colors): 1.07B				
	©Contrast Ratio (Min.): 700:1				
	■Contrast Ratio (Typ.): 1000:1				
	■Response Time 5ms (GtG at Faster)				



	<b>Solution</b> ■Viewing Angle (CR≥10) 178°(R/L), 178°(U/D)				
	Surface Treatment Anti-Glare				
69	SDS: 8417M-delete Micro Cut Paper Shredder	unit	2	10,800.00	21,600.00
	Paper Shredder				
	Features:				
	- Sheets / Pass: 17 Pages				
	- Cut Type: Micro-Cut				
	- Cut Size: 2mmx10mm				
	- Security: High Security Level Din-P-5				
	- Users: 5+				
	- Bin Size: 26L				
	- Safety: Safe touch function - stops shredder immediately when hand is detected too close to the paper opening				
	- Shreds: Paper, staples, paper clips, CDs, credit cards				
	- Warranty: 1 Year				
	- LCD display, retractable cover guard, easy carry				
	handles, bin level indicator, easy roll wheels				
70	GPS, Waterproof Hiking	unit	2	20,000.00	40,000.00
	General				
	Physical Dimensions - 2.7" x 6.2" x 1.2" (6.9 x 15.7 x 3.0 cm)				
	Display Size - 1.6" x 2.2" (4.1 x 5.6 cm)				
	Display Type - 256 color transflective TFT				
	Weight - 7.7 oz (218 g) with batteries				
	Battery Type - 2 AA batteries				
	Battery Life - 18 hours, typical				
	Watering Rating - IPX7				
	High-Sensitivity Receiver - Yes				
	Maps & Memory				
	Ability to add maps - Yes				
	Basemap - Yes				
	Automatic routing (turn by turn routing on roads) - Yes				
	External Memory Storage - 128 microSD card (included)				
	Waypoints/favorites/locations - 1000				
	Track Log - 10,000 points; 20 saved tracks				
	Routes - 50				
	Outdoor Recreation				
	Hunt/Fish Calendar - Yes				
	Sun and Moon information - Yes				
	Geocaching-Friendly - Yes				
	Sensors				
	Barometric Altimeter - Yes				
	Compass - Yes				
71	Area Calculation - Yes Ink cartridge HP # Q6003A, magenta	nc	10	4,140.00	41,400.00
11	ink cartriage or # Q0003A, magenta	рс	10	,	•
				TOTAL:	3,800,000.00

DILBERTO O. FERRAREN BAC Chairman