



BID BULLETIN 01

Date: April 5, 2024

Project Title: Supply and Delivery of Hardware, Electrical and Construction Supplies (VSU-GOODS-24-29)

Location: VSU Main, Visca, Baybay City, Leyte

Bidders are hereby informed/reminded of the following addendums/amendments/clarifications:

I. LIST OF REQUIREMENTS

| (1st Envelope) TECHNICAL COMPONENT ENVELOPE | |
|---|---|
| <i>Legal Documents</i> | |
| 1 | PhilGEPS Certificate of Registration (Platinum) |
| <i>Technical Documents</i> | |
| 2 | Statement of All On-Going Government & Private Contracts |
| 3 | Statement of Bidder's Single Largest Completed Contract (at least 25% of the ABC or Php 1,142,441.25 .) |
| | Or |
| | Statement of at least two (2) similar completed contracts w/ total amount of at least Php 1,142,441.25 and the largest of which should be at least Php 571,220.62 |
| 4 | Bid Security |
| 5 | Technical Specifications |
| 6 | SCHEDULE of Requirements/Production and delivery schedule |
| 7 | Manpower Requirements |
| 8 | After Sales service/parts from acceptance of delivered goods (at least 1 year for equipment and 3 months for supplies) |
| 9 | Original Duly Signed Omnibus Sworn Statement |
| <i>Financial Documents</i> | |
| 10 | The Supplier's Audited Financial Statements |
| 11 | Net Financial Contracting Capacity (at least Php 4,569,765.00) |
| | Or |
| | Committed Line of Credit (at least Php 456,976.50) |
| (2nd Envelope) FINANCIAL COMPONENT ENVELOPE | |
| 12 | Original of duly signed and accomplished Financial Bid Form |
| 13 | Original of duly signed and accomplished Price Schedule(s) |



Please take note:

1. In the **Technical Specifications**, bidders must state either “Comply” or “Not Comply” **against each of the individual parameters of the specifications** per item stating the corresponding performance parameter of the equipment offered. Statements of “Comply” or “Not Comply” must be supported by evidence in the **Bidders Bid** and cross-referenced to that evidence. Evidence shall be in the form of **manufacturer’s un-amended sales literature (Data Sheets), unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data, and Brand and Model** as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidders statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the provisions of **ITB** Clause 3.1(a)(ii) and/or **GCC** Clause 2.1 (a)(ii).

2. Bidders are advised to use the latest GPPB forms for the following documents:

- a) Omnibus Sworn Statement
- b) Performance Securing Declaration (if applicable)
- c) Price Schedule for Goods Offered
- d) Bid Form
- e) Bid Securing Declaration

These forms can be accessed from the GPPB website: <https://www.gppb.gov.ph/downloadables.php>. Documents that are not in its updated/latest format shall be a ground for disqualification of the bidder.

II. Preparation of Electronic Bid (for bidders who prefer electronic bid submission)

- 1. **Scan per document** into Portable Document Format (PDF) and should be printable.
- 2. Properly label all scanned documents for prompt identification. Filename of documents, whichever are applicable to the bidder, should be as follows:

| Document | Filename (in PDF form) |
|---|----------------------------------|
| 1. PhilGEPS Certificate of Registration (Platinum) | PhilGEPS |
| 2. Statement of On-Going Government & Private Contracts | Statement of On-Going Contracts |
| 3. Statement of Bidder's Single Largest Completed Contract | SLCC |
| 4. Statement of at least two (2) similar completed contracts | Statement of Completed Contracts |
| 5. Bid Security | Bid Security |
| 6. Technical Specifications | Technical Specifications |
| 7. SCHEDULE of Requirements/ 8. Production and delivery schedule | Schedule of Requirements |
| 9. Manpower Requirements | Manpower Requirements |
| 10. After Sales service/parts | After Sales |
| 11. Omnibus Sworn Statement | Omnibus Sworn Statement |
| 12. Audited Financial Statements | Audited Financial Statements |
| 13. Net Financial Contracting Capacity | NFCC |
| 14. Committed Line of Credit | CLC |
| 15. Bid Form | Bid Form |
| 16. Price Schedule | Price Schedule |



3. Create two (2) folders that are password-protected. The first folder should contain all requirements under Technical Component checklist as presented under Section VIII.

The second folder should contain all requirements under Financial Component checklist.

4. Compress the two (2) folders and name as follows: a) first folder: **Technical Documents**, b) second folder: **Financial Documents**.
5. Email the 2 compressed folders to Ms. Jessamine C. Ecleo at jessamine.ecleo@vsu.edu.ph before the deadline.

III. Changes in the Bidding Documents

| Original | |
|--|--|
| <p>Section I. Invitation to Bid</p> <p>5. A complete set of Bidding Documents may be acquired by interested Bidders on 20 March – 15 April 2024 until 8:30 AM from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Five Thousand Pesos (PhP 5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means.</p> | <p><i>(Amendment)</i></p> <p>5. A complete set of Bidding Documents may be acquired by interested Bidders on 20 March – 15 April 2024 until 8:30 AM from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Five Thousand Pesos (PhP 5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means:</p> <p>The Bidders may deposit the payment for the bidding documents to the Visayas State University Landbank Account with the following details:</p> <p>Account Name: Visayas State University Fund 164 Account Number: <u>3572-1000-13</u></p> <p>Then send the deposit slip to jessamine.ecleo@vsu.edu.ph</p> |
| <p>Section II. Instructions to Bidders</p> <p>15. Sealing and Marking of Bids</p> | <p><i>(Additional Instructions)</i></p> <p>Bidders are requested to submit three (3) copies of its bid – 1 Original, Copy 1, and Copy 2.</p> <p>For filing purposes, the bidders are urged to use Blue envelopes for its Technical and Financial Component envelopes, including the Mother (outer) Envelope.</p> |



IV. Revised List of Goods and Technical Specifications

- Some Specifications were added (in red font) and/or deleted (in blue font)
- Some Quantities and Unit Prices (ABC) were changed

| Item # | Description | Unit | Qty | ABC/Unit (Pesos) | Total ABC (Pesos) |
|--------|--|--------|-----|------------------|-------------------|
| 1 | Abrasive Paper, Sand Paper Grit #120, 9" x 11" | sheet | 26 | 30.00 | 780.00 |
| | ☑ <i>Fine Sanding, Waterproof, Good Quality;</i> | | | | |
| 2 | Acrytex Cast | gal | 1 | 750.00 | 750.00 |
| 3 | Backpack Leaf Blower | unit | 1 | 92,500.00 | 92,500.00 |
| | ☑ <i>4 stroke Gasoline 75.6 cc (3.8HP) ml.</i> | | | | |
| | ☑ <i>Engine (HP: 3.8 HP</i> | | | | |
| | ☑ <i>Max. Air Volume: 706 CFM</i> | | | | |
| | ☑ <i>Max Air Volume: 206 MPH</i> | | | | |
| | ☑ <i>Fuel Type: Unleaded gas</i> | | | | |
| | ☑ <i>Fuel Tank Capacity: 64 oz.</i> | | | | |
| | ☑ <i>Crank Case Capacity: 7.4 oz.</i> | | | | |
| | ☑ <i>Sound pressure: 76 dB(A)</i> | | | | |
| | ☑ <i>Dry weight: 24.1 lbs</i> | | | | |
| | ☑ <i>Power type: 4-stroke gas</i> | | | | |
| | ☑ <i>Blower type: backpack</i> | | | | |
| | ☑ <i>Use type: Professional</i> | | | | |
| | ☑ <i>Shipping weight: 31.1 lbs.</i> | | | | |
| 4 | Bulb, LED, 15W | pc | 6 | 300.00 | 1,800.00 |
| | ☑ <i>Wattage: 15 Watts</i> | | | | |
| | ☑ <i>Lumens: 1521</i> | | | | |
| | ☑ <i>Color Temp. : Daylight</i> | | | | |
| | ☑ <i>Beam Angle: 200 degrees</i> | | | | |
| | ☑ <i>Voltage: 170-240 V AC 50/60Hz</i> | | | | |
| | ☑ <i>Bulb Holder: E27</i> | | | | |
| | ☑ <i>Life Hours: 15,000 hrs.</i> | | | | |
| | ☑ <i>Material: PC cover & Aluminum PCB</i> | | | | |
| 5 | Electrical Conduit, (PVC) Orange, 3" x 3m | length | 10 | 750.00 | 7,500.00 |
| 6 | Electrical Outlet, Convenience 2 gang, (Flush type) | set | 10 | 200.00 | 2,000.00 |
| | <i>Good Quality, Durable</i> | | | | |
| 7 | Electrical PVC long sweep elbow, 3" x 90deg | pc | 10 | 350.00 | 3,500.00 |
| 8 | Electrical Wire, THHN 250 MCM (125mm²), Stranded Copper for 600Volts | meter | 80 | 1,500.00 | 120,000.00 |
| 9 | Electrical Wire, THHN/THW AWG 4/0(100 mm²), Stranded wire | meter | 250 | 920.00 | 230,000.00 |
| 10 | Fire Extinguisher, HCFC-123 10lbs (new) | unit | 12 | 7,000.00 | 84,000.00 |
| | SAFETY EQUIPMENT AND DEVICES | | | | |
| | <i>Clean Agent</i> | | | | |
| | <i>BPS Certified,</i> | | | | |
| | <i>HCFC-123</i> | | | | |
| | <i>with Free Wall Bracket,</i> | | | | |



| | | | | | |
|----|--|-------|----|-----------|------------|
| | BFP Approved | | | | |
| | 10lbs capacity tank | | | | |
| | with pressure gauge | | | | |
| | Nozzle and handle | | | | |
| 11 | Garden hose, 1/2" diameter | meter | 5 | 55.00 | 275.00 |
| 12 | Good Lumber, 2" x 6" x 12' | pc | 8 | 1,500.00 | 12,000.00 |
| 13 | Grass/Brush cutter | pc | 10 | 14,999.00 | 149,990.00 |
| | Ergonomically designed easy-grip bike handle and comes with added protection in the form of safety goggles and a single operator harness | | | | |
| | 4-Stroke engines deliver power, performance and reliability that no 2-Stroke can match | | | | |
| | Comfortable to use solid drive shaft with unique anti-vibration engine mount | | | | |
| 14 | Grass/Brush Cutter | pc | 3 | 25,000.00 | 75,000.00 |
| | Power type: 4 stroke Brush Cutter | | | | |
| | Displacement: 40.2 cc | | | | |
| | Match Engine: 1E40F-7 | | | | |
| | Rated Power: 1.4 kw | | | | |
| | Idle speed: 2800-3200 r/min | | | | |
| | Mix ratio : 25:1 (Gas/2T oil) | | | | |
| | Tank capacity: 1200 ml | | | | |
| | Shaft diameter: 28 mm | | | | |
| | Shaft length: 160 cm | | | | |
| 15 | Grass/Brush cutter (Four Stroke Engine) | unit | 1 | 25,000.00 | 25,000.00 |
| | ☑Engine: 4 stroke engine | | | | |
| | ☑Handle type: both hands | | | | |
| | ☑Power transmission method: automatic centrifugal clutch, spiral gear | | | | |
| | ☑Displacement Volume (cc): 41.5 | | | | |
| | ☑Carburetor: Float, piston valve | | | | |
| | ☑Starting Method: Recoil starter | | | | |
| | ☑Stopping Method: Sparking Circuit Primary Short | | | | |
| | ☑Lubricating Oil Used: 2-cycle engine oil | | | | |
| | ☑Fuel Tank Capacity (L): at least 1 | | | | |
| 16 | Hedge Trimmer | pc | 1 | 25,000.00 | 25,000.00 |
| | Dimension: 108 x 24.89 x 23 cm | | | | |
| | Size: Hedge Trimmer 50 cm | | | | |
| | Motor: 480 watts | | | | |
| | Sound level: 91 db (A) | | | | |
| | Blade Length: 50cm | | | | |
| | Tooth opening: 26mm | | | | |
| | No load stroke rate: 3,400 sPM | | | | |
| 17 | Top Coat, Polyurethane | liter | 2 | 660.00 | 1,320.00 |
| 18 | Knife, 6", Stainless Steel | pc | 1 | 280.00 | 280.00 |
| | High quality stainless steel, Non slip plastic handle, Durable | | | | |
| 19 | KSB Circuit Breaker 40 Amperes Three Phase | pc | 7 | 3,500.00 | 24,500.00 |



| | | | | | |
|----|--|--------|----|-----------|------------|
| 20 | KSB Circuit Breaker 60 Amperes Three Phase | pc | 7 | 5,000.00 | 35,000.00 |
| 21 | KSB Safety Breaker 20 amperes single phase | pc | 7 | 750.00 | 5,250.00 |
| 22 | KSB Safety Breaker 30 amperes single phase | pc | 7 | 850.00 | 5,950.00 |
| 23 | Lacquer Thinner | gal | 2 | 1,000.00 | 2,000.00 |
| 24 | Lawn Mower 22" | unit | 2 | 55,835.00 | 111,670.00 |
| | <i>Side discharge</i> | | | | |
| | <i>Steel deck</i> | | | | |
| | <i>Straight blade 22"</i> | | | | |
| | <i>Drive system: Hand Push Type</i> | | | | |
| | <i>Material: Metal</i> | | | | |
| | <i>Front wheel size: 8"</i> | | | | |
| | <i>Rear wheel size: 11"</i> | | | | |
| | <i>6.5 hp engine</i> | | | | |
| | <i>Height-of-cut: 25mm to 80mm</i> | | | | |
| 25 | LED Bulb, 5 watts | pc | 6 | 130.00 | 780.00 |
| 26 | LED tube T8, 18 watts | pc | 12 | 300.00 | 3,600.00 |
| | <i>LED Tube T8, 18 watts Fluorescent Day light;</i> | | | | |
| 27 | Metal Box/Pull Box 6" x 6" x 6" with cover | set | 5 | 600.00 | 3,000.00 |
| 28 | Nails, Finishing 1-1/2" | kg | 2 | 90.00 | 180.00 |
| 29 | Nails, Finishing 2-1/2" | kg | 1 | 100.00 | 100.00 |
| 30 | Nails, Finishing, 1" | kg | 2 | 90.00 | 180.00 |
| | <i>Smooth Shank</i> | | | | |
| 31 | Nails, Finishing, 2" | kg | 2 | 90.00 | 180.00 |
| | <i>Smooth Shank</i> | | | | |
| 32 | Oil Wood Stain Maple | can | 3 | 230.00 | 690.00 |
| 33 | Paint Brush, 2" | pc | 2 | 80.00 | 160.00 |
| | <input checked="" type="checkbox"/> <i>Durable bristles</i> | | | | |
| | <input checked="" type="checkbox"/> <i>Heavy duty metal ferrules</i> | | | | |
| 34 | Paint Thinner, at least 350cc per bottle | btl | 3 | 100.00 | 300.00 |
| | <i>Premium Quality</i> | | | | |
| 35 | Paint, Acrytex cast | gal | 1 | 750.00 | 750.00 |
| 36 | Paint, Burnt Umber Latex | liter | 2 | 260.00 | 520.00 |
| 37 | Paint, Raw Sienna, Latex | liter | 2 | 210.00 | 420.00 |
| 38 | Paint, Tolidine Red, Latex | liter | 1 | 260.00 | 260.00 |
| 39 | Paint, TTC, Raw Sienna, Latex | liter | 1 | 500.00 | 500.00 |
| | <i>Premium Quality</i> | | | | |
| 40 | Paint. Burnt umber, enamel | liter | 1 | 210.00 | 210.00 |
| 41 | Plywood, Marine, 3/4"(thickness) x 4' x 8' | pc | 5 | 1,650.00 | 8,250.00 |
| | <i>Standard, Good Quality</i> | | | | |
| 42 | Plywood, Ordinary, 3/4"(thickness) x 4' x 8' | pc | 25 | 1,500.00 | 37,500.00 |
| | <i>Standard, Good Quality</i> | | | | |
| 43 | Polyurethane Top coat | gal | 1 | 1,900.00 | 1,900.00 |
| 44 | Polyurethane Top Coat | liter | 1 | 660.00 | 660.00 |
| 45 | PVC Long Sweep elbow 2 1/4" Heavy Duty PNS:14 | pc | 15 | 250.00 | 3,750.00 |
| 46 | PVC Pipe 2 1/4" Heavy Duty PNS: 14 | length | 60 | 550.00 | 33,000.00 |
| 47 | Roller Runner / Drawer Roller (12") | set | 35 | 100.00 | 3,500.00 |
| | <i>One full set for 1 drawer (computer keyboard)</i> | | | | |
| | <i>Coated with white paint for anti-rust</i> | | | | |



| | | | | | |
|----|---|-------|-----|------------|------------|
| | <i>Easy to install</i> | | | | |
| 48 | S4S Wood Lauan or Equivalent Good Lumber (1/2"x2"x10') | pc | 55 | 250.00 | 13,750.00 |
| | <i>Good lumber 1/2 inch x 2 inch x 10 ft</i> | | | | |
| 49 | Sanding sealer, 500ml/bot | btl | 2 | 150.00 | 300.00 |
| 50 | Screened Sand | cu.m. | 80 | 1,500.00 | 120,000.00 |
| 51 | Solderless connector (Split Bolt) for 250 MCM Wire | pc | 6 | 3,000.00 | 18,000.00 |
| 52 | Solderless Connector for 100AWG Wire Split Bolt | pc | 6 | 1,500.00 | 9,000.00 |
| 53 | Stand Fan, 405 mm diameter, 220 volts | unit | 2 | 2,500.00 | 5,000.00 |
| | ☑ <i>Durable High-performance motor</i> | | | | |
| | ☑ <i>3-speed push button switch</i> | | | | |
| | ☑ <i>Thermal fuse protection</i> | | | | |
| | ☑ <i>Oscillation</i> | | | | |
| | ☑ <i>With height adjustment</i> | | | | |
| 54 | Transformer, Distribution, 100 KVA | unit | 3 | 230,000.00 | 690,000.00 |
| | <i>100 KVA; OISC;</i> | | | | |
| | <i>Copper to copper both primary and secondary windings;</i> | | | | |
| | <i>8 KV with changer, 2-2 1/2% above rated primary voltage and 2-2 1/2% below rated primary voltage double bushing;</i> | | | | |
| | <i>Secondary voltage 120/240 volts with changer tap</i> | | | | |
| | <i>Pad/pole mounted</i> | | | | |
| | <i>Amorphous Metal Core</i> | | | | |
| 55 | U-Clip (Stainless), 3" , with screw | pc | 20 | 300.00 | 6,000.00 |
| 56 | U-clip Stainless 2 1/4", with screw | pc | 50 | 250.00 | 12,500.00 |
| 57 | Wood Glue, Premium Quality | quart | 1 | 275.00 | 275.00 |
| 58 | Wood Glue | liter | 1 | 275.00 | 275.00 |
| 59 | Hacksaw Blade, 24 TPI x 12" | pc | 4 | 55.00 | 220.00 |
| | <i>Bi-metal, High-Speed, Durable, Premium Quality</i> | | | | |
| 60 | Wheelbarrow | unit | 1 | 3,500.00 | 3,500.00 |
| | ☑ <i>Atleast 4 cu.ft lightweight powder-coated steel tray with rust-resistant zinc handles and legs</i> | | | | |
| | ☑ <i>Heavy-duty rubber wheels, Durable</i> | | | | |
| 61 | Steel Angle bars, 1-inch | pc | 3 | 500.00 | 1,500.00 |
| | <i>1"x1"x3mm; Length: 6m</i> | | | | |
| 62 | Steel Flat bar, 1-inch | pc | 3 | 250.00 | 750.00 |
| | <i>1"x3mm; Length: 6m;</i> | | | | - |
| 63 | Fire Alarm Photo Electric Smoke Detector | pc | 15 | 650.00 | 9,750.00 |
| | <i>2 Wire, DC, 24 Volts</i> | | | | |
| 64 | 2.0 mm Welding rods, E6013 | kg | 2 | 500.00 | 1,000.00 |
| 65 | 8m Tape Measure | pc | 3 | 500.00 | 1,500.00 |
| | <i>8m (26 feet), Heavy duty Matte-finish blade with 3-rivet corrosion-resistant hook;</i> | | | | - |
| | <i>ergonomic bi-material cushioned grip with belt clip on the back</i> | | | | - |
| 66 | Blade, Circular Saw Wood 10" 250mm x 30T | pc | 8 | 3,000.00 | 24,000.00 |
| 67 | Cement, Portland | bag | 500 | 330.00 | 165,000.00 |



| | | | | | |
|----|---|--------|----|-----------|-----------|
| | ☑Type 1P, Premium Quality | | | | - |
| | ☑ASTM C150 | | | | - |
| 68 | Expansion bolt for concrete, 1/4"x50mm, Hex type | pc | 20 | 10.00 | 200.00 |
| 69 | Extension cord, 3 universal outlets, 5 meters. Power capacity, at least 2200W | pc | 5 | 350.00 | 1,750.00 |
| 70 | GI Pipe 1/2 x 6 m. sch 40 | length | 2 | 650.00 | 1,300.00 |
| 71 | Hacksaw frame | pc | 2 | 500.00 | 400.00 |
| | Steel frame with molded cushion grip, adjustable 8-12 inches; | | | | - |
| 72 | Hand Planer Portable 3-1/4" good quality | unit | 1 | 6,000.00 | 6,000.00 |
| 73 | Round file, 3/16" x 7-7/8" for Chainsaw | pc | 25 | 300.00 | 7,500.00 |
| 74 | Router Bit Set 12mm 1/2, atleast 12 pcs/set | set | 1 | 2,000.00 | 2,000.00 |
| 75 | S-type Load Cell (weight sensor), 1000 kg | pc | 1 | 4,000.00 | 4,000.00 |
| 76 | S-type Load Cell (weight sensor), 500 kg | pc | 1 | 2,000.00 | 2,000.00 |
| 77 | Wood Router Machine | unit | 1 | 17,000.00 | 17,000.00 |
| | Plunge 1/4" & 1/2" | | | | - |
| | Power: 1850W | | | | - |
| | Speed: 23000 Rpm | | | | - |
| 78 | Bidet spray toilet bidet rinse set, Heavy Duty | pc | 42 | 2,000.00 | 84,000.00 |
| 79 | Fire Alarm Bell | unit | 2 | 1,885.00 | 3,770.00 |
| | Conventional 8 inches, 24 DC | | | | |
| | Sound Output: 80 dB | | | | |
| | Operating voltage limit: 16-33V DC | | | | |
| | Maximum current: (DC) 31.1 mA | | | | |
| | Operating Temperature: -35C to 60C | | | | |
| 80 | Flat Bar, 1/4" (thickness) 1" x 6 meter | pc | 1 | 500.00 | 500.00 |
| 81 | Angle Bar, 1/4"(thickness) x 1-1/2" x 1-1/2" x 20', standard | length | 2 | 1,000.00 | 2,000.00 |
| | Premium Grade | | | | |
| 82 | Angle Bar, 1/4"(thickness) x 2" x 2" x 20', standard | length | 4 | 1,300.00 | 5,200.00 |
| | Premium Grade | | | | |
| | GOODS-23-47 Rebidding | | | | |
| 83 | 24V Cordless Grass Cutter 2 Lithium battery Electric Brush trimmer 650W power outdoor telescopic Lawn mower | pc | 1 | 5,000.00 | 5,000.00 |
| 84 | 50 watts LED spotlight RGB flood light multicolor | set | 3 | 2,500.00 | 7,500.00 |
| | LED spotlight RGB flood light | | | | |
| | Multicolor with changing color dimming lights outdoor | | | | |
| | Round type | | | | |
| | 230V AC supply | | | | |
| 85 | Anti UV 85% Sun Shade Net black Outdoor Garden Net Farm Net Greenhouse Net Sunscreen | meter | 60 | 60.00 | 3,600.00 |
| | Sun shade net | | | | |
| | Color: Black | | | | |
| | Dimension (LXW): 1x50M | | | | |
| | Function: Shading heat insulation, humidity reduction | | | | |
| | Applicable scene: Garden, Plants shade, Greenhouse | | | | |
| 86 | Terminal Lug for cable insulated fork type 100 | pc | 50 | 90.00 | 4,500.00 |



| | | | | | |
|-----|---|-------|-----|----------|------------|
| | amperes capacity heavy duty | | | | |
| 87 | Terminal Lug for cable insulated fork type 125 amperes capacity heavy duty | pc | 50 | 150.00 | 7,500.00 |
| 88 | Terminal Lug for cable insulated fork type 15 amperes capacity heavy duty | pc | 200 | 10.00 | 2,000.00 |
| 89 | Terminal Lug for cable insulated fork type 150 amperes capacity heavy duty | pc | 50 | 200.00 | 10,000.00 |
| 90 | Terminal Lug for cable insulated fork type 175 amperes capacity heavy duty | pc | 50 | 200.00 | 10,000.00 |
| 91 | Terminal Lug for cable insulated fork type 20 amperes capacity heavy duty | pc | 200 | 10.00 | 2,000.00 |
| 92 | Terminal Lug for cable insulated fork type 200 amperes capacity heavy duty | pc | 50 | 200.00 | 10,000.00 |
| 93 | Terminal Lug for cable insulated fork type 30 amperes capacity heavy duty | pc | 200 | 30.00 | 6,000.00 |
| 94 | Terminal Lug for cable insulated fork type 300 amperes capacity heavy duty | pc | 50 | 300.00 | 15,000.00 |
| 95 | Terminal Lug for cable insulated fork type 350 amperes capacity heavy duty | pc | 50 | 300.00 | 15,000.00 |
| 93 | Terminal Lug for cable insulated fork type 40 amperes capacity heavy duty | pc | 200 | 30.00 | 6,000.00 |
| 97 | Terminal Lug for cable insulated fork type 400 amperes capacity heavy duty | pc | 50 | 350.00 | 17,500.00 |
| 98 | Terminal Lug for cable insulated fork type 60 amperes capacity heavy duty | pc | 200 | 50.00 | 10,000.00 |
| 99 | Terminal Lug for cable insulated fork type 70 amperes capacity heavy duty | pc | 50 | 50.00 | 2,500.00 |
| 100 | Terminal Lug for cable insulated fork type 80 amperes capacity heavy duty | pc | 50 | 90.00 | 4,500.00 |
| | <i>Sample picture for items 86-100</i> | | | | |
| |  | | | | |
| 101 | Electrical wire, THHN/THWN 250 MCM/150MM2 600 Volts, Stranded Wire | meter | 500 | 1,900.00 | 950,000.00 |
| 102 | Formica sheets, (White), 4' x 8', Plain White <i>Good Quality</i> | sheet | 5 | 1,500.00 | 7,500.00 |
| 103 | Gravel, 3/4" size | cu.m. | 1 | 1,500.00 | 1,500.00 |
| 104 | Mosquito Net for Windows, Aluminum/Stainless, 3' | meter | 12 | 200.00 | 2,400.00 |
| 105 | Mounting Screw and Nut, set (arduino) M3 <i>Hex Screw Nut Assortment Kit in box</i> <i>Hex Spacers/ Screws/ Nuts Assorted Kit</i> | set | 6 | 250.00 | 1,500.00 |



| | | | | | |
|-----|--|--------|----|----------|-----------|
| | M3 - 0.5 | | | | |
| | Good quality | | | | |
| 106 | Pipe Fittings, (G.I.) Flange, 1"Ø with bolt and nut | pc | 5 | 150.00 | 750.00 |
| | Schedule 40, Good Quality | | | | |
| 107 | Pipe Fittings, (G.I.), Tee, 2"Ø | pc | 5 | 300.00 | 1,500.00 |
| | Schedule 40, Good Quality | | | | |
| 108 | Plywood, Ordinary, 3/4"(thickness) x 4' x 8' | pc | 20 | 1,500.00 | 30,000.00 |
| | Standard, Good Quality | | | | |
| 109 | Raincoat, Jacket and Pants, Large, Transparent | pair | 9 | 600.00 | 5,400.00 |
| | Heavy Duty, Good Quality | | | | |
| 110 | Sand, Washed | cu.m. | 1 | 1,500.00 | 1,500.00 |
| 111 | Solar Water Pump, DC 12V | pc | 2 | 2,000.00 | 4,000.00 |
| | Model:DC-12V/10/120 | | | | |
| | Voltage: 12V | | | | |
| | Power: 180W | | | | |
| | Max. flow rate: 1.5M ³ /H | | | | |
| | Max. head: 15m | | | | |
| | Outlet Size: 1 Inch | | | | |
| | Good quality, durable | | | | |
| 112 | Steel Bar, Round (plain), 25mm x 6m | length | 10 | 1,700.00 | 17,000.00 |
| | Standard Grade | | | | |
| 113 | Tiles, Granite 60cm x 60cm | pc | 16 | 280.00 | 4,480.00 |
| | Biege, Premium grade | | | | |
| 114 | UV plastic, (Greenhouse anti UV treated polyethylene) | roll | 1 | 4,500.00 | 4,500.00 |
| | Thickness: 150 microns - 6 mil | | | | |
| | Size: 4m x 12m | | | | |
| 115 | Paint Brush, Lettering, 1" | pc | 12 | 880.00 | 10,560.00 |
| | Camel's hair, Good Quality | | | | |
| 116 | Fire alarm with Strobe light | unit | 3 | 3,000.00 | 9,000.00 |
| | Operating voltage Loop: 24V (18.5V ~26V) | | | | |
| | Standby current Loop: ≤0.4mA | | | | |
| | Indoor (Non-residential); Temperature: -10°C ~+50°C | | | | |
| | Relative Humidity: ≤95% (40±2°C) | | | | |
| | Sound level 75dB ~115dB (A weighte | | | | |
| | Basic flashing frequency 1Hz ~1.5Hz | | | | |
| | Certification: ISO9001/CE/ROHS/UL Listed | | | | |
| 117 | Capacitive soil moisture sensor, (corrosion resistant) | pc | 12 | 200.00 | 2,400.00 |
| | Soil moisture sensor capacitive | | | | |
| | voltage range: 3v-5.5v | | | | |
| | interface: PH2.0-3P | | | | |
| 118 | Float Valve for Water Tank Cistern | pc | 1 | 650.00 | 650.00 |
| 119 | LED Headlamp Rechargeable Head Lamp Zoom Waterproof Headlight Flashlight USB Charging | unit | 30 | 650.00 | 19,500.00 |
| 200 | LPG Tank, Approx. Weight 11kg, refill for Petron Gasul | tank | 2 | 1,500.00 | 3,000.00 |
| 201 | Water hose/pipe, at least 25 meters/roll | roll | 3 | 850.00 | 2,550.00 |



| | | | | | |
|-----|---|-------|----|-----------|-----------|
| 202 | High Density Polystyrene Board (Styrofoam) - 1/2" x 2' x 4' sheet | sheet | 20 | 220.00 | 4,400.00 |
| 203 | Thick Glass, 4' x 1' - 2 items -5mm | lot | 1 | 10,000.00 | 10,000.00 |
| | Thick Glass 8' x 1' - 2 items | | | | |
| 204 | Bristol Board/Fold Coat (6 Ply) | sheet | 50 | 100.00 | 5,000.00 |
| 205 | Dried Moss | bag | 50 | 300.00 | 15,000.00 |
| 206 | Styrofoam Cutter (Hot Blade) - 4" and 6" blade/rod | lot | 1 | 5,000.00 | 5,000.00 |
| 207 | Styrofoam Cutter (Hot wire assembly) - 6 inch max thickness cut | lot | 1 | 7,500.00 | 7,500.00 |
| 208 | Flow Acrylic (Canvass Painting) | btl | 3 | 100.00 | 300.00 |
| | Good Quality | | | | |
| 209 | Sheet, Acrylic, 1/8"(thickness) x 4' x 8', Clear | sheet | 1 | 3,200.00 | 3,200.00 |
| | Good Quality | | | | |
| 210 | Solar charge controller 100amps | unit | 1 | 4,000.00 | 4,000.00 |
| | ☑Solar charge controller | | | | |
| | ☑Charge current: 100amps | | | | |
| | ☑Battery voltage: 12v/24v auto adapt | | | | |
| 211 | Solar Power Inverter, 12v to 220v (5kw) | unit | 1 | 2,500.00 | 2,500.00 |
| | Input voltage : 12v/24v | | | | |
| | Peak power : 5000watts | | | | |
| | Output Voltage: 110v/220v | | | | |
| 212 | Acrylic Paint, White | gal | 2 | 2,200.00 | 4,400.00 |
| | VSU-GOODS-24-06- Rebidding | | | | |
| 213 | 10 Amperes, Type K Fuse links, 10 pcs. per box | box | 10 | 4,000.00 | 40,000.00 |
| | 10 Amperes, Type K Fuselinks, 23" length, removable head, stainless steel strain wire and a silver copper fuse wire fuse element (ANSI, IEEE, NEMA certified) | | | | |
| 214 | 15 Amperes, Type K Fuselinks, 10 pcs. per box | box | 10 | 5,000.00 | 50,000.00 |
| | 15 Amperes, Type K Fuselinks, 23" length, removable head, stainless steel strain wire and a silver copper fuse wire fuse element (ANSI, IEEE, NEMA certified) | | | | |
| 215 | 25 Amperes, Type K Fuselinks, 10 pcs. per box | box | 10 | 6,500.00 | 65,000.00 |
| | 25 Amperes, Type K Fuselinks, 23" length, removable head, stainless steel strain wire and a silver copper fuse wire fuse element (ANSI, IEEE, NEMA certified) | | | | |
| 216 | 260 Watts Beam Lamp/Bulb | pc | 8 | 6,000.00 | 48,000.00 |
| | Replacement part for the existing 260 moving head lights | | | | |
| | YODN Light 260 watts Original Beam Lamp | | | | |
| | MSD 260R9, M60250-0007510 | | | | |
| 217 | 30 Amperes, Type K Fuselinks, 10 pcs. per box | box | 10 | 7,500.00 | 75,000.00 |
| | 30 Amperes, Type K Fuselinks, 23" length, removable head, stainless steel strain wire and a silver copper fuse wire fuse element (ANSI, IEEE, NEMA certified) | | | | |
| 218 | 8 amperes, Type K Fuse links, 10 pcs. per box | box | 10 | 3,500.00 | 35,000.00 |
| | 8 Amperes, Type K Fuselinks, 23" length, removable head, stainless steel strain wire and a silver copper fuse wire fuse element (ANSI, IEEE, NEMA certified) | | | | |
| 219 | 8 ways MCB distribution Box, surface type | pc | 5 | 1,000.00 | 5,000.00 |



| | | | | | |
|------------|---|-------------|-----------|------------------|------------------|
| | -High Quality, -waterproof | | | | |
| | -With free din rails and bush bar | | | | |
| 220 | AC Water Pump with Pressure Switch | pc | 1 | 15,000.00 | 15,000.00 |
| | <i>Fitted with an electronic pressure switch that starts and stops the pump as required when a tap is turned on or off. The pump is also protected against dry running.</i> | | | | |
| | <i>Motor connection: SINGLE PHASE</i> | | | | |
| | <i>Motor power (HP): 0.75</i> | | | | |
| | <i>Absorption at 230V (A)": 3.9</i> | | | | |
| | <i>Suction mouth: 1 "</i> | | | | |
| | <i>Delivery port: 1 "</i> | | | | |
| | <i>Body Pump</i> | | | | |
| | <i>Flow rate min. (l./min.): 5</i> | | | | |
| | <i>Max flow (l./min.): 60</i> | | | | |
| | <i>Min head (m.): 17</i> | | | | |
| | <i>Max head (m.): 48</i> | | | | |
| 221 | Chainsaw 11.5" attachment for 4" angle grinder | pc | 1 | 2,000.00 | 2,000.00 |
| | <i>Heavy duty and durable 11.5" chain saw</i> | | | | |
| | <i>Heavy duty blade protection</i> | | | | |
| | <i>Safety grip</i> | | | | |
| | <i>Heavy duty and durable chain blade cover</i> | | | | |
| | <i>Heavy duty and durable guide bar adapter</i> | | | | |
| 222 | Contact cleaner | pc | 12 | 600.00 | 7,200.00 |
| | ☑ <i>Anti-rust</i> | | | | |
| | ☑ <i>Wet-type Lubricant</i> | | | | |
| | ☑ <i>Spray-type</i> | | | | |
| | ☑ <i>Penetrating-type</i> | | | | |
| | ☑ <i>360ml/can</i> | | | | |
| 223 | Cross arm steel brace (V-shaped angle), Standard | pc | 20 | 2,000.00 | 40,000.00 |
| | <i>V-brace Steel Standard;</i> | | | | |
| 224 | Electric Motor, DC 12V, 200rpm | pc | 3 | 400.00 | 1,200.00 |
| | <i>Operating voltage: between 6 V and 18 V</i> | | | | |
| | <i>Nominal voltage: 12 V</i> | | | | |
| | <i>Free-run speed at 12 V: 250 RPM</i> | | | | |
| | <i>Free-run current at 12 V: 50 mA</i> | | | | |
| | <i>Stall current at 12V: 1200 mA</i> | | | | |
| | <i>Stall torque at 12V: 38 kg.cm</i> | | | | |
| | <i>Gear ratio: 1:35</i> | | | | |
| 225 | Electrical, Grounding Clamp (Galvanize) | pc | 15 | 120.00 | 1,800.00 |
| 226 | Electrical, PVC long sweep elbow, 3' x 90deg | pc | 20 | 340.00 | 6,800.00 |
| 227 | Knife Switch 225 ampere Double Throw 3 Phase | unit | 1 | 15,000.00 | 15,000.00 |
| 228 | LED Ceiling Mlni Chandelier Hanging Lights | set | 2 | 3,000.00 | 6,000.00 |
| | <i>LED Ceiling Mini Chandelier Hanging Lights with 2 square shape Nordic lamp fixture pendant lighting for Bedroom daylight</i> | | | | |
| 229 | Lever Block 1 ton | unit | 1 | 6,000.00 | 6,000.00 |
| | <i>Heavy Duty Lever Block 1 ton</i> | | | | |
| | <i>Chain Lifting & Tighting</i> | | | | |



| | | | | | |
|------------|--|-------------|-----------|------------------|------------------|
| | <i>Light weight and easy handling</i> | | | | |
| | <i>Durable</i> | | | | |
| 230 | Magnetic contactor with overload relay, 3Phase | pc | 3 | 6,000.00 | 18,000.00 |
| | ☑AC-1=Ith=20A Three Phase 220V/440V. 60Hz <i>Orange Line (Non-reversing)</i> | | | | |
| | ☑motor capacity: 220v- 4.7hp (3.5kw) 440v- 7.5hp <i>(5.5kw)</i> | | | | |
| | ☑operational current: 220v-13a/ 440v-12a | | | | |
| | ☑auxiliary contact: 1no+1nc | | | | |
| 231 | Manual Crimping Tool with Interchangeable Dies | unit | 1 | 43,000.00 | 43,000.00 |
| | <i>"D3" and "BG" Die Grooves/Inserts</i> | | | | |
| | <i>Designed to crimp range of overhead service entrance connections, splices and taps electrical wire for both aluminum & copper</i> | | | | |
| | <i>Heavy duty and durable</i> | | | | |
| | <i>ISO certified</i> | | | | |
| 232 | MCB Miniature Circuit Breaker, single pole, 20A, 220-230V | pc | 10 | 700.00 | 7,000.00 |
| | <i>-Good Quality</i> | | | | |
| | <i>-iC60N C 20A</i> | | | | |
| | <i>-Din Rail type</i> | | | | |
| 233 | Mini submersible Water Pump, DC 12V | pc | 2 | 1,000.00 | 2,000.00 |
| | <i>Ultra Quiet Mini DC Lift 5M Brushless Motor 12V Submersible Water Pump</i> | | | | |
| | <i>Specifications:</i> | | | | |
| | <i>Material: ABS</i> | | | | |
| | <i>Inlet: 4mm Threaded port</i> | | | | |
| | <i>Voltage: DC12V</i> | | | | |
| | <i>Power: 19W</i> | | | | |
| | <i>Maximum Rated Current: 1000MA</i> | | | | |
| | <i>Flow Rate: 800L/h(m3/h)</i> | | | | |
| | <i>Max Water Lift: 5 metre</i> | | | | |
| | <i>Working Environment Temperature: 1-60 °C</i> | | | | |
| | <i>Max Circulating Water Temperature: 100°C</i> | | | | |
| | <i>Noise: < 40 db (water) under operation</i> | | | | |
| | <i>Drive Mode: Electromagnetic</i> | | | | |
| | <i>Pump Shaft Position: Horizontal</i> | | | | |
| | <i>Impeller Structure: Open impeller</i> | | | | |
| | <i>Impeller Suction Method: one suction type</i> | | | | |
| | <i>Cable Line: 500mm / 19.69in</i> | | | | |
| | <i>Item Size: 77 * 65 * 42mm / 3.03 * 2.56 * 1.65in</i> | | | | |
| | <i>Package Weight: 220g / 7.76ounces</i> | | | | |
| | <i>Package Size: 80 * 70 * 50mm / 3.15 * 2.76 * 1.97in</i> | | | | |
| 234 | Oil Pump, 12V, 50L/min | pc | 1 | 5,000.00 | 5,000.00 |
| | <i>Waterproof switch designed, effectively prevent liquid erosion. Bionics handle designed, easy to handle, comfortable grip.</i> | | | | |
| | <i>power : 260W</i> | | | | |



| | | | | | |
|-----|---|-------|---|------------|------------|
| | Voltage: 12V | | | | |
| | Maximum flow: 50L | | | | |
| | used for: kerosene, diesel | | | | |
| 235 | Pipe Fittings, (G.I.) Flange, 3"Ø with bolt and nut | pc | 2 | 180.00 | 360.00 |
| | Schedule 40, Good Quality | | | | |
| 236 | Power Generator Equipment | pc | 1 | 250,000.00 | 250,000.00 |
| | Engine/ Driveline | | | | |
| | Fuel- Diesel | | | | |
| | Engine Cylinders: 4 | | | | |
| | Power Output: 24hp | | | | |
| | Model Year: 2023 | | | | |
| | Generator Capacity: 30KVA | | | | |
| | Net Weight: 680kg | | | | |
| | Voltage: 400 | | | | |
| | Color: Any Color | | | | |
| 237 | Propeller, stainless steel | pc | 2 | 1000.00 | 2,000.00 |
| | -Heavy Duty | | | | |
| | -Stainless S304 material | | | | |
| | -Solid Casted | | | | |
| | two blades | | | | |
| | OD 6 1/2" | | | | |
| 238 | Rubber gasket (sheet) 3mm x 4' x 20' | sheet | 1 | 5,000.00 | 5,000.00 |
| | Nitrile rubber good quality | | | | |
| 239 | Sliding Window, (1/4" thickness), 1.5m x 3.5m, with analok frame, bronze, with free installation | set | 1 | 17,000.00 | 17,000.00 |
| | With free installation; bronze colored glass and aluminium frame; | | | | |
| 240 | Sliding Window, (1/4" thickness), 1m x 0.60m, with analok frame, bronze, with free installation | set | 1 | 4,000.00 | 4,000.00 |
| | with free installation; colored bronze glass and frame; | | | | |
| 241 | Sliding Window, (1/4" thickness), 1m x 2m, with analok frame, bronze, with free installation | set | 2 | 9,000.00 | 18,000.00 |
| | With free installation; Colored bronze glass and frame; | | | | |
| 242 | Solar Battery ,12V, 100ah | unit | 2 | 8,160.00 | 16,320.00 |
| | Sealed 18650 Lithium ion battery pack | | | | |
| | long life deep cycle | | | | |
| | nominal voltage: 12.6 V | | | | |
| | nominal capacity: 100 Ah | | | | |
| | Size (body): 215 x 20 x 15 cm | | | | |
| | with charger cord | | | | |
| 243 | Solar charge controller 100amps | unit | 2 | 1,500.00 | 3,000.00 |
| | ☑Solar charge controller | | | | |
| | ☑Charge current: 100amps | | | | |
| | ☑Battery voltage: 12v/24v auto adapt | | | | |
| 244 | Solar powered Water Pump, DC 12V | set | 2 | 2,700.00 | 5,400.00 |
| | Voltage: 12V | | | | |
| | Power: 180W | | | | |
| | Max. flow rate: 1.5M ³ /H | | | | |



| | | | | | |
|-----|---|-------|----|----------|----------|
| | Max. head: 15m | | | | |
| | Outlet Size: 1 Inch | | | | |
| | Good quality, durable | | | | |
| 245 | Stainless Steel Plate, (6mm) 4' x 8' | sheet | 1 | 8,500.00 | 8,500.00 |
| | good and standard quality stainless | | | | |
| 246 | Surge Arrester, 230V,Max 125A gL, iPRD Neutral, iPRD 8-350 | pc | 5 | 1,800.00 | 9,000.00 |
| | -high quality | | | | |
| | Din rail type | | | | |
| | Surge Protection | | | | |
| 247 | Terminal Lug, 240 mm2 | pc | 10 | 700.00 | 7,000.00 |
| 248 | Access Valve Charging Line for Refrigeration and Airconditioning | pc | 10 | 55.00 | 550.00 |
| 249 | Solenoid Valve, 1/2" NPS, Brass | pc | 2 | 600.00 | 1,200.00 |
| | Working Liquid Pressure: 0 Mpa - 1.0 Mpa (140 PSI) | | | | |
| | Working Temperature: -5°C - 80 °C | | | | |
| | Actuating life: ≥ 50 million cycles | | | | |
| | Actuating voltage: 12VDC | | | | |
| 250 | Solenoid Valve, Normally close, DC 24V | pc | 4 | 600.00 | 2,400.00 |
| | Normally closed | | | | |
| | 24V DC | | | | |
| | Power: 4.8W | | | | |
| | Water pressure: 0.02-0.8MPa | | | | |
| | Nominal diameter: 4 point double thread, outlet diameter 13 (mm) | | | | |
| | G1/2 Brass Electric Solenoid Valve Normally Closed Water Inlet Switch | | | | |
| 251 | Temperature Controller, Digital PID | set | 2 | 1,500.00 | 3,000.00 |
| | Measuring accuracy: +/-0.5%FS | | | | |
| | Cold-end compensation tolerance: +/-2 Celsius (can be modified by software in 0~50 Celsius) | | | | |
| | Resolution: 14 bit | | | | |
| | Sampling cycle: 0.5 Sec | | | | |
| | Power : AC 100-240V 50/60HZ | | | | |
| | Process value (PV), Setting value (SV) | | | | |
| | PIN control (including ON/OFF, step-type PID and continuous PID) | | | | |
| | Self-tuning control | | | | |
| | Relay output: contact capacity 250V AC 3A (resistive load) | | | | |
| | Proportional band (P): 0~full range (ON/OFF control when set to 0) | | | | |
| | Detective temperature range: 0 to 400 Celsius | | | | |
| | Insulation resistance: more than the 50M ohm(500V DC) | | | | |
| | Insulation resistance : 1500V AC/min | | | | |
| | Insulation resistance : Power Consumption Less than 10 VA | | | | |



| | | | | | |
|-----|---|-------|----|---------------|---------------------|
| | Service environment: 0~50 Celsius | | | | |
| | environment with no corrosive gas 30~85% RH | | | | |
| | Aluminum Alloy Heat Sink | | | | |
| 252 | Paint, TTC, Ultramarine Blue, Latex | liter | 50 | 500.00 | 25,000.00 |
| | Premium Quality | | | | |
| 253 | Pipe Fittings, (PVC) Saddle Clamp, 4"Ø x 1"Ø | pc | 2 | 350.00 | 700.00 |
| | Schedule 40, Good Quality | | | | |
| 254 | Hose | set | 1 | 2,500.00 | 2,500.00 |
| | garden, 1/2 inch with spray nozzle and solid brass connector, green, 50 m | | | | |
| 255 | Saw, Crosscut, 18"(wooden handle) | pc | 1 | 700.00 | 700.00 |
| | | | | TOTAL: | 4,569,765.00 |

DILBERTO O. FERRAREN
BAC Chairman