

PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

Supply and Delivery Office Equipment (VSU-GOODS-24-22)

Government of the Republic of the Philippines

March 13, 2023; 9:00 AM BAC Conference Room, VSU Market, Visca, Baybay City, Leyte and via Zoom

> Sixth Edition July 2020



Table of Contents

Glossa	ry of Acronyms, Terms, and Abbreviations	3
Section	ı I. Invitation to Bid	6
Section	II. Instructions to Bidders	26
1.	Scope of Bid	27
2.	Funding Information	27
3.	Bidding Requirements	27
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	27
5.	Eligible Bidders	27
6.	Origin of Goods	28
7.	Subcontracts	28
8.	Pre-Bid Conference	28
9.	Clarification and Amendment of Bidding Documents	28
10.	Documents comprising the Bid: Eligibility and Technical Components	28
11.	Documents comprising the Bid: Financial Component	29
12.	Bid Prices	29
13.	Bid and Payment Currencies	30
14.	Bid Security	30
15.	Sealing and Marking of Bids	30
16.	Deadline for Submission of Bids	30
17.	Opening and Preliminary Examination of Bids	31
18.	Domestic Preference	31
19.	Detailed Evaluation and Comparison of Bids	31
20.	Post-Qualification	32
21.	Signing of the Contract	32
Section	ı III. Bid Data Sheet	33
Section	IV. General Conditions of Contract	35
1.	Scope of Contract	36
2.	Advance Payment and Terms of Payment	36
3.	Performance Security	36
4.	Inspection and Tests	36
5.	Warranty	37
6.	Liability of the Supplier	37
Section	V. Special Conditions of Contract	38
Section	VI. Schedule of Requirements	43
Section	VII. Technical Specifications	60
Section	VIII. Checklist of Technical and Financial Documents	78



Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF - Cost Insurance and Freight.

CIP – Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."



DTI – Department of Trade and Industry.

EXW - Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project— Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC – Government-owned and/or –controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national



buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC - Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.



Section I. Invitation to Bid



INVITATION TO BID FOR SUPPLY AND DELIVERY OF OFFICE EQUIPMENT

1. The *Visayas State University* through the *GF*, *STF*, *TF* 2024 intends to apply the sum of *Three Million Seven Hundred Fifty Thousand Pesos* (*PhP* 3,750,000.00) being the ABC to payments under the contract for *Supply and Delivery of Office Equipment* (*VSU-GOODS-24-22*). Bids received in excess of the ABC shall be automatically rejected at bid opening.

The *Visayas State University*, through the *GF*, *STF*, *TF* 2024 intends to apply the following ABC per item to payments under the contract for each item, to wit:

Item No.	Description	Unit	Qty	ABC/Unit (Pesos)	Total ABC (Pesos)
1	18" STAND FAN	pcs	11	2,500.00	27,500.00
	Product Overview				
	Reliability (Motor Life)				
	Performance: 7,000 hours				
	Energy Efficient				
	Less Power Consumption				
	Energy Savings up to 10% with the new motor				
	vs. Existing				
	New Modern Design				
	Elegant Design				
	New Modern "Minimalist" Design				
	Warranty				
	Parts: 1 year				
	Labor: 1 year				
	Motor Warranty: 3 Year				
	General Specifications				
	Blade Material / Size, cm: PP / 40				
	Wattage (W, Max): 60				
	RPM (Max): 1350				
	Air Delivery (\M3/min. Max): 119				
	Max Center Height, mm: 1,197				
	Height Adjustment: Free Stop Mechanism				
	Stroke, mm: 150				
	Switch Type: 3 Speed Piano Switch				
	Vertical Angle Adjustment: Free Neck				
	Oscillation: Double				
	Color: Black				
2	18" Wall Mount Oscillating Hydroponic- Clarify Fan	рс	20	2,500.00	50,000.00
	Keeps room and leaf temperatures down				



	Smooth and quiet operation				
	90° oscillating action				
	Pull to change speed and Pull for oscillating or				
	one position.				
	Assembly required				
3	2 BURNER GAS STOVE	рс	3	2,000.00	6,000.00
	■Heavy duty gas stove				
	■High quality fuel-efficient burner				
	■Durable metal gas ignition controls				
	■Stainless metal gasket and body				
	■Auto-ignition burner				
	■# of burners: 2				
	■Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches				
	■Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches				
	■Space in between outer rings: 20cm 7.9 inches				
	Color: silver				
	■Warranty: 1 year				
4	Air Condition, Split type, Inverter, 1.5 HP	set	6	45,000.00	270,000.00
	Wattage: 1250 Watts				
	EER Rating: 14.26				
	WindFree Technology				
	Digital Inverter Boost				
	Fast Cooling				
	Cooling capacity: at least 12,500 kj/hr				
	Easy Filter Plus				
	DuraFin				
	Triple Protector Plus				
	Quiet Mode				
	Single User Mode				
	R32 Refrigerant				
	12x Tapping Screw				
	4x Rubber Foot (Outdoor Package)				
	2x Remote Control Batteries				
	Mounting Bracket				
	wall mounted				
	EER rating above 10				



	with remote control				
	with one year warranty on parts and services				
	with free installation				
5	Air Condition, Split type, Inverter, 2.0 HP	set	2	55,000.00	110,000.00
	■Cooling capacity: at least 18,500 kj/h			00,000.00	110,000.00
	■wall mounted				
	■EER rating above 10				
	with Quiet Mode				
	with remote control				
	with Anti bacterial air filter				
	with Micro Dust Filter				
	with at least 10 years compressor warranty				
	offer must be in the market for at least 10				
	years				
	with at least 10-Year Warranty on Compressor				
	with one year warranty on parts and services				
	with free installation				
6	Aircon Split Type (1.5 HP)	unit	4	49,000.00	196,000.00
	Dimensions	gara t	<u> </u>	10,000100	100,000100
	Net Dimensions (W x H x D):				
	Indoor - 779mm x 290mm x 209mm				
	Outdoor - 780mm x 542mm x 289mm				
	Gross Dimensions (W x H x D):				
	Indoor - 861mm x 364mm x 255mm				
	Outdoor - 891mm x 603mm x 396mm				
	Power Requirements:				
	230 V				
	Power Consumption:				
	750 W				
	General Specifications				
	Remote: Yes				
	Timer: Yes				
	Cooling Capacity: 11,020 kj/h				
	Control Type: With remote				
	Cooling Area (sq. meters): Survey is				
	recommended				
	Noise Level (Indoor) – Low: 28dB				
	Filter: Yes				
	Airflow Direction Control (Up & Down):				
	Automatic				
	Airflow Direction Control (Left & Right): Manual				
	Temperature Control: With remote				
	Fan Speed: 5 Speed Level				
	Energy Efficiency Ratio: 14.69				
	with free installation				
7	Aircon Split Type 2.5 HP Inverter , With	11254	A	59 000 00	222 000 00
7	Installation	unit	4	58,000.00	232,000.00



	0 " 0 5 ! ! D				
	Capacity: 2.5HP				
	Power Supply: 220,230,60,1 V, Hz, Ph				
	Cooling Capacity: 24,000 Btu/h				
	Cooling Input: 2,000W				
	Cooling Current: 8.7A				
	EER: 12.7				
	Indoor Unit				
	Air Flow (Hi/Mi/Lo): 1063x955x759 m3/h				
	,				
	Noise Level (Hi/Mi?Lo): 50/–/40 dB (A)				
	Unit Dimension (W*D*H) : approx.				
	1080x336x326mm (Indoor Unit)				
	Outdoor Unit				
	Compressor Type: Rotary				
	Unit Dimension (W*D*H) : Approx.				
	845x363x702mm (outdoor unit)				
	Application Area: 29-43sqm	_			
	One (1) year warranty on parts and service five				
	(5) years on compressor provided that the unit				
	is installed by accredited installation team				
	With Free installation				
8	Aircon, Split Type, 1HP (Inverter)	unit	3	44,000.00	132,000.00
	Features:	•		11,000100	102,000100
	* High-density Dust Filter				
	* Smooth Frequency Control				
	* Gold Fin Protection				
	* Silver Ion Filter				
	* Sleep Mode				
	* Turbo Mode				
	* Louver Position Memory				
	* Fast Cooling				
	*with remote control				
	Specifications:				
	* 1.0HP Inverter				
	* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)				
	* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)				
	* 700 (290-990) Power Input (W)				
	* 4.32 CSPF				
	* R32 Refrigerant				
	* 39.5/34/32 dB (A) Sound Level (H/M/L)				
	1 year warranty				
	• •			+	
	l with tree installation				
0	with free installation	no	2	20 000 00	160 000 00
9	Airconditioning Unit	рс	2	80,000.00	160,000.00
9	Airconditioning Unit Split Type, Air-conditioning Unit with 2.5 HP	рс	2	80,000.00	160,000.00
9	Airconditioning Unit Split Type, Air-conditioning Unit with 2.5 HP Remote control with 24 hours programmable	рс	2	80,000.00	160,000.00
9	Airconditioning Unit Split Type, Air-conditioning Unit with 2.5 HP Remote control with 24 hours programmable timer ON/OFF	рс	2	80,000.00	160,000.00
9	Airconditioning Unit Split Type, Air-conditioning Unit with 2.5 HP Remote control with 24 hours programmable	рс	2	80,000.00	160,000.00



	FFD /min mayl: approx 1/17 /16/12/12/61			1	
	EER (min-max): approx. 14.17 (16.12-12.61) kJ/hW,				
	,				
	Voltage: 230 V				
	Current: approx. 6.9 A				
- 10	with free installation			44 500 00	
10	Bottom Loading Water Dispenser	рс	2	14,500.00	29,000.00
	Product Model: JD-8044				
	Voltage/frequency: 220V~50Hz				
	Cooling Power: 75W				
	Heating Power Warm & Hot: Rated Power: 425W, Heating Power: 425W				
	Cold & Hot: Rated Power: 500W, Heating Power: 425W				
	Carton Size: 355x325x1040mm				
	Actual Product Size: 320x285x980mm				
11	Hot Water Temperature: 85 - 95 Degree Celsius DEEP FREEZER	uni4	1	30 000 00	30,000.00
	©DEEP FREEZER ©DEEP FREEZER 13 CUBIC FEET CHEST	unit	ı	30,000.00	30,000.00
	FREEZER 13 CUBIC FEET CHEST				
	■ WIRE BASKET SHELVING MATERIAL,				
	approx. 216 WATTS; NO FROST; WITH				
	INVERTER				
	© CHARCOAL DEODORIZER. 220V or auto				
	voltage				
12	Dehumidifier for Extra Large Rooms and Basements	рс	1	19,300.00	19,300.00
	Includes: Washable Filter, Built-in Handles and				
	Wheels, Drain Hose Outlet				
	Weight: at most 40 lbs				
	Rated Current: approx. 4.7 Amps				
	Moisture Removal: 70 pints per day				
	Air CFM Range (cubic feet per minute): 165				
	(Normal) to 188 (Turbo)				
	Removable Water Tank Capacity: at least 1.6				
	gallons / 6 liters				
	Certifications: UL & Energy Star rated				
	Features: Touch Control Panel; Auto Restart,			1	
	Shut Off, Defrost; Turbo Mode; Continuous				
	Dehumidifying; 24-hour Timer; Custom Humidity				
	Level from 35% to 85%				
	Spaces between 2500 and 4000 square feet,				
	with room temp from 41°F to 95°F				
	Power: 220/240V				
13	Digital Duplicator Machine, Copy printer, 300x600 DPI printing	set	1	150,000.00	150,000.00
	Master Making/Printing Methods: High-speed				
	digital master-making/Fully automatic printing				
	Scanning: 600 dpi × 600 dpi				
	Printing: 300 dpi × 600 dpi, Quick Master			+	
1	i mining. 500 upi ^ 000 upi, Quick iviaster				



	Making mode: 300 dpi × 400 dpi				
	, ,				
	Maximum Scanning Area: 297 mm × 432 mm				
	Print Paper Weight: 46 gsm to 157 gsm				
	Print Paper Size: 100 mm × 148 mm to 310 mm				
	× 432 mm				
	Maximum Printing Area: 210 mm × 357 mm				
	Paper Feed Tray Stacking Capacity: 1000				
	sheets*2, stacking height of 110 mm or lower				
	Paper Receiving Tray Stacking Capacity: 1000				
	sheets*2, stacking height of 110 mm or lower				
	Print Speed: 5 levels: 60, 80, 100, 120 and 130				
	ppm				
	Functions: Original Scanning mode, Scanning				
	Level, Enlargement/Reproduction, Dot Process,				
	2-Up, Book, Ink Saving, Quick Master Making,				
	ADF-Semi-Auto*3, Speed, Density, Print Position, Program A/B, Job Separation*3, Idling,				
	Confidential, Meter Display, Count Report				
	Output, Proof, Direct Printing, USB Flash-via-				
	Printing, Auto Sleep Setting, Auto Power-OFF				
	Setting, ECO mode, RISO iQuality System				
	Ink Supply: Full automatic (1000 ml/cartridge)				
	Dry Seal, Customized Machine Engraved,				
14	Stainless Steel Material	unit	2	4,000.00	8,000.00
15	Electric fan	рс	8	2,500.00	20,000.00
	■Stand fan 16" metal blade				
	■Adjustable height				
	■three speed controller				
16	Floor Standing Mounted Airconditioner	unit	4	80,000.00	320,000.00
	■At least 4.0HP				
	■Energy Saving Compressor, 3D Air Delivery				
	System				
	■with Sleep Mode				
	■with Auto On / Off Timer				
	■with High Efficiency Air Filter				
	with Remote Control				
	■Air Conditioner Rated Capacity (BTUs) at				
	least 2.5				
17	Gas Stove, 4 Burners, Heavy Duty	unit	1	15,000.00	15,000.00
	4 Gas Burners				-
	Rust Proof				
	Black Enamel Pan Support				
	0.5mm Painted cold-rolled steel Side panel				
	0.4mm Stainless Steel Surface				
	Whirlwind Burner				
	90mm Double / 40mm / 90mm Double burner /				
	1 90MM Double	1			
	90mm Double Cast Iron Burner with Stainless Steel Burner				



	Cover				
	Automatic Ignition				
	Save Gas More than 30%				
	Quantity: 1set				
	Net Weight: 7.2kg				
	Unit Dimension: 480x570x125mm				
18	Wet and dry vacuum cleaner, 10L	рс	1	5,000.00	5,000.00
	Power input: 1000W	, , , , , , , , , , , , , , , , , , ,	<u> </u>	3,000.00	
	Airflow: 35l/s				
	Capacity: 10 Liters or 3 Gallons				
	Cord Length: 3m				
	4 in 1 application: wet, dry, indoor & outdoor				
	Strong handle for easy carrying				
	Large switch button with waterproof design for				
	safe & easy operation				
	Comes with complete accessories				
19	Heavy Duty Combo Binding Machine	unit	1	18,000.00	18,000.00
	ΦSpecs:		<u>-</u>	1,111111	-,
	■Maximum Punching Sheets: 25				
	■Max Size: LS, F4, A4, Extra Long				
	Selectable Punching Pins: 24 slots				
	■Net Weight: 12.5kgs				
20	Heavy Sheetfed Scanner	рс	1	48,000.00	48,000.00
	Technology			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,
	Scanner Type: Sheetfed Scanner				
	Optical Resolution (ADF): 600 DPI x 600 DPI				
	(Horizontal x Vertical)				
	Optical Resolution: 600 DPI x 600 DPI				
	(Horizontal x Vertical)				
	ADF Minimum Document Size: 50.8 mm x				
	50.8 mm (Horizontal x Vertical)				
	ADF Maximum Document Size: 215.9 mm x				
	6,096 mm (Horizontal x Vertical)				
	Paper Formats				
	A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6				
	(10.5x14.8 cm), B6 (12.5x17.6 cm), B5				
	(17.6x25.7 cm), B4 (25.7x36.4 cm), Letter,				
	Legal, Postcard, Business cards, Plastic cards			+	
	Scanning color depth				
	Input: 30 Bits Color / 10 Bits Monochrome ,				
	Output: 24 Bits Color / 8 Bits Monochrome Ultrasonic Sensor: Yes			+	
				+	
	High Capacity, General Office Scanner			+	
	Light Source: ReadyScan LED technology				
	Output Resolution:1200 DPI			+	
	Scanning Speed			+	
	Monochrome: 65 pages/min -				



	Color CE naggar/min managered with Circ. Ad				
	Color: 65 pages/min measured with Size: A4 ,				
	Resolution: 200 / 300 dpi,				
	Monochrome: 130 image/min -				
	Color: 130 image/min measured with Size: A4, Resolution: 200 / 300 dpi				
	'				
	Paper / Media Handling				
	Paper Setting Capacity:100 Sheets				
	Auto loading: 27 - 413 g/m²				
	Automatic Document Feeder Type				
	Single pass dual scanning				
	Reliability Daily Duty Cycle: 7,000 pages				
	Automatic Document Feed:100 pages				
	Duplex Scan:Yes				
	Scanning Features				
	Output formats:BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG				
	File compression features:Hardware JPEG compression, TIFF Compression (JPEG(7),				
	CITT G4, LZW), PDF Compression				
	Advanced document integration: Scan to Email,				
	Scan to FTP, Scan to Microsoft SharePoint®,				
	Scan to Print, Scan to Web folders, Scan to				
	Network folders				
	Scanning Volume:7,000 Pages per day				
	Connectivity				
	,				
	Interfaces: USB 2.0 Type B, USB 3.0 Type B				
21	Options: Roller Assembly Kit		c	44 500 00	07 000 00
	Hot & Cold water dispenser	unit	6	14,500.00	87,000.00
	Bottom load water dispenser Towards: List Cold and Normal water.				
	■3 Faucets: Hot, Cold and Normal water				
	function				
	■3-Push Button dispensing control				
	■ Anti-scald safety lock switch				
	■Child Lock Safety feature on Hot Water Forest				
	Faucet				
	■ Floater indicator to avoid water overflow				
	©Capacity: Hot - 1.2 Liters, Cold - 3.5 liters,				
	Power Rating: Hot - 420 watts, Cold - 100				
22	watts, R134a Laminator	no	4	5,000,00	E 000 00
		рс	1	5,000.00	5,000.00
23	A4 Hot and Cold Laminating Machine Microwave Oven	1110;4	1	15,000.00	15 000 00
23		unit	ı	15,000.00	15,000.00
	Capacity: 32 litres				
	Dimension: 517 x 297 x 384mm				
	Power source: 220V / 60Hz				
	Power Consumption: 1500W				
24	Mirrorless Camera, 24.1MP, 3" LCD Monitor, 4K Video	unit	1	54,000.00	54,000.00



A.E. A.A. O.C. O. O. O. A.E. O. A.E. O. O. O. O. O. O. O.	1	
AF Modes - Stills: One-Shot AF, Servo AF,		
Manual Movie recording: One-Shot AF, Movie		
Servo AF, Manual		
AF Point Selection - Automatic selection,		
Manual selection		
AF System Points - Stills: Max. 3975 selectable		
AF point positions / Up to 143 zones (auto		
selection)		
Movie recording: Max. 3375 selectable AF point		
,		
positions / Up to 117 zones (auto selection)		
Built-in Flash		
Closest Focusing Distance (cm) - 25		
Continuous Shooting Speed (Shots Per Sec)		
(Up To) - 10 (One-Shot AF) / 7.4 (Servo AF)		
Digital Zoom - Approx. 3-10x (for movie		
recording only)		
Drive System - Stepping Motor-driven lead		
screw + rack system		
Effective ISO - Stills: 100 - 25,600 (H:51,200),		
Movie (full HD/HD): 100 - 12,800 (H: 25,600),		
Movie (4K): 100 - 6,400		
Exposure Compensation - ±3 stops in 1/3-stop		
increments, AEB: ±2 stops in 1/3-stop		
increments		
Eye Detection AF - One-Shot AF / Servo AF /		
Movie Servo AF		
Flash Modes - E-TTL II Autoflash, FE Lock,		
Manual pop-up, Retractable, Built-in		
Focal Length (35mm Equivalent) - 24 -		
72mm(3x)		
Guide Number ISO 100 metres - 5		
Image Resolution - 6000 x 4000 (L), 3984 x		
2656 (M), 2976 x 1984 (S1), 2400 x 1600 (S2),		
6000 x 4000 (RAW/C-RAW)		
Image Stabilizer - Stills: Lens shift type, Movie		
recording: Lens shift type & In-body 5-axis		
, ,		
electronic image stabilization (movie recording		
only)		
with Manual Focus		
Memory Card Type - SD, SDHC*, SDXC*,		
*UHS-I cards compatible		
Metering Mode - Stills: Evaluative, Partial, Spot,		
Center-weighted average, Movie: Evaluative		
(when faces are detected with		
[Face+Tracking]), Center-weighted average		
(when no faces are detected)		
Processor Type - DIGIC 8		
Sensor Size - APS-C		
Shooting Modes - Stills: Scene Intelligent Auto,		



	11111 4 1 0 11				
	Hybrid Auto, Special scene modes (Self				
	Portrait, Portrait, Smooth Skin, Landscape,				
	Sports, Panning, Close-up, Food, Night Portrait,				
	Handheld Night Scene, HDR Backlight Control,				
	Silent Mode), Creative filters (Grainy B/W, Soft				
	focus, Fish-eye effect, Water painting effect,				
	Toy camera effect, Miniature effect, HDR art				
	standard, HDR art vivid, HDR art bold, HDR art				
	embossed), Program AE, Shutter-priority AE,				
	Aperture-priority AE, Manual Exposure, Movie				
	recording: Movie auto exposure, Movie manual				
	exposure				
	Shutter Speed Range (Sec.) - Stills: 30 -				
	1/4000, Bulb, Movie recording: 1/25 - 1/4000				
	(PAL) or 1/30 - 1/4000 (NTSC)				
	Standard Power Supply - LP-E12				
	Silent Shutter - Available: Single Shot				
	Still Image Format - JPEG, RAW, RAW +				
	JPEG, C-RAW, C-RAW+JPEG				
	Viewfinder Coverage (Approx.) - 100%				
	Viewfinder Type - 0.39-inch OLED, 2.36million				
	dots, 59.94fps refresh rate				
	White Balance - Auto (Ambience priority), Auto				
	(White priority), Preset (Daylight, Shade,				
	Cloudy, Tungsten light, White fluorescent light,				
	Flash), Custom, Color temperature setting				
	(approx. 2500-10000 K), White balance				
	correction and white balance bracketing				
	features provided, *Flash color temperature				
	information transmission possible				
	X-sync (sec.) - 1/200				
25	Paper shredder machine, heavy duty	рс	1	12,000.00	12,000.00
	■Shred Type: Cross Cut	po		12,000.00	12,000.00
	,				
	■Maximum Sheet capacity(70gsm): 10 Sheets				
	■Waste Container capacity: 21 Liters				
- 00	■Power Source: 220 - 240 VAC	.,	4	0.000.00	0.000.00
26	Photography Camera Tripod, Lightweight	unit	1	3,000.00	3,000.00
	Compatible with Mirrorless Camera (Canon,				
	Nikon, Fuji, Pentax, etc.)				
27	Portable Trolley 15" Speaker with wireless	unit	2	10,000.00	20,000.00
	microphone		_	10,000.00	_3,000.00
	■15" 2 Way 480 Watts Powered Portable				
	Sound System				
	■Plastic Cabinet				
	■AC220V or DC12V (With built-in				
	Rechargeable Batteries)				
	■With 2 Wireless Microphone				
	■ With 2 Mic Input (1 XLR, 1 PL55)				
	■With FM Radio, Bluetooth, Guitar Input				
	vvilli rivi radio, didelootti, Guitai Input				



	(Shared with Mic 2 input), USB & SD Port				
	■With 5 Band Equalizer and LCD Display				
	■With Aux / Line In and Line Out				
	With Remote Control, Handle and Wheel				
28	Refrigerator	unit	1	25,000.00	25,000.00
	uses a compressor or evaporator to circulate	Cinc		20,000.00	20,000.00
	cooled air or water around the samples				
	7 cu. ft. HD Inverter No Frost Refrigerator				
	Bottom Freezer				
	Heavy Duty Inverter				
	Energy Efficient Compressor				
	Triple Bottom Freezer Drawers				
	Fresh Zone Drawer (Crisper)				
	Independent Temparature Control for Fridge				
	and Freezer				
	Recessed Handle				
	Stainless Steel Finish				
	Net Weight: 52kg				
	Gross Weight: 57kg				
	Gross Dimension (h:w:d): 166:55:64 cm				
29	Refrigerator	unit	1	31,000.00	31,000.00
	Transparent door , Upright at least 10 to 12.4 Cubic Feet inverter				
	Transparent Anti Frost Double Layered				
	Tempered Glass Door				
	Adjustable Shelves				
	Efficient Cooling				
	Interior Lights				
	Input 220/240V, 50/60 Hz with power cord &				
	plug				
	Automatic voltage stabilizer with time delay				
	restart				
30	Refrigerator- at least 6.0 cu.ft. (Two-door) inverter	рс	1	17,000.00	17,000.00
	■Two-Door Direct Cool Refrigerator				
31	Smart TV, 70" with Android 10 OS	unit	1	50,000.00	50,000.00
	■4K Ultra HD			, i	·
	■Borderless Design				
	© Chameleon Extreme				
	■Picture Engine				
	■Dolby Digital Plus with 12x12w				
	■Android 10.0 Q				
	■Bluetooth 5.0				
	■Audio: Dolby Digital Plus			†	
	■DTS TruSurround			+	
	©Equalizer				
	■Quad-Core				
	■ Internal Memory: 8GB			+	
	■IIIIGIIIGI WIGIIIOI Y. UGD				



	■RAM: 2GB				
	■With Voice Search				
	■Google Assistant				
	© Chromecast Built-in or Wireless Display				
	■Wi-Fi Connectivity 2.4G				
	©2T2R				
	■Android 10.0				
	■Bluetooth 5.1				
	■Display Panel: LED				
32	Laminator Machine, A3	unit	2	5,000.00	10,000.00
	■Heavy Duty, for A3 & A4 size, infrared heating			5,00000	,
	system and adjustable temperature control with				
	overheating protection				
33	Aircon, Window Type, 2HP Inverter	unit	3	60,000.00	180,000.00
	2.0 HP, Inverter Window Type				
	R32 Refrigerant				
	High Energy Efficiency Ratio				
	All-DC Motor				
	Room Temperature Display & Setting				
	Air Swing Control				
	Filter Clean Indicator				
	Power Source 230, 60, 1Ø (V, Hz, Ph)				
	Cooling Capacity 18,750 (kJ/h)				
	Current 7.3 (A)				
	Input Power 1563 (W)				
	EER Rating 12.0 (kJ/hW)				
	Recommended Floor Area 23 – 33 m ²				
	Moisture Removal 2.8 (L/h)				
	Noise Level Indoor (dB-A) 51 / 48 (H / L)				
	Air Circulation (indoor) 14.2 m3/min				
	Air Circulation (outdoor) 23.0 m3/min				
	Timer (12-Hour On/Off)				
	Fan Speed				
	Auto / Cool / Dry Mode				
	Powerful mode				
	Sleep Mode				
	Quiet Mode				
	Blue Fin Condenser (anti-corrosion fin)				
	Anti-Bacterial Filter				
	Wireless Remote Control				
	Random Auto Restart				
34	Aircon Split Type (2 HP)	unit	2	45,000.00	90,000.00
	Capacity: 2.HP				
	Power Supply: 220,230,60,1 V, Hz, Ph				
	Cooling Capacity: 18,000 Btu/h				
	Cooling Input: 1552W				
	Cooling Current: 6.75A				



	EED 40.04			1	
	EER: 12.24				
	Air Flow (Hi/Mi/Lo): 848x796x626m3/h				
	Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)				
	Unit Dimension (W*D*H) : 965x203x323mm				
	(Indoor Unit)				
	Refrigerant Type: R32				
	Compressor Type: Rotary				
	Unit Dimension (W*D*H) : 914x343x546mm (
	outdoor unit)				
	Application Area: 23-33 sqm				
	Accesories such as breaker, bracket and				
	copper tubbing not included				
	One (1) year warranty on parts and service &				
	compressor				
	with free installation				
35	Aircon, Window Type, 1.0HP (Inverter)	unit	21	35,000.00	735,000.00
33	1HP Inverter, 8-in-1 Filter, R410A	unit	<u> </u>	33,000.00	1 33,000.00
	Energy Savings Feature:				
	24-hour Timer				
	Energy Saving Plug				
	Econo and Sleep Mode				
	EER Rating: 11.6 (10.8 - 10.7)				
	Sleek, Modern Aesthetic				
	Remote Control				
	2 x AAA Batteries				
	With Free Installation				
	1 year warranty				
36		pc	1	10.000.00	10.000.00
				1,111111	
	Š				
	, , ,				
27	, ,	201	4	55 000 00	EE 000 00
31		Set	<u>I</u>	55,000.00	55,000.00
	Type:Portable PA System				
	· ·				
	•				
	·				
	·				
	1 ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '				
	USB:1 x Type A (ULM wireless ready)				
	Bluetooth: Yes				
	Total Power:500W				
	E D FOLL 00111				
	Frequency Response:50Hz-22kHz			1	
36	2 x AAA Batteries With Free Installation 1 year warranty Water Dispenser, Cabinet type ■Floor standing ■Hot and cold function ■plastic body,high efficiency compressor ■thermally protected Sound System Type:Portable PA System Speaker Drivers:1 x 8" woofer, 1.35" compression driver Number of Mixer Channels:6 Number of Mic Preamps:2 EQ:Treble, Bass, 5-band Graphic Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in) Outputs:2 x 1/4" (speaker out) USB:1 x Type A (ULM wireless ready) Bluetooth:Yes Total Power:500W	pc set	1	55,000.00	55,000.00



	Power Source:Standard IEC AC cable				
	Height: 25.9"				
	Width:13.9"				
	Depth:34.8"				
	Weight:44.7 lbs.				
38	Sliding Paper Cutter	unit	1	2,550.00	2,550.00
	Working Area: A3 and A4				
	Cutting Capacity: 16 sheets				
	Packing Weight: 5 kg				
	Material: Metal				
	Available Size: A3 and A4				
	Packing Measurement: 56x34x11 cm				
	Other Specifications: Heavy duty for Vinyl,				
	Cardboard Paper				
20	Sony Electret Condenser Microphone for		4	7 000 00	7 000 00
39	lapel mic (for compatibility)	рс	1	7,000.00	7,000.00
	3.5 mm connector				
40	Vacuum cleaner, wet and dry, 1200 watts	unit	1	13,000.00	13,000.00
	1200 Watts power				
	At least 30L dust/liquid capacity				
	Double stage long life motor				
	With auto shut-off function				
	With blower function				
	Washable ecological HEPA filter				
	At least 3 meters flexible hose				
	At least 9 meters power cord length				
	With handrail/handle for easy transport				
	Accessories:				
	Extension tube				
	Bristle brush				
	Crevice nozzle				
	2-in-1 brush and round brush				
	Floor/carpet brush				
	Wet/dry floor brush				
	Washable HEPA filter				
	Flexible extension tube				
41	Microwave Oven, Digital, Non-Inventer, 13 Power Levels	рс	1	14,000.00	14,000.00
	■30 Liters capacity				
	■Grill and convection				
	■ electronic control				
	■dual wave system				
	■13 power levels				
	■900W				
	■Non-Inventer				
42	Hot and Cold Table Top Water Dispenser	unit	1	4,000.00	4,000.00
	Table top water dispenser				



	Hot and cold				
	Electronic type cooling				
43	Television, Smart	рс	3	18,000.00	54,000.00
	32 inch television, Smart				
	Resolution: 1,366 x 768				
	HDMI Ports: 2				
	USB Ports: 1				
	Power Supply: AC100-240V 50/60Hz				
	Set Size with Stand (WxHxD): 732.9 x 462.8 x 163.7 mm				
	Set Size without Stand (WxHxD): 732.9 x 440.3 x 78.5 mm				
44	Cordless Kettle	unit	16	1,200.00	19,200.00
	Electric Glass Kettle, Cordless				
	HWK-118GI				
	Power: 230V - 60Hz, 2000W				
	Capacity: 1.8L				
	360 degree rotary base, easy to use with high borosilicate glass body,				
	Durable and stain resistant blue LED light				
	indication when boiling Concealed stainless				
	steel				
	heating element Automatic one button cover				
	starter boiling dry protection Automatically				
	turns off when water boiled.				
45	Active Speaker, 12", 1000W peak two-way, full range	unit	1	33,000.00	33,000.00
	-1000 watts(peak) 500 watts (program)				
	-Superior DSP processing with component protection				
	-12-inch woofers with 2.5-inch voice coils				
	-1-inch HF compression drivers				
	-90 x 60 deg. HF dispersion				
	-Dual purpose full-range and wedge monitor speaker				
	-Ultra-clear reproduction throughout the whole				
	audio bandwidth				
	-Recessed control panel				
	-Master Level control with activity indicator (
	cabinet level adjustment)				
	-3 performance modes, concert, club and monitor				
	-Defeatable 3 channelmixer with lecel controls				
	and clip indicators				
	-Bluetooth input/streaming, not affected by				
	mixer defeat				
	-2 microphone inputs with level and phantom				
	power				



	-1/4-inch TRS Instrument and Line Inputs				
	-18-inch AUX input for connecting or stereo				
	audio sources				
	-an XLR Main In & link output for easy				
	connection and looping				
	-Selectable Sub Filter (HPF) for connecting a				
	subwoofer				
	Wireless Microphone Mic System, 2.4G, 6				
46	channels	unit	2	15,000.00	30,000.00
	■2.4G wireless Microphone Mic System 6				
	channels XLR Connection Built-in				
	Rechargeable Lithium Battery				
	©Compact size 2.4G wireless microphone				
	system, XLR connection, easy to use				
	■less than 4ms ultra-low latency, clear and				
	stable signal transmission				
	■32bit/48Khz high resolution audio quality				
	■Built -in rechargeable lithium battery				
47	Shower Heater with Inverter Booster Pump	unit	10	15,000.00	150,000.00
	Features		-	,	,
	Sleek and Stylish Casing				
	Energy Saving Inverter DC Pump 50%				
	Silent Below 35dB				
	Double Layer 2K Spray Paint Finish with 3				
	Colour Options				
	Stepless Electronic Power Control				
	Accessories				
	5 Spray Showerhead				
	Slim and Chromed Slider Bar				
	1/4 Turn Valve for turn On/Off Shower				
	Durable, Safe and Hygienic Triple Reinforced				
	Non-Conductive Hose Safety				
	Thermostat with Safety Cut-Out				
	Double Poles ELCB System with 10mA				
	sensitivity				
	Splash Proof IP25 Casing				
	SVF Valve With Built-In Filter				
	INNOVATIVE FEATURES				
	Urban & Stylish Design				
	Adjust To The				
	Temperature You Desire				
	Stepless Electronic Power Control System				
	Desire Temperature				
	Booster Power Icon				
	Energy Saving & SilentPlus Technology				
	Quiet Operation (Below 35dB)				
	Inverter DC Pump Icon				
	Turbo Charge Your Shower with Energy Saving				
	Turbo charge rour shower with Energy Saving				



	Describes Only on Finish			1	
	Premium Colour Finish				
	Premium & Long Lasting Colour Finish				
	Double Layer 2K Spray Paint Finish				
	(Colour models only)				
	SAFETY FEATURES				
	High Protection Against Water SplashWater				
	Splash Icon				
	High Protection Against				
	Water Splash				
	Comply with IEC 60529 (IP25) Standard				
	ELCB System Icon				
	The Safest Protection				
	Against Current Leakage				
	Double Poles ELCB				
	complete with accessories				
48	Smart TVs, 50"	set	2	25,000.00	50,000.00
	Display Size: 50"		_		30,000.00
	Ports Input: OTHERS, HDMI, USB, Component				
	in (Y/PB/Pr), RF in (Terrestrial/Cable Input),				
	Digital Audio Out (Optical), Audio Out (Mini				
	Jack), Ethernet (LAN), Composite in (AV)				
	TV Features: Netflix, HDR, Cinema 3D				
	Wireless Connectivity, Web Browser, Mobile				
	Screen Mirroring, Youtube, DTS Audio,				
	Bluetooth Connectivity				
	TV Resolution: 4K UHD				
	Smart TV OS: Android OS				
49	Stand Fan, 405 mm diameter, 220 volts	unit	24	2,500.00	60,000.00
	■Durable High-performance motor				
	■3-speed push button switch				
	■Thermal fuse protection				
	Oscillation				
	With height adjustment				
	Exhaust Fan (Industrial wall exhaust fan,				
50	12")	unit	5	1,600.00	8,000.00
51	Wireless Microphone	set	7	5,500.00	38,500.00
	Carrier Frequency: UHF 613 - 870MHz		•	0,000.00	23,000.00
	Frequency Steadying: -0.002-				
	Modulating Mode: FM				
	Audio Dynamic Range: Over 70 dB				
	Audio Dynamic Kange. Over 10 dB Audio Frequency Responses: 100Hz - 15KHz				
	Audio Output Level: 0 - 280mV				
	S/N Ratio: Over 70bdB				
	T.H.D: -0.5-				
	Sensitivity: 3uVFor30dBS/N				
				TOTAL:	3,750,000.00



Bids received in excess of the ABC for each item shall be automatically rejected at bid opening.

- 2. The *Visayas State University* now invites bids for the above Procurement Project. Delivery of the Goods is required by *Forty-Five (45) calendar days upon receipt of Notice to Proceed (NTP)*. Bidders should have completed, within *two (2) years* from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- 3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.
 - Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.
- 4. Prospective Bidders may obtain further information from *Visayas State University* and inspect the Bidding Documents at the address given below during *Mondays Fridays* (8:00 AM-5:00 PM).
- 5. A complete set of Bidding Documents may be acquired by interested Bidders on 21 February 13 March 2024 until 8:30 AM from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Five Thousand Pesos (PhP 5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means.
- 6. The Visayas State University will hold a Pre-Bid Conference on February 29, 2014; 9:00 AM at the BAC Conference Room, VSU Market, Visca, Baybay City, Leyte and through video conferencing via Zoom, which shall be open to prospective bidders.
 - Bidders are advised to contact the BAC Secretariat before the scheduled Pre-Bid Conference for the Zoom meeting details.
- 7. Bids must be duly received by the BAC Secretariat through (i) manual submission at the office address indicated below, (ii) online or electronic submission as indicated below, or (iii) both on or before 13 March 2024 until 8:30 AM. Late bids shall not be accepted.
- 8. For bidders who opt to submit their bids electronically, a hardcopy (original) of the bid must be sent to the BAC through preferred couriers. A proof (e.g. courier receipt/waybill, etc.) that a hardcopy of the bid is on transit must be presented upon submission of the electronic bid.
- 9. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in **ITB** Clause 14.



10. Bid opening shall be on 13 March 2024 until 9:00 AM at the BAC Conference Room, VSU Market, Visca, Baybay City, Leyte and through video conferencing via Zoom. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.

Bidders are advised to contact the BAC Secretariat before the scheduled Bid Opening for the Zoom meeting details.

- 11. The *Visayas State University* reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 12. For further information, please refer to:

Ms. Jessamine C. Ecleo (BAC Secretariat)

Office of the Head for Procurement, VSU-Main, Visca, Baybay City, Leyte

Mobile: 053 565 0600 local 1093 or 0998 555 0106

Email: jessamine.ecleo@vsu.edu.ph

or

13.

Mr. Toni Marc L. Dargantes (BAC Secretariat)

Office of the VP for Planning, Resource Generation & Auxiliary Services

VSU-Main, Visca, Baybay City, Leyte Mobile: 0977 7186594

Email: tmdargantes@vsu.edu.ph

You may visit the following websites:

For downloading of Bidding Documents: https://www.vsu.edu.ph/philgeps-opportunities

February 20, 2024

DILBERTO O. FERRAREN

Chairperson, VSU BAC



Section II. Instructions to Bidders



1. Scope of Bid

The Procuring Entity, *Visayas State University*, wishes to receive Bids for the *Supply and Delivery of Office Equipment*, with identification number *VSU-GOODS-24-22*.

The Procurement Project (referred to herein as "Project") is composed of *51 items*, the details of which are described in Section VII (Technical Specifications).

2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for 2024 in the amount of *Three Million Seven Hundred Fifty Thousand Pesos (PhP* 3.750.000.00).
- 2.2. The source of funding is: NGA, the General Fund, Special Trust Fund, and Trust Fund.

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. Foreign ownership limited to those allowed under the rules may participate in this Project.



5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:

Bidder should comply with the following requirements:

- i. Completed at least two (2) similar contracts, the aggregate amount of which should be equivalent to at least *fifty percent* (50%) of the ABC for this Project; and
- ii. The largest of these similar contracts must be equivalent to at least half of the percentage of the ABC as required above.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that: **Subcontracting is not allowed**.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address and/or through videoconferencing/webcasting as indicated in paragraph 6 of the **IB**.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII** (Checklist of Technical and Financial **Documents**).



- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within **two** (2 years) prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in **Section VIII** (**Checklist of Technical and Financial Documents**).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, ex-warehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;
 - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
 - iv. The price of other (incidental) services, if any, listed in e.
 - b. For Goods offered from abroad:



- i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
- ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications).**

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in: Philippine Pesos.

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security shall be valid until *July 13*, *2024*. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the **IB**.



17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "*passed*," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII** (**Technical Specifications**), although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows: One Project having several items, which shall be awarded as separate contracts per item.
- 19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.



20. Post-Qualification

20.1. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**.

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.



Section III. Bid Data Sheet



Bid Data Sheet

	Dia Data Silect
ITB Clause	
5.3	For this purpose, contracts similar to the Project shall be:
	a. Office Equipment
	b. completed within two (2) years prior to the deadline for the submission and receipt of bids.
7.1	Subcontracting is not allowed.
12	The price of the Goods shall be quoted DDP <i>VSU Main, Visca, Baybay City, Leyte</i> or the applicable International Commercial Terms (INCOTERMS) for this Project.
14.1	The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:
	a. The amount of not less than <i>Seventy Five Thousand Pesos (PhP 75,000.00)</i> or <i>two percent (2%) of ABC</i> , if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or
	b. The amount of not less than <i>One Hundred Eighty Seven Thousand Five Hundred Pesos (PhP 187,500.00) or five percent (5%) of ABC</i> if bid security is in Surety Bond.
15	Bidders are requested to submit two (2) more copies of its bid (Copy 1 and Copy 2) in addition to the required original hardcopy.
15	For filing purposes, the bidders are urged to use Orange envelopes for its Technical and Financial Component envelopes, including the Mother (outer) Envelope.
19.3	See Section I. Invitation to Bid (Item 1) for the list of items and their corresponding total Approved Budget for the Contract (ABC) per item.
20.2	Bidders are required to submit its updated Mayor's/Business Permit during post-qualification.
21.2	Not Applicable.



Section IV. General Conditions of Contract



1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the **SCC**, **Section IV** (**Technical Specifications**) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.



5. Warranty

- 6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.



Section V. Special Conditions of Contract



Special Conditions of Contract

	Special Conditions of Contract
GCC Clause	
1	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	The delivery term applicable to this Contract is delivered VSU Main Campus, Visca, Baybay City, Leyte. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination.
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is:
	 Vivian V. Balbarino Head, Supply and Property Office VSU-Main, Visca, Baybay City, Leyte Contact #: 053 565 0600 local 1082/09175518871 sppmo@vsu.edu.ph Additional Instruction: The Supplier should notify the Head of Supply and Property Management Office at least 1 week before the scheduled delivery.
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements:
	 a. performance r supervision of on-site assembly and/or start-up of the supplied Goods;
	b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;



- c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
- d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
- e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.

The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

Spare Parts -

The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:

- a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
- b. in the event of termination of production of the spare parts:
 - i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
 - ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (**Schedule of Requirements**) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of 3 years.



Spare parts or components shall be supplied as promptly as possible, but in any case, within 1 month of placing the order.

Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity

Name of the Supplier

Contract Description

Final Destination

Gross weight

Any special lifting instructions

Any special handling instructions

Any relevant HAZCHEM classifications

A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging.

Transportation -



Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price. Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price. Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure. The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination. **Intellectual Property Rights –** The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof. 2.2 Payment of staggered deliveries shall be allowed. Payment shall be on "as per cost of the items delivered" subject to inspection and acceptance. The inspections and tests that will be conducted will be specified by the 4 appropriate technical team of VSU to confirm conformity to the contract specifications at no extra cost to VSU.



Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item No.	Unit	Qty	Description	Delivered, Weeks/Months
1	рс	11	18" STAND FAN	
			Product Overview	All Items Should Be Delivered
			Reliability (Motor Life)	to VSU Main Campus, Visca,
			Performance: 7,000 hours	Baybay City, Leyte within 45
			Energy Efficient	Calendar Days from receipt of
			Less Power Consumption	Notice To Proceed (NTP) and
			Energy Savings up to 10% with the new motor vs. Existing	Purchase Order
			New Modern Design	
			Elegant Design	
			New Modern "Minimalist" Design	
			Warranty	
			Parts: 1 year	
			Labor: 1 year	
			Motor Warranty: 3 Year	
			General Specifications	
			Blade Material / Size, cm: PP / 40	
			Wattage (W, Max): 60	
			RPM (Max): 1350	
			Air Delivery (\M3/min. Max): 119	
			Max Center Height, mm: 1,197	
			Height Adjustment: Free Stop Mechanism	
			Stroke, mm: 150	
			Switch Type: 3 Speed Piano Switch	
			Vertical Angle Adjustment: Free Neck	
			Oscillation: Double	
			Color: Black	
2	рс	20	18" Wall Mount Oscillating Hydroponic-Clarify	
	PC	20	Fan	
			Keeps room and leaf temperatures down	
			Smooth and quiet operation	
			90° oscillating action	
			Pull to change speed and Pull for oscillating or	
			one position.	
			Assembly required	



3 pc 3 2 BURNER GAS STOVE Heavy duty gas stove		1		■Cooling capacity: at least 18,500 kj/h	
3 pc 3 2 BURNER GAS STOVE	5	set	2		
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ### of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package) 2x Remote Control Batteries Mounting Bracket wall mounted EER rating above 10 with one year warranty on parts and services			_		
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner BDurable metal gas ignition controls BStainless metal gasket and body BAuto-ignition burner B# of burners: 2 BDimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches BBurner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches BColor: silver BWarranty: 1 year A set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package) 2x Remote Control Batteries Mounting Bracket wall mounted EER rating above 10 with remote control				, ,	
3 pc 3 2 BURNER GAS STOVE B-Heavy duty gas stove B-High quality fuel-efficient burner B-Durable metal gas ignition controls B-Stainless metal gasket and body B-Auto-ignition burner B-H of burners: 2 B-Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches B-Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches B-Space in between outer rings: 20cm 7.9 inches B-Color: silver B-Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package) 2x Remote Control Batteries Mounting Bracket wall mounted EER rating above 10					
3 pc 3 2 BURNER GAS STOVE B-Heavy duty gas stove B-High quality fuel-efficient burner B-Durable metal gas ignition controls B-Stainless metal gasket and body B-Auto-ignition burner B-H of burners: 2 B-Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches B-Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches B-Space in between outer rings: 20cm 7.9 inches B-Color: silver B-Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package) 2x Remote Control Batteries Mounting Bracket wall mounted					
3 pc 3 2 BURNER GAS STOVE Image: Black Burner Burn					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches BBurner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package) 2x Remote Control Batteries					
3 pc 3 2 BURNER GAS STOVE MHeavy duty gas stove MHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw 4x Rubber Foot (Outdoor Package)					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant 12x Tapping Screw					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner BDurable metal gas ignition controls BStainless metal gasket and body BAuto-ignition burner B# of burners: 2 BDimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches BBurner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches BSpace in between outer rings: 20cm 7.9 inches Color: silver BWarranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode R32 Refrigerant				11 0	
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner BDurable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 BDimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches BBurner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches BSpace in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin Triple Protector Plus Quiet Mode Single User Mode				Š	
3 pc 3 2 BURNER GAS STOVE Heavy duty gas stove					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner BDurable metal gas ignition controls Stainless metal gasket and body BAuto-ignition burner B# of burners: 2 BDimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches BBurner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches BSpace in between outer rings: 20cm 7.9 inches BColor: silver BWarranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus DuraFin					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner BH of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches BSpace in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr Easy Filter Plus				Triple Protector Plus	
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year A set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology Digital Inverter Boost Fast Cooling Cooling capacity: at least 12,500 kj/hr				DuraFin	
3 pc 3 2 BURNER GAS STOVE ———————————————————————————————————					
3 pc 3 2 BURNER GAS STOVE				Cooling capacity: at least 12,500 kj/hr	
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts EER Rating: 14.26 WindFree Technology				Č	
3 pc 3 2 BURNER GAS STOVE ———————————————————————————————————				Ü,	
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year 4 set 6 Air Condition, Split type, Inverter, 1.5 HP Wattage: 1250 Watts					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner # of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year A set 6 Air Condition, Split type, Inverter, 1.5 HP					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches Color: silver Warranty: 1 year	•				
3 pc 3 2 BURNER GAS STOVE ———————————————————————————————————	4	set	6		
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner ## of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9 inches					
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner Durable metal gas ignition controls Stainless metal gasket and body Auto-ignition burner BH of burners: 2 Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches Space in between outer rings: 20cm 7.9					
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body — Auto-ignition burner — of burners: 2 — Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches — Burner diameter: 9cm 3.5 inches Outer ring diameter: 22.5cm 8.9 inches				· · · · · · · · · · · · · · · · · · ·	
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body — Auto-ignition burner — # of burners: 2 — Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches — Burner diameter: 9cm 3.5 inches Outer ring				,	
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body — Auto-ignition burner — of burners: 2 — Dimensions: (W x L X D) 71 x 35.5 x 8.5cm 28 x 14 x 3.3 inches				·	
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body — Auto-ignition burner — # of burners: 2 — Dimensions: (W x L X D) 71 x 35.5 x 8.5cm					
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body — Auto-ignition burner — of burners: 2					
3 pc 3 2 BURNER GAS STOVE					
3 pc 3 2 BURNER GAS STOVE — Heavy duty gas stove — High quality fuel-efficient burner — Durable metal gas ignition controls — Stainless metal gasket and body				ŭ	
3 pc 3 2 BURNER GAS STOVE BHeavy duty gas stove BHigh quality fuel-efficient burner BDurable metal gas ignition controls				ž ,	
3 pc 3 2 BURNER GAS STOVE ——————————————————————————————————				5 5	
3 pc 3 2 BURNER GAS STOVE					
,				■Heavy duty gas stove	
	3	рс	3	2 BURNER GAS STOVE	



	1 1		T
			■wall mounted
			■EER rating above 10
			⊚ with Quiet Mode
			■ with remote control
			■ with Anti bacterial air filter
			■ with Micro Dust Filter
			■with at least 10 years compressor warranty
			■offer must be in the market for at least 10 years
			■with at least 10-Year Warranty on Compressor
			■with one year warranty on parts and services
			■ with free installation
6	unit	4	Aircon Split Type (1.5 HP)
			Dimensions
			Net Dimensions (W x H x D):
			Indoor - 779mm x 290mm x 209mm
			Outdoor - 780mm x 542mm x 289mm
			Gross Dimensions (W x H x D):
			Indoor - 861mm x 364mm x 255mm
			Outdoor - 891mm x 603mm x 396mm
			Power Requirements:
			230 V
			Power Consumption:
			750 W
			General Specifications
			Remote: Yes
			Timer: Yes
			Cooling Capacity: 11,020 kj/h
			Control Type: With remote
			Cooling Area (sq. meters): Survey is
			recommended
			Noise Level (Indoor) – Low: 28dB
			Filter: Yes
			Airflow Direction Control (Up & Down): Automatic
			Airflow Direction Control (Left & Right): Manual
			Temperature Control: With remote
			Fan Speed: 5 Speed Level
			Energy Efficiency Ratio: 14.69
			with free installation
7			Aircon Split Type 2.5 HP Inverter, With
7	unit	4	Installation
			Capacity: 2.5HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 24,000 Btu/h
			Cooling Input: 2,000W
			Cooling Current: 8.7A
			EER: 12.7
			Indoor Unit
			mador offic



10	рс	2	with free installation Bottom Loading Water Dispenser Product Model: JD-8044 Voltage/frequency: 220V~50Hz
10	рс	2	Bottom Loading Water Dispenser
		_	
	1		Current: approx. 6.9 A
			Voltage: 230 V
			kJ/hW,
			EER (min-max): approx. 14.17 (16.12-12.61)
			21,960 (4,030-25,850) kJ/h
			Cooling Capacity (min-max): 6.10 (1.12-7.18) kW,
			timer ON/OFF
			Remote control with 24 hours programmable
		_	Split Type, Air-conditioning Unit with 2.5 HP
9	рс	2	Airconditioning Unit
			with free installation
			1 year warranty
			* 39.5/34/32 dB (A) Sound Level (H/M/L)
			* R32 Refrigerant
			* 4.32 CSPF
			* 700 (290-990) Power Input (W)
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)
			* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)
			* 1.0HP Inverter
			Specifications:
			*with remote control
			* Fast Cooling
			* Louver Position Memory
			* Turbo Mode
			* Sleep Mode
			* Silver Ion Filter
			* Gold Fin Protection
			* Smooth Frequency Control
			* High-density Dust Filter
	1	-	Features:
8	unit	3	Aircon, Split Type, 1HP (Inverter)
			With Free installation
			installed by accredited installation team
			(5) years on compressor provided that the unit is
			One (1) year warranty on parts and service five
			845x363x702mm (outdoor unit) Application Area: 29-43sgm
			Unit Dimension (W*D*H) : Approx.
			Compressor Type: Rotary
			Outdoor Unit
			1080x336x326mm (Indoor Unit)
			Unit Dimension (W*D*H) : approx.
			Noise Level (Hi/Mi?Lo): 50/–/40 dB (A)
			Air Flow (Hi/Mi/Lo): 1063x955x759 m3/h



			Cooling Down 7514/
			Cooling Power: 75W
			Heating Power Warm & Hot: Rated Power:
			425W, Heating Power: 425W
			Cold & Hot: Rated Power: 500W, Heating Power: 425W
			Carton Size: 355x325x1040mm
			Actual Product Size: 320x285x980mm
			Hot Water Temperature: 85 - 95 Degree Celsius
11	unit	1	DEEP FREEZER
			■DEEP FREEZER 13 CUBIC FEET CHEST FREEZER
			■ WIRE BASKET SHELVING MATERIAL,
			approx. 216 WATTS; NO FROST; WITH INVERTER
			■CHARCOAL DEODORIZER. 220V or auto
			voltage
12	nc	1	Dehumidifier for Extra Large Rooms and
14	рс	'	Basements
			Includes: Washable Filter, Built-in Handles and Wheels, Drain Hose Outlet
			Weight: at most 40 lbs
			Rated Current: approx. 4.7 Amps
			Moisture Removal: 70 pints per day
			Air CFM Range (cubic feet per minute): 165
			(Normal) to 188 (Turbo)
			Removable Water Tank Capacity: at least 1.6
			gallons / 6 liters
			Certifications: UL & Energy Star rated
			Features: Touch Control Panel; Auto Restart,
			Shut Off, Defrost; Turbo Mode; Continuous
			Dehumidifying; 24-hour Timer; Custom Humidity
			Level from 35% to 85%
			Spaces between 2500 and 4000 square feet, with
			room temp from 41°F to 95°F
			Power: 220/240V
12	004	А	Digital Duplicator Machine, Copy printer,
13	set	1	300x600 DPI printing
			Master Making/Printing Methods: High-speed
			digital master-making/Fully automatic printing
			Scanning: 600 dpi × 600 dpi
			Printing: 300 dpi × 600 dpi, Quick Master Making
			mode: 300 dpi × 400 dpi
			Maximum Scanning Area: 297 mm × 432 mm
			Print Paper Weight: 46 gsm to 157 gsm
			Print Paper Size: 100 mm × 148 mm to 310 mm ×
			432 mm
			Maximum Printing Area: 210 mm × 357 mm
			Maximum Printing Area: 210 mm × 357 mm



<u> </u>	1 (*0 (); 1 ; 1 ; 1 ; 1 ; 1 ; 1
	sheets*2, stacking height of 110 mm or lower
	Print Speed: 5 levels: 60, 80, 100, 120 and 130
	ppm
	Functions: Original Scanning mode, Scanning
	Level, Enlargement/Reproduction, Dot Process,
	2-Up, Book, Ink Saving, Quick Master Making,
	ADF-Semi-Auto*3, Speed, Density, Print Position,
	Program A/B, Job Separation*3, Idling,
	Confidential, Meter Display, Count Report Output,
	Proof, Direct Printing, USB Flash-via-Printing,
	Auto Sleep Setting, Auto Power-OFF Setting,
	ECO mode, RISO iQuality System
	Ink Supply: Full automatic (1000 ml/cartridge)
14 unit 2	Dry Seal, Customized Machine Engraved, Stainless Steel Material
15 pc 8	Electric fan
	■Stand fan 16" metal blade
	Adjustable height
	othree speed controller
16 unit 4	Floor Standing Mounted Airconditioner
	■At least 4.0HP
	■Energy Saving Compressor, 3D Air Delivery
	System
	■with Sleep Mode
	with Auto On / Off Timer
	■with High Efficiency Air Filter
	with Remote Control
	■Air Conditioner Rated Capacity (BTUs) at least
	2.5
17 unit 1	Gas Stove, 4 Burners, Heavy Duty
	4 Gas Burners
	Rust Proof
	Black Enamel Pan Support
	0.5mm Painted cold-rolled steel Side panel
	0.4mm Stainless Steel Surface
	Whirlwind Burner
	90mm Double / 40mm / 90mm Double burner /
	90mm Double
	Cast Iron Burner with Stainless Steel Burner
	Cover
	Cover
	Automatic Ignition
	Automatic Ignition
	Automatic Ignition Save Gas More than 30%
	Automatic Ignition Save Gas More than 30% Quantity: 1set
18 pc 1	Automatic Ignition Save Gas More than 30% Quantity: 1set Net Weight: 7.2kg
18 pc 1	Automatic Ignition Save Gas More than 30% Quantity: 1set Net Weight: 7.2kg Unit Dimension: 480x570x125mm



			Capacity: 10 Liters or 3 Gallons	
			Cord Length: 3m	
			4 in 1 application: wet, dry, indoor & outdoor	
			Strong handle for easy carrying	
			Large switch button with waterproof design for	
			safe & easy operation	
			Comes with complete accessories	
19	unit	1	Heavy Duty Combo Binding Machine	
			ΦSpecs:	
			■Maximum Punching Sheets: 25	
			■Max Size: LS, F4, A4, Extra Long	
			■Selectable Punching Pins: 24 slots	
			■Net Weight: 12.5kgs	
20	рс	1	Heavy Sheetfed Scanner	
	P	-	Technology	
			Scanner Type: Sheetfed Scanner	
			Optical Resolution (ADF): 600 DPI x 600 DPI	
			(Horizontal x Vertical)	
			Optical Resolution: 600 DPI x 600 DPI	
			(Horizontal x Vertical)	
			ADF Minimum Document Size: 50.8 mm x	
			50.8 mm (Horizontal x Vertical)	
			ADF Maximum Document Size: 215.9 mm x	
			6,096 mm (Horizontal x Vertical)	
			Paper Formats	
			A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6	
			(10.5x14.8 cm), B6 (12.5x17.6 cm), B5	
			(17.6x25.7 cm), B4 (25.7x36.4 cm), Letter, Legal,	
			Postcard, Business cards, Plastic cards	
			Scanning color depth	
			Input: 30 Bits Color / 10 Bits Monochrome ,	
			Output: 24 Bits Color / 8 Bits Monochrome	
			Ultrasonic Sensor: Yes	
			High Capacity, General Office	
			Scanner	
			Light Source: ReadyScan LED technology	
			Output Resolution:1200 DPI	
			Scanning Speed	
			Monochrome: 65 pages/min -	
			Color: 65 pages/min measured with Size: A4,	
			Resolution: 200 / 300 dpi,	
			Monochrome: 130 image/min -	
			Color: 130 image/min measured with Size: A4,	
			Resolution: 200 / 300 dpi	
			Paper / Media Handling	
			Paper Setting Capacity:100 Sheets	
			Auto loading: 27 - 413 g/m²	
			Automatic Document Feeder Type	



	1		T
			Single pass dual scanning
			Reliability Daily Duty Cycle: 7,000 pages
			Automatic Document Feed:100 pages
			Duplex Scan:Yes
			Scanning Features
			Output formats:BMP, JPEG, TIFF, multi-TIFF,
			PDF, searchable PDF, PDF/A, PNG
			File compression features:Hardware JPEG
			compression, TIFF Compression (JPEG(7), CITT
			G4, LZW), PDF Compression
			Advanced document integration:Scan to Email,
			Scan to FTP, Scan to Microsoft SharePoint®,
			Scan to Print, Scan to Web folders, Scan to
			Network folders
			Scanning Volume:7,000 Pages per day
			Connectivity
			Interfaces:USB 2.0 Type B, USB 3.0 Type B
64			Options: Roller Assembly Kit
21	unit	6	Hot & Cold water dispenser
			■Bottom load water dispenser
			■3 Faucets: Hot, Cold and Normal water function
			■3-Push Button dispensing control
			■Anti-scald safety lock switch
			■Child Lock Safety feature on Hot Water Faucet
			■Floater indicator to avoid water overflow
			© Capacity: Hot - 1.2 Liters, Cold - 3.5 liters,
			Power Rating: Hot - 420 watts, Cold - 100 watts,
			R134a
22	рс	1	Laminator
			A4 Hot and Cold Laminating Machine
23	unit	1	Microwave Oven
			Capacity: 32 litres
			Dimension: 517 x 297 x 384mm
			Power source: 220V / 60Hz
			Power Consumption: 1500W
24	unit	1	Mirrorless Camera, 24.1MP, 3" LCD Monitor,
24	unit	ı	4K Video
			AF Modes - Stills: One-Shot AF, Servo AF,
			Manual Movie recording: One-Shot AF, Movie
			Servo AF, Manual
			AF Point Selection - Automatic selection, Manual
			selection
			AF System Points - Stills: Max. 3975 selectable
			AF point positions / Up to 143 zones (auto
			selection)
			Movie recording: Max. 3375 selectable AF point
			positions / Up to 117 zones (auto selection)
			Built-in Flash



0/ /5 / 0/ / 05	
Closest Focusing Distance (cm) - 25	
Continuous Shooting Speed (Shots Per Sec) (Up	
To) - 10 (One-Shot AF) / 7.4 (Servo AF)	
Digital Zoom - Approx. 3-10x (for movie recording	
only)	
Drive System - Stepping Motor-driven lead screw	
+ rack system	
Effective ISO - Stills: 100 - 25,600 (H:51,200),	
Movie (full HD/HD): 100 - 12,800 (H: 25,600),	
Movie (4K): 100 - 6,400	
Exposure Compensation - ±3 stops in 1/3-stop	
increments, AEB: ±2 stops in 1/3-stop increments	
Eye Detection AF - One-Shot AF / Servo AF /	
Movie Servo AF	
Flash Modes - E-TTL II Autoflash, FE Lock,	
Manual pop-up, Retractable, Built-in	
• • •	
Focal Length (35mm Equivalent) - 24 - 72mm(3x)	
Guide Number ISO 100 metres - 5	
Image Resolution - 6000 x 4000 (L), 3984 x 2656	
(M), 2976 x 1984 (S1), 2400 x 1600 (S2), 6000 x	
4000 (RAW/C-RAW)	
Image Stabilizer - Stills: Lens shift type, Movie	
recording: Lens shift type & In-body 5-axis	
electronic image stabilization (movie recording	
only)	
with Manual Focus	
Memory Card Type - SD, SDHC*, SDXC*, *UHS-I	
cards compatible	
Metering Mode - Stills: Evaluative, Partial, Spot,	
Center-weighted average, Movie: Evaluative	
(when faces are detected with [Face+Tracking]),	
Center-weighted average (when no faces are	
detected)	
Processor Type - DIGIC 8	
Sensor Size - APS-C	
Shooting Modes - Stills: Scene Intelligent Auto,	
Hybrid Auto, Special scene modes (Self Portrait,	
Portrait, Smooth Skin, Landscape, Sports,	
Panning, Close-up, Food, Night Portrait,	
Handheld Night Scene, HDR Backlight Control,	
Silent Mode), Creative filters (Grainy B/W, Soft	
focus, Fish-eye effect, Water painting effect, Toy	
camera effect, Miniature effect, HDR art	
standard, HDR art vivid, HDR art bold, HDR art	
embossed), Program AE, Shutter-priority AE,	
Aperture-priority AE, Manual Exposure, Movie	
recording: Movie auto exposure, Movie manual	
exposure	
Shutter Speed Range (Sec.) - Stills: 30 - 1/4000,	



		ı		
			Bulb, Movie recording: 1/25 - 1/4000 (PAL) or 1/30 - 1/4000 (NTSC)	
			Standard Power Supply - LP-E12	
			Silent Shutter - Available: Single Shot	
			Still Image Format - JPEG, RAW, RAW + JPEG,	
			C-RAW, C-RAW+JPEG	
			Viewfinder Coverage (Approx.) - 100%	
			Viewfinder Type - 0.39-inch OLED, 2.36million	
			dots, 59.94fps refresh rate	
			White Balance - Auto (Ambience priority), Auto	
			(White priority), Preset (Daylight, Shade, Cloudy,	
			Tungsten light, White fluorescent light, Flash),	
			Custom, Color temperature setting (approx.	
			2500-10000 K), White balance correction and	
			white balance bracketing features provided,	
			*Flash color temperature information	
	-		transmission possible	
25	no	1	X-sync (sec.) - 1/200	
23	рс	I	Paper shredder machine, heavy duty	
			Shred Type: Cross Cut	
	1		Maximum Sheet capacity(70gsm): 10 Sheets Maximum Sheet capacity(21 Literal All Literal	
	1		■Waste Container capacity: 21 Liters	
00	*4		Power Source: 220 - 240 VAC	
26	unit	1	Photography Camera Tripod, Lightweight	
			Compatible with Mirrorless Camera (Canon,	
	1		Nikon, Fuji, Pentax, etc.)	
27	unit	2	Portable Trolley 15" Speaker with wireless microphone	
	 		■15" 2 Way 480 Watts Powered Portable Sound	
			System	
			■Plastic Cabinet	
			■AC220V or DC12V (With built-in Rechargeable	
			Batteries)	
			■With 2 Wireless Microphone	
			■With 2 Mic Input (1 XLR, 1 PL55)	
			■With FM Radio, Bluetooth, Guitar Input (Shared	
			with Mic 2 input), USB & SD Port	
			■With 5 Band Equalizer and LCD Display	
	1		■With Aux / Line In and Line Out	
	1		■With Remote Control, Handle and Wheel	
28	unit	1	Refrigerator	
		-	uses a compressor or evaporator to circulate	
	1	I	· · · · · · · · · · · · · · · · · · ·	
			cooleg air or water around the samples	
			cooled air or water around the samples 7 cu. ft. HD Inverter No Frost Refrigerator	
			7 cu. ft. HD Inverter No Frost Refrigerator Bottom Freezer	
			7 cu. ft. HD Inverter No Frost Refrigerator Bottom Freezer	
			7 cu. ft. HD Inverter No Frost Refrigerator Bottom Freezer Heavy Duty Inverter	
			7 cu. ft. HD Inverter No Frost Refrigerator Bottom Freezer	



	1		[
			Fresh Zone Drawer (Crisper)
			Independent Temparature Control for Fridge and
			Freezer
			Recessed Handle
			Stainless Steel Finish
			Net Weight: 52kg
			Gross Weight: 57kg
20		4	Gross Dimension (h:w:d) : 166:55:64 cm
29	unit	1	Refrigerator
			Transparent door , Upright at least 10 to 12.4 Cubic Feet inverter
			Transparent Anti Frost Double Layered
			Tempered Glass Door
			Adjustable Shelves
			Efficient Cooling
			Interior Lights
			Input 220/240V, 50/60 Hz with power cord & plug
			Automatic voltage stabilizer with time delay
			restart
30	no	4	Refrigerator- at least 6.0 cu.ft. (Two-door)
3 0	рс	1	inverter
			■Two-Door Direct Cool Refrigerator
31	unit	1	Smart TV, 70" with Android 10 OS
			■4K Ultra HD
			■Borderless Design
			■Chameleon Extreme
			■Picture Engine
			■Dolby Digital Plus with 12x12w
			■Android 10.0 Q
			■Bluetooth 5.0
			■Audio: Dolby Digital Plus
			■DTS TruSurround
			■Equalizer
			■Quad-Core
			■Internal Memory: 8GB
			■RAM: 2GB
			■With Voice Search
			■Google Assistant
			■ Chromecast Built-in or Wireless Display
			■Wi-Fi Connectivity 2.4G
			■272R
			■Android 10.0
			■Bluetooth 5.1
22	:4	1	■Display Panel: LED
32	unit	2	Laminator Machine, A3
			■Heavy Duty, for A3 & A4 size, infrared heating
			system and adjustable temperature control with overheating protection
			Overneating protection



33	unit	3	Aircon, Window Type, 2HP Inverter
JJ	uiiit	J	2.0 HP, Inverter Window Type
			R32 Refrigerant
			High Energy Efficiency Ratio
			All-DC Motor
			Room Temperature Display & Setting
			Air Swing Control
			Filter Clean Indicator
			Power Source 230, 60, 1Ø (V, Hz, Ph)
			Cooling Capacity 18,750 (kJ/h)
			Current 7.3 (A)
			Input Power 1563 (W)
			EER Rating 12.0 (kJ/hW)
			Recommended Floor Area 23 – 33 m ²
			Moisture Removal 2.8 (L/h)
			Noise Level Indoor (dB-A) 51 / 48 (H / L)
			Air Circulation (indoor) 14.2 m3/min
			Air Circulation (outdoor) 23.0 m3/min
			Timer (12-Hour On/Off)
			Fan Speed
			Auto / Cool / Dry Mode
			Powerful mode
			Sleep Mode
			Quiet Mode
			Blue Fin Condenser (anti-corrosion fin)
			Anti-Bacterial Filter
			Wireless Remote Control
			Random Auto Restart
34	unit	2	Aircon Split Type (2 HP)
			Capacity: 2.HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 18,000 Btu/h
			Cooling Input: 1552W
			Cooling Current: 6.75A
			EER: 12.24
			Air Flow (Hi/Mi/Lo): 848x796x626m3/h
			Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)
			Unit Dimension (W*D*H) : 965x203x323mm
			(Indoor Unit)
			Refrigerant Type: R32
			Compressor Type: Rotary
			Unit Dimension (W*D*H) : 914x343x546mm (
			outdoor unit)
			Application Area: 23-33 sqm Accesories such as breaker, bracket and copper
			tubbing not included
			One (1) year warranty on parts and service &
	I		1 (1) Joan marrainty on parto and convice a



			compressor
			with free installation
35	unit	21	Aircon, Window Type, 1.0HP (Inverter)
-	dille		1HP Inverter, 8-in-1 Filter, R410A
			Energy Savings Feature:
			24-hour Timer
		Energy Saving Plug	
			Econo and Sleep Mode
			EER Rating: 11.6 (10.8 - 10.7)
			Sleek, Modern Aesthetic
			Remote Control
			2 x AAA Batteries
			With Free Installation
			1 year warranty
36	рс	1	Water Dispenser, Cabinet type
	P •	-	■Floor standing
			■Hot and cold function
			plastic body,high efficiency compressor
			■thermally protected
37	set	1	Sound System
			Type:Portable PA System
			Speaker Drivers:1 x 8" woofer, 1.35"
			compression driver
			Number of Mixer Channels:6
			Number of Mic Preamps:2
			EQ:Treble, Bass, 5-band Graphic
			Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x
			stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in)
			Outputs:2 x 1/4" (speaker out)
			USB:1 x Type A (ULM wireless ready)
			Bluetooth:Yes
			Total Power:500W
			Frequency Response:50Hz-22kHz
			Microphone:1 x Behringer XM1800S
			Power Source:Standard IEC AC cable
			Height:25.9"
			Width:13.9"
			Depth:34.8"
			Weight:44.7 lbs.
38	unit	1	Sliding Paper Cutter
			Working Area: A3 and A4
			Cutting Capacity: 16 sheets
			Packing Weight: 5 kg
			Material: Metal
			Available Size: A3 and A4
			Packing Measurement: 56x34x11 cm
			Other Specifications: Heavy duty for Vinyl,



			Cardboard Paper
39	no	1	Sony Electret Condenser Microphone for lapel
39	рс	ı	mic (for compatibility)
			3.5 mm connector
40	unit	1	Vacuum cleaner, wet and dry, 1200 watts
			1200 Watts power
			At least 30L dust/liquid capacity
			Double stage long life motor
			With auto shut-off function
			With blower function
			Washable ecological HEPA filter
			At least 3 meters flexible hose
			At least 9 meters power cord length
			With handrail/handle for easy transport
			Accessories:
			Extension tube
			Bristle brush
			Crevice nozzle
			2-in-1 brush and round brush
			Floor/carpet brush
			Wet/dry floor brush
			Washable HEPA filter Flexible extension tube
			Microwave Oven, Digital, Non-Inventer, 13
41	рс	1	Power Levels
			■30 Liters capacity
			■Grill and convection
			■electronic control
			■dual wave system
			■13 power levels
			■900W
			■Non-Inventer
42	unit	1	Hot and Cold Table Top Water Dispenser
			Table top water dispenser
			Hot and cold
			Electronic type cooling
43	рс	3	Television, Smart
			32 inch television, Smart
			Resolution: 1,366 x 768
			HDMI Ports: 2
			USB Ports: 1
			Power Supply: AC100-240V 50/60Hz
			Set Size with Stand (WxHxD): 732.9 x 462.8 x 163.7 mm
			Set Size without Stand (WxHxD): 732.9 x 440.3 x
			78.5 mm
	1		Cordless Kettle



Electric Glass Kettle, Cordless HWK-118GI Power: 230V - 60Hz, 2000W Capacity: 1.8L 360 degree rotary base, easy to use with high borosilicate glass body. Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluelooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 24 G wireless Microphone Mic System, 2.4G, 6 channels 26 Compact size 2.4G wireless microphone system, XLR connection, easy to use 27 less than 4ms ultra-low latency, clear and stable signal transmission				Florida Olora Matti O II
Power: 230V - 60Hz, 2000W Capacity: 1.8L 360 degree rotary base, easy to use with high borosilicate glass body. Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch Woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 24 G wireless Microphone Mic System, 2.4G, 6 channels				
Capacity: 1.8L 360 degree rotary base, easy to use with high borosilicate glass body. Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 24 Wireless Microphone Mic System, 2.4G, 6 channels				
360 degree rotary base, easy to use with high borosilicate glass body. Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 24 Wireless Microphone Mic System, 2.4G, 6 channels				
borosilicate glass body, Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2 Wireless Microphone Mic System, 2.4G, 6 channels				. ,
Durable and stain resistant blue LED light indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts (peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels Chann				
indication when boiling Concealed stainless steel heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System, 5.4G, 6 channels ©2.4G wireless Microphone Mic System, 6 channels ©2.4G wireless Microphone Mic System, 6 channels ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				
heating element Automatic one button cover starter boiling dry protection Automatically turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels				
starter boiling dry protection Automatically turns off when water boiled. Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				
turns off when water boiled. 45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels				
45 unit 1 Active Speaker, 12", 1000W peak two-way, full range -1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels				9 3 7
-1000 watts(peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -11/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System, 2.4G, 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				
-1000 watts (peak) 500 watts (program) -1000 watts (peak) 500 watts (program) -Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels **Electable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels **Electable Sub Filter (HPF) for connection and looping subwoofer ### Compact size 2.4G wireless microphone system, XLR connection, easy to use ### Bless than 4ms ultra-low latency, clear and	45	unit	1	Active Speaker, 12", 1000W peak two-way, full
-Superior DSP processing with component protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and	70	unit	•	range
protection -12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels				-1000 watts(peak) 500 watts (program)
-12-inch woofers with 2.5-inch voice coils -1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use				-Superior DSP processing with component
-1-inch HF compression drivers -90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				protection
-90 x 60 deg. HF dispersion -Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				-12-inch woofers with 2.5-inch voice coils
-Dual purpose full-range and wedge monitor speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				-1-inch HF compression drivers
speaker -Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer 46 unit 2 Wireless Microphone Mic System, 2.4G, 6 channels				-90 x 60 deg. HF dispersion
-Ultra-clear reproduction throughout the whole audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use				
audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use				speaker
audio bandwidth -Recessed control panel -Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use				-Ultra-clear reproduction throughout the whole
-Master Level control with activity indicator (cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				
cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				-Recessed control panel
cabinet level adjustment) -3 performance modes, concert, club and monitor -Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				-Master Level control with activity indicator (
-Defeatable 3 channelmixer with lecel controls and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use				,
and clip indicators -Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use				-3 performance modes, concert, club and monitor
-Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				
-Bluetooth input/streaming, not affected by mixer defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				and clip indicators
defeat -2 microphone inputs with level and phantom power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2 Wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use Iless than 4ms ultra-low latency, clear and				,
power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				
power -1/4-inch TRS Instrument and Line Inputs -18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				-2 microphone inputs with level and phantom
-18-inch AUX input for connecting or stereo audio sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels ©2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				
sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use eless than 4ms ultra-low latency, clear and				-1/4-inch TRS Instrument and Line Inputs
sources -an XLR Main In & link output for easy connection and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use eless than 4ms ultra-low latency, clear and				-18-inch AUX input for connecting or stereo audio
and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels © 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery © Compact size 2.4G wireless microphone system, XLR connection, easy to use © less than 4ms ultra-low latency, clear and				
and looping -Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels © 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery © Compact size 2.4G wireless microphone system, XLR connection, easy to use © less than 4ms ultra-low latency, clear and				-an XLR Main In & link output for easy connection
-Selectable Sub Filter (HPF) for connecting a subwoofer Wireless Microphone Mic System, 2.4G, 6 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use eless than 4ms ultra-low latency, clear and				
subwoofer Wireless Microphone Mic System, 2.4G, 6 channels © 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery © Compact size 2.4G wireless microphone system, XLR connection, easy to use © less than 4ms ultra-low latency, clear and				1 0
channels 2 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use Compact size 2.4G wireless microphone system, XLR connection, easy to use				, ,
channels 2 channels 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery 2.4G wireless microphone system, XLR connection, easy to use 3.4G wireless microphone system, XLR connection, easy to use	40		_	
channels XLR Connection Built-in Rechargeable Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use less than 4ms ultra-low latency, clear and	46	unit	2	
channels XLR Connection Built-in Rechargeable Lithium Battery ©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				■2.4G wireless Microphone Mic System 6
Lithium Battery Compact size 2.4G wireless microphone system, XLR connection, easy to use In this in this indicate of the size of the si				· · · · · · · · · · · · · · · · · · ·
©Compact size 2.4G wireless microphone system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				
system, XLR connection, easy to use ©less than 4ms ultra-low latency, clear and				,
■less than 4ms ultra-low latency, clear and				,
				stable signal transmission



			■32bit/48Khz high resolution audio quality
			■Built -in rechargeable lithium battery
47	unit	10	Shower Heater with Inverter Booster Pump
			Features
			Sleek and Stylish Casing
			Energy Saving Inverter DC Pump 50%
			Silent Below 35dB
			Double Layer 2K Spray Paint Finish with 3 Colour
			Options
			Stepless Electronic Power Control
			Accessories
			5 Spray Showerhead
			Slim and Chromed Slider Bar
			1/4 Turn Valve for turn On/Off Shower
			Durable, Safe and Hygienic Triple Reinforced
			Non-Conductive Hose
			Safety The research to eith Section Code Code
			Thermostat with Safety Cut-Out
			Double Poles ELCB System with 10mA sensitivity
			Splash Proof IP25 Casing
			SVF Valve With Built-In Filter
			INNOVATIVE FEATURES
			Urban & Stylish Design Adjust To The
			Temperature You Desire
			Stepless Electronic Power Control System
			Desire Temperature
			Booster Power Icon
			Energy Saving & SilentPlus Technology
			Quiet Operation (Below 35dB)
			Inverter DC Pump Icon
			Turbo Charge Your Shower with Energy Saving
			Premium Colour Finish
			Premium & Long Lasting Colour Finish
			Double Layer 2K Spray Paint Finish
			(Colour models only)
			SAFETY FEATURES
			High Protection Against Water SplashWater
			Splash Icon
			High Protection Against
			Water Splash
			Comply with IEC 60529 (IP25) Standard
			ELCB System Icon
			The Safest Protection
			Against Current Leakage
			Double Poles ELCB
			complete with accessories



48	set	2	Smart TVs, 50"
			Display Size: 50"
			Ports Input: OTHERS, HDMI, USB, Component
			in (Y/PB/Pr), RF in (Terrestrial/Cable Input),
			Digital Audio Out (Optical), Audio Out (Mini Jack),
			Ethernet (LAN), Composite in (AV)
			TV Features: Netflix, HDR, Cinema 3D, Wireless
			Connectivity, Web Browser, Mobile Screen
			Mirroring, Youtube, DTS Audio, Bluetooth
	1		Connectivity
			TV Resolution: 4K UHD
40		24	Smart TV OS: Android OS
49	unit	24	Stand Fan, 405 mm diameter, 220 volts
			■Durable High-performance motor
			■3-speed push button switch
			■Thermal fuse protection
			■Oscillation
			■With height adjustment
50	unit	5	Exhaust Fan (Industrial wall exhaust fan, 12")
51	set	7	Wireless Microphone
			Carrier Frequency: UHF 613 - 870MHz
			Frequency Steadying: -0.002-
			Modulating Mode: FM
			Audio Dynamic Range: Over 70 dB
			Audio Frequency Responses: 100Hz - 15KHz
			Audio Output Level: 0 - 280mV
			S/N Ratio: Over 70bdB
			T.H.D: -0.5-
			Sensitivity: 3uVFor30dBS/N



Section VII. Technical Specifications



Technical Specifications

Item No.	Unit	Qty	Description	Statement of Compliance
1	рс	11	18" STAND FAN	
			Product Overview	[Bidders must state here either
			Reliability (Motor Life)	"Comply" or "Not Comply" against
			Performance: 7,000 hours	each of the individual parameters of each Specification stating the
			Energy Efficient	corresponding performance
			Less Power Consumption	parameter of the equipment
			Energy Savings up to 10% with the new motor vs. Existing	offered. Statements of "Comply" or "Not Comply" must be
			New Modern Design	supported by evidence in a
			Elegant Design	Bidders Bid and cross-referenced
			New Modern "Minimalist" Design	to that evidence. Evidence shall
			Warranty	be in the form of manufacturer's un-amended sales literature,
			Parts: 1 year	unconditional statements of
			Labor: 1 year	specification and compliance
			Motor Warranty: 3 Year	issued by the manufacturer,
			General Specifications	samples, independent test data
			Blade Material / Size, cm: PP / 40	etc., as appropriate. A statement that is not supported by evidence
			Wattage (W, Max): 60	or is subsequently found to be
			RPM (Max): 1350	contradicted by the evidence
			Air Delivery (\M3/min. Max): 119	presented will render the Bid
			Max Center Height, mm: 1,197	under evaluation liable for
			Height Adjustment: Free Stop Mechanism	rejection. A statement either in the Bidder's statement of
			Stroke, mm: 150	the Bidder's statement of compliance or the supporting
			Switch Type: 3 Speed Piano Switch	evidence that is found to be false
			Vertical Angle Adjustment: Free Neck	either during Bid evaluation, post-
			Oscillation: Double	qualification or the execution of
			Color: Black	the Contract may be regarded as
2	рс	20	18" Wall Mount Oscillating Hydroponic-Clarify	fraudulent and render the Bidder or supplier liable for prosecution
	_		Fan Keeps room and leaf temperatures down	subject to the applicable laws and
			Smooth and quiet operation	issuances.]
			90° oscillating action	
			Pull to change speed and Pull for oscillating or	
			one position.	
			Assembly required	
		<u> </u>	Assumbly required	_



		1	1
3	рс	3	2 BURNER GAS STOVE
			■Heavy duty gas stove
			■High quality fuel-efficient burner
			■Durable metal gas ignition controls
			■Stainless metal gasket and body
			■Auto-ignition burner
			o # of burners: 2
			■ Dimensions: (W x L X D) 71 x 35.5 x 8.5cm
			28 x 14 x 3.3 inches
			■Burner diameter: 9cm 3.5 inches Outer ring
			diameter: 22.5cm 8.9 inches
			■Space in between outer rings: 20cm 7.9
			inches
			© Color: silver
			■Warranty: 1 year
4	set	6	Air Condition, Split type, Inverter, 1.5 HP
			Wattage: 1250 Watts
			EER Rating: 14.26
			WindFree Technology
			Digital Inverter Boost
			Fast Cooling
			Cooling capacity: at least 12,500 kj/hr
			Easy Filter Plus
			DuraFin
			Triple Protector Plus
			Quiet Mode
			Single User Mode
			R32 Refrigerant
			12x Tapping Screw
			4x Rubber Foot (Outdoor Package)
			2x Remote Control Batteries
			Mounting Bracket
			wall mounted
			EER rating above 10
			with remote control
			with one year warranty on parts and services
			with free installation
5	set	2	Air Condition, Split type, Inverter, 2.0 HP
			■Cooling capacity: at least 18,500 kj/h



			Ewall mounted
			wall mounted
			■EER rating above 10
			with Quiet Mode
			with remote control
			with Anti bacterial air filter
			with Micro Dust Filter
			with at least 10 years compressor warranty
			■ offer must be in the market for at least 10 years
			with at least 10-Year Warranty on Compressor
			with one year warranty on parts and services with free installation
c		4	
6	unit	4	Aircon Split Type (1.5 HP) Dimensions
			Net Dimensions (W x H x D):
			Indoor - 779mm x 290mm x 209mm Outdoor - 780mm x 542mm x 289mm
			Gross Dimensions (W x H x D): Indoor - 861mm x 364mm x 255mm
			Outdoor - 891mm x 603mm x 396mm
			Power Requirements:
			230 V
			Power Consumption:
			750 W
			General Specifications
			Remote: Yes
			Timer: Yes
			Cooling Capacity: 11,020 kj/h
			Control Type: With remote
			Cooling Area (sq. meters): Survey is
			recommended
			Noise Level (Indoor) – Low: 28dB
			Filter: Yes
			Airflow Direction Control (Up & Down): Automatic
			Airflow Direction Control (Left & Right): Manual
			Temperature Control: With remote
			Fan Speed: 5 Speed Level
			Energy Efficiency Ratio: 14.69
			with free installation
7	:4	4	Aircon Split Type 2.5 HP Inverter , With
7	unit	4	Installation
			Capacity: 2.5HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 24,000 Btu/h
			Cooling Input: 2,000W
			Cooling Current: 8.7A
			EER: 12.7
			Indoor Unit



			ALEL /100AUL \ 1000 0== ==0 0"
			Air Flow (Hi/Mi/Lo): 1063x955x759 m3/h
			Noise Level (Hi/Mi?Lo): 50/–/40 dB (A)
			Unit Dimension (W*D*H) : approx.
			1080x336x326mm (Indoor Unit)
			Outdoor Unit
			Compressor Type: Rotary
			Unit Dimension (W*D*H) : Approx.
			845x363x702mm (outdoor unit)
			Application Area: 29-43sqm
			One (1) year warranty on parts and service five
			(5) years on compressor provided that the unit is
			installed by accredited installation team
			With Free installation
8	unit	3	Aircon, Split Type, 1HP (Inverter)
			Features:
			* High-density Dust Filter
			* Smooth Frequency Control
			* Gold Fin Protection
			* Silver Ion Filter
			* Sleep Mode
			* Turbo Mode
			* Louver Position Memory
			* Fast Cooling
			*with remote control
			Specifications:
			* 1.0HP Inverter
			* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)
			* 700 (290-990) Power Input (W)
			* 4.32 CSPF
			* R32 Refrigerant
			* 39.5/34/32 dB (A) Sound Level (H/M/L)
			1 year warranty
			with free installation
9	рс	2	Airconditioning Unit
	"		Split Type, Air-conditioning Unit with 2.5 HP
			Remote control with 24 hours programmable
			timer ON/OFF
			Cooling Capacity (min-max): 6.10 (1.12-7.18) kW,
			21,960 (4,030-25,850) kJ/h
			EER (min-max): approx. 14.17 (16.12-12.61)
			kJ/hW,
			Voltage: 230 V
			Current: approx. 6.9 A
			with free installation
	рс	2	Bottom Loading Water Dispenser
10	l pc		DOLLOIN LOAUING WALE DISDENSE



			Voltage/frequency: 220V~50Hz
			Cooling Power: 75W
			Heating Power Warm & Hot: Rated Power:
			425W, Heating Power: 425W
			Cold & Hot: Rated Power: 500W, Heating Power: 425W
			Carton Size: 355x325x1040mm
			Actual Product Size: 320x285x980mm
44			Hot Water Temperature: 85 - 95 Degree Celsius
11	unit	1	DEEP FREEZER
			■DEEP FREEZER 13 CUBIC FEET CHEST FREEZER
			FREEZER ■WIRE BASKET SHELVING MATERIAL,
			approx. 216 WATTS; NO FROST; WITH
			INVERTER
			■CHARCOAL DEODORIZER. 220V or auto
			voltage
		_	Dehumidifier for Extra Large Rooms and
12	рс	1	Basements
			Includes: Washable Filter, Built-in Handles and
			Wheels, Drain Hose Outlet
			Weight: at most 40 lbs
			Rated Current: approx. 4.7 Amps
			Moisture Removal: 70 pints per day
			Air CFM Range (cubic feet per minute): 165
			(Normal) to 188 (Turbo)
			Removable Water Tank Capacity: at least 1.6
			gallons / 6 liters
			Certifications: UL & Energy Star rated
			Features: Touch Control Panel; Auto Restart,
			Shut Off, Defrost; Turbo Mode; Continuous
			Dehumidifying; 24-hour Timer; Custom Humidity
			Level from 35% to 85%
			Spaces between 2500 and 4000 square feet, with
			room temp from 41°F to 95°F
			Power: 220/240V
13	set	1	Digital Duplicator Machine, Copy printer,
13	361	'	300x600 DPI printing
			Master Making/Printing Methods: High-speed
			digital master-making/Fully automatic printing
			Scanning: 600 dpi × 600 dpi
			Printing: 300 dpi × 600 dpi, Quick Master Making
			mode: 300 dpi × 400 dpi
			Maximum Scanning Area: 297 mm × 432 mm
			Print Paper Weight: 46 gsm to 157 gsm
			Print Paper Size: 100 mm × 148 mm to 310 mm ×
			432 mm
			Maximum Printing Area: 210 mm × 357 mm
			Paper Feed Tray Stacking Capacity: 1000



			1	
			sheets*2, stacking height of 110 mm or lower	
			Paper Receiving Tray Stacking Capacity: 1000	
			sheets*2, stacking height of 110 mm or lower	
			Print Speed: 5 levels: 60, 80, 100, 120 and 130	
			ррт	
			Functions: Original Scanning mode, Scanning	
			Level, Enlargement/Reproduction, Dot Process,	
			2-Up, Book, Ink Saving, Quick Master Making,	
			ADF-Semi-Auto*3, Speed, Density, Print Position,	
			Program A/B, Job Separation*3, Idling,	
			Confidential, Meter Display, Count Report Output,	
			Proof, Direct Printing, USB Flash-via-Printing,	
			Auto Sleep Setting, Auto Power-OFF Setting,	
			ECO mode, RISO iQuality System	
			Ink Supply: Full automatic (1000 ml/cartridge)	
14	unit	2	Dry Seal, Customized Machine Engraved, Stainless Steel Material	
15		8	Electric fan	
13	рс	0	Stand fan 16" metal blade	
			Adjustable height	
46	:4		Story Standing May read Airconditionar	
16	unit	4	Floor Standing Mounted Airconditioner	
			■Energy Saving Compressor, 3D Air Delivery System	
			System with Sleep Mode	
			■with Sieep Mode ■with Auto On / Off Timer	
			with High Efficiency Air Filter with Remote Control	
			■ Air Conditioner Rated Capacity (BTUs) at least 2.5	
17	unit	1	Gas Stove, 4 Burners, Heavy Duty	
- 11	anne		4 Gas Burners	
			Rust Proof	
			Black Enamel Pan Support	
			0.5mm Painted cold-rolled steel Side panel	
			0.4mm Stainless Steel Surface	
	1		Whirlwind Burner	
			90mm Double / 40mm / 90mm Double burner /	
			90mm Double	
			Cast Iron Burner with Stainless Steel Burner	
			Cover	
			Automatic Ignition	
	 		Save Gas More than 30%	
·				
			Quantity: 1set	
			Quantity: 1set Net Weight: 7.2kg	
			Quantity: 1set Net Weight: 7.2kg Unit Dimension: 480x570x125mm	



	1		D
			Power input: 1000W
			Airflow: 35l/s
			Capacity: 10 Liters or 3 Gallons
			Cord Length: 3m
			4 in 1 application: wet, dry, indoor & outdoor
			Strong handle for easy carrying
			Large switch button with waterproof design for
			safe & easy operation
40	••		Comes with complete accessories
19	unit	1	Heavy Duty Combo Binding Machine
			ΦSpecs:
			Maximum Punching Sheets: 25
			■Max Size: LS, F4, A4, Extra Long
			Selectable Punching Pins: 24 slots
			Net Weight: 12.5kgs
20	рс	1	Heavy Sheetfed Scanner
			Technology
			Scanner Type: Sheetfed Scanner
			Optical Resolution (ADF): 600 DPI x 600 DPI (Horizontal x Vertical)
			Optical Resolution: 600 DPI x 600 DPI (Horizontal x Vertical)
			ADF Minimum Document Size: 50.8 mm x
			50.8 mm (Horizontal x Vertical)
			ADF Maximum Document Size: 215.9 mm x
			6,096 mm (Horizontal x Vertical)
			Paper Formats
			A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6
			(10.5x14.8 cm), B6 (12.5x17.6 cm), B5
			(17.6x25.7 cm), B4 (25.7x36.4 cm), Letter, Legal,
			Postcard, Business cards, Plastic cards
			Scanning color depth
			Input: 30 Bits Color / 10 Bits Monochrome,
			Output: 24 Bits Color / 8 Bits Monochrome
			Ultrasonic Sensor: Yes
	<u> </u>		High Capacity, General Office
			Scanner
			Light Source: ReadyScan LED technology
			Output Resolution:1200 DPI
			Scanning Speed
			Monochrome: 65 pages/min -
			Color: 65 pages/min measured with Size: A4,
			Resolution: 200 / 300 dpi,
			Monochrome: 130 image/min
			Color: 130 image/min measured with Size: A4,
			Resolution: 200 / 300 dpi
			Paper / Media Handling
			Paper Setting Capacity:100 Sheets



			Auto loodings 07 440 c/m²
			Autonotic Document Fooder Type
			Automatic Document Feeder Type
			Single pass dual scanning
			Reliability Daily Duty Cycle: 7,000 pages
			Automatic Document Feed:100 pages
			Duplex Scan:Yes
			Scanning Features
			Output formats:BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG
			File compression features:Hardware JPEG
			compression, TIFF Compression (JPEG(7), CITT
			G4, LZW), PDF Compression
			Advanced document integration:Scan to Email,
			Scan to FTP, Scan to Microsoft SharePoint®,
			Scan to Print, Scan to Web folders, Scan to
			Network folders
			Scanning Volume:7,000 Pages per day
			Connectivity
			Interfaces:USB 2.0 Type B, USB 3.0 Type B
			Options: Roller Assembly Kit
21	unit	6	Hot & Cold water dispenser
			Bottom load water dispenser
			■3 Faucets: Hot, Cold and Normal water function
			■3-Push Button dispensing control
			■Anti-scald safety lock switch
			©Child Lock Safety feature on Hot Water Faucet
			Selection indicator to avoid water overflow Consoit in the description of the consoit in the c
			©Capacity: Hot - 1.2 Liters, Cold - 3.5 liters,
			Power Rating: Hot - 420 watts, Cold - 100 watts, R134a
22	рс	1	Laminator
	Po	•	A4 Hot and Cold Laminating Machine
23	unit	1	Microwave Oven
	3	•	Capacity: 32 litres
			Dimension: 517 x 297 x 384mm
			Power source: 220V / 60Hz
			Power Consumption: 1500W
<u> </u>			Mirrorless Camera, 24.1MP, 3" LCD Monitor,
24	unit	1	4K Video
			AF Modes - Stills: One-Shot AF, Servo AF,
			Manual Movie recording: One-Shot AF, Movie
			Servo AF, Manual
			AF Point Selection - Automatic selection, Manual
			selection
			AF System Points - Stills: Max. 3975 selectable
			AF point positions / Up to 143 zones (auto
			selection)
			Movie recording: Max. 3375 selectable AF point



positions / Up to 117 zones (auto selection)
Built-in Flash
Closest Focusing Distance (cm) - 25
Continuous Shooting Speed (Shots Per Sec) (Up
To) - 10 (One-Shot AF) / 7.4 (Servo AF)
Digital Zoom - Approx. 3-10x (for movie recording
only)
Drive System - Stepping Motor-driven lead screw
+ rack system
Effective ISO - Stills: 100 - 25,600 (H:51,200),
Movie (full HD/HD): 100 - 12,800 (H: 25,600),
Movie (4K): 100 - 6,400
Exposure Compensation - ±3 stops in 1/3-stop
increments, AEB: ±2 stops in 1/3-stop increments
Eye Detection AF - One-Shot AF / Servo AF /
Movie Servo AF
Flash Modes - E-TTL II Autoflash, FE Lock,
Manual pop-up, Retractable, Built-in
Focal Length (35mm Equivalent) - 24 - 72mm(3x)
Guide Number ISO 100 metres - 5
Image Resolution - 6000 x 4000 (L), 3984 x 2656
(M), 2976 x 1984 (S1), 2400 x 1600 (S2), 6000 x
4000 (RAW/C-RAW)
Image Stabilizer - Stills: Lens shift type, Movie
recording: Lens shift type & In-body 5-axis
electronic image stabilization (movie recording
only)
with Manual Focus
Memory Card Type - SD, SDHC*, SDXC*, *UHS-I
cards compatible
Metering Mode - Stills: Evaluative, Partial, Spot,
Center-weighted average, Movie: Evaluative
(when faces are detected with [Face+Tracking]),
Center-weighted average (when no faces are
detected)
Processor Type - DIGIC 8
Sensor Size - APS-C
Shooting Modes - Stills: Scene Intelligent Auto,
Hybrid Auto, Special scene modes (Self Portrait,
Portrait, Smooth Skin, Landscape, Sports,
Panning, Close-up, Food, Night Portrait,
Handheld Night Scene, HDR Backlight Control,
Silent Mode), Creative filters (Grainy B/W, Soft
focus, Fish-eye effect, Water painting effect, Toy
camera effect, Miniature effect, HDR art
standard, HDR art vivid, HDR art bold, HDR art
embossed), Program AE, Shutter-priority AE,
Aperture-priority AE, Manual Exposure, Movie
recording: Movie auto exposure, Movie manual



			T
			exposure
			Shutter Speed Range (Sec.) - Stills: 30 - 1/4000,
			Bulb, Movie recording: 1/25 - 1/4000 (PAL) or
			1/30 - 1/4000 (NTSC)
			Standard Power Supply - LP-E12
			Silent Shutter - Available: Single Shot
			Still Image Format - JPEG, RAW, RAW + JPEG,
			C-RAW, C-RAW+JPEG
			Viewfinder Coverage (Approx.) - 100%
			Viewfinder Type - 0.39-inch OLED, 2.36million
			dots, 59.94fps refresh rate
			White Balance - Auto (Ambience priority), Auto
			(White priority), Preset (Daylight, Shade, Cloudy,
			Tungsten light, White fluorescent light, Flash),
			Custom, Color temperature setting (approx.
			2500-10000 K), White balance correction and
			white balance bracketing features provided,
			*Flash color temperature information
			transmission possible
			X-sync (sec.) - 1/200
25	рс	1	Paper shredder machine, heavy duty
			Shred Type: Cross Cut
			■Maximum Sheet capacity(70gsm) : 10 Sheets
			■Waste Container capacity: 21 Liters
			■Power Source: 220 - 240 VAC
26	unit	1	Photography Camera Tripod, Lightweight
			Compatible with Mirrorless Camera (Canon,
			Nikon, Fuji, Pentax, etc.)
27		2	Portable Trolley 15" Speaker with wireless
27	unit		microphone
			■15" 2 Way 480 Watts Powered Portable Sound
			System
			■Plastic Cabinet
			■AC220V or DC12V (With built-in Rechargeable
			Batteries)
			■With 2 Wireless Microphone
			■With 2 Mic Input (1 XLR, 1 PL55)
			■With FM Radio, Bluetooth, Guitar Input (Shared
			with Mic 2 input), USB & SD Port
			■With 5 Band Equalizer and LCD Display
	 		■With Aux / Line In and Line Out
	1		■With Remote Control, Handle and Wheel
28	unit	1	Refrigerator
20	unit	1	uses a compressor or evaporator to circulate
			cooled air or water around the samples
			7 cu. ft. HD Inverter No Frost Refrigerator
	1		Bottom Freezer
	ļ		Heavy Duty Inverter



			Farmer F. William L. Oranger
			Energy Efficient Compressor
			Triple Bottom Freezer Drawers
			Fresh Zone Drawer (Crisper)
			Independent Temparature Control for Fridge and
			Freezer
			Recessed Handle
			Stainless Steel Finish
			Net Weight: 52kg
			Gross Weight: 57kg
			Gross Dimension (h:w:d): 166:55:64 cm
29	unit	1	Refrigerator
			Transparent door, Upright at least 10 to 12.4
			Cubic Feet inverter
			Transparent Anti Frost Double Layered
			Tempered Glass Door
			Adjustable Shelves
			Efficient Cooling
			Interior Lights
			Input 220/240V, 50/60 Hz with power cord & plug
			Automatic voltage stabilizer with time delay
			restart
30	рс	1	Refrigerator- at least 6.0 cu.ft. (Two-door) inverter
			■Two-Door Direct Cool Refrigerator
31	unit	1	Smart TV, 70" with Android 10 OS
			■4K Ultra HD
			■Borderless Design
			■Chameleon Extreme
			■Picture Engine
			■Dolby Digital Plus with 12x12w
			■Android 10.0 Q
			■ Bluetooth 5.0
			■Audio: Dolby Digital Plus
			■ DTS TruSurround
			© Equalizer
			■ Quad-Core
			■Internal Memory: 8GB
			■RAM: 2GB
			■ With Voice Search
			■Google Assistant
			· ·
			■Chromecast Built-in or Wireless Display
			■Chromecast Built-in or Wireless Display■Wi-Fi Connectivity 2.4G■2T2R
			⊠ Wi-Fi Connectivity 2.4G
			■Wi-Fi Connectivity 2.4G■2T2R
			■Wi-Fi Connectivity 2.4G ■2T2R ■Android 10.0



			-Usani Duki far 40 0 44 -! ' f II ''
			■Heavy Duty, for A3 & A4 size, infrared heating
			system and adjustable temperature control with
33	unit	3	overheating protection Aircon, Window Type, 2HP Inverter
33	uiiit	<u> </u>	2.0 HP, Inverter Window Type
			R32 Refrigerant
			High Energy Efficiency Ratio
			All-DC Motor
			Room Temperature Display & Setting
			Air Swing Control
			Filter Clean Indicator
			Power Source 230, 60, 1Ø (V, Hz, Ph)
			Cooling Capacity 18,750 (kJ/h)
			Current 7.3 (A)
			Input Power 1563 (W)
			EER Rating 12.0 (kJ/hW)
			Recommended Floor Area 23 – 33 m ²
			Moisture Removal 2.8 (L/h)
			Noise Level Indoor (dB-A) 51 / 48 (H / L)
			Air Circulation (indoor) 14.2 m3/min
			Air Circulation (outdoor) 23.0 m3/min
			Timer (12-Hour On/Off)
			Fan Speed
			Auto / Cool / Dry Mode
			Powerful mode
			Sleep Mode
			Quiet Mode
			Blue Fin Condenser (anti-corrosion fin)
			Anti-Bacterial Filter
			Wireless Remote Control
			Random Auto Restart
34	unit	2	Aircon Split Type (2 HP)
			Capacity: 2.HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 18,000 Btu/h
			Cooling Input: 1552W
			Cooling Current: 6.75A
			EER: 12.24 Air Flow (Hi/Mi/Lo): 848x796x626m3/h
			Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)
			Unit Dimension (W*D*H) : 965x203x323mm
			(Indoor Unit)
			Refrigerant Type: R32
			Compressor Type: Rotary
			Unit Dimension (W*D*H) : 914x343x546mm (
			outdoor unit)
			Application Area: 23-33 sqm



	 		TA 1 1 1 1 1 1 1 1
			Accesories such as breaker, bracket and copper
			tubbing not included
			One (1) year warranty on parts and service &
			compressor
			with free installation
35	unit	21	Aircon, Window Type, 1.0HP (Inverter)
			1HP Inverter, 8-in-1 Filter, R410A
			Energy Savings Feature:
			24-hour Timer
			Energy Saving Plug
			Econo and Sleep Mode
			EER Rating: 11.6 (10.8 - 10.7)
			Sleek, Modern Aesthetic
			Remote Control
			2 x AAA Batteries
			With Free Installation
			1 year warranty
36	рс	1	Water Dispenser, Cabinet type
			■Floor standing
			■Hot and cold function
			■plastic body,high efficiency compressor
			■thermally protected
37	set	1	Sound System
			Type:Portable PA System
			Speaker Drivers:1 x 8" woofer, 1.35"
			compression driver
			Number of Mixer Channels:6
			Number of Mic Preamps:2
			EQ:Treble, Bass, 5-band Graphic
			Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x
			stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in)
			Outputs:2 x 1/4" (speaker out)
			USB:1 x Type A (ULM wireless ready)
			Bluetooth: Yes
			Total Power:500W
			Frequency Response:50Hz-22kHz
			Microphone:1 x Behringer XM1800S
			Power Source:Standard IEC AC cable
			Height:25.9"
			Width:13.9"
			Depth:34.8"
			Weight:44.7 lbs.
38	unit	1	Sliding Paper Cutter
			Working Area: A3 and A4
			Cutting Capacity: 16 sheets
			Packing Weight: 5 kg
			Tacking Weight. 5 kg



			Available Size: A3 and A4
			Packing Measurement: 56x34x11 cm
			Other Specifications: Heavy duty for Vinyl
			Cardboard Paper
39	no	1	Sony Electret Condenser Microphone for lape
33	рс	I	mic (for compatibility)
			3.5 mm connector
40	unit	1	Vacuum cleaner, wet and dry, 1200 watts
			1200 Watts power
			At least 30L dust/liquid capacity
			Double stage long life motor
			With auto shut-off function
			With blower function
			Washable ecological HEPA filter At least 3 meters flexible hose
			At least 9 meters power cord length
			With handrail/handle for easy transport
			Accessories:
			Extension tube
			Bristle brush
			Crevice nozzle
			2-in-1 brush and round brush
			Floor/carpet brush
			Wet/dry floor brush
			Washable HEPA filter
			Washable HEPA filter Flexible extension tube
41	рс	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13
41	рс	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels
41	рс	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels ■30 Liters capacity
41	рс	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels © 30 Liters capacity © Grill and convection
41	pc	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control
41	pc	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels © 30 Liters capacity © Grill and convection
41	pc	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system
41	pc	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels
41	pc	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels
			Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser
			Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold
42		1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling
			Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart
42	unit	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart 32 inch television, Smart
42	unit	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart 32 inch television, Smart Resolution: 1,366 x 768
42	unit	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart 32 inch television, Smart Resolution: 1,366 x 768 HDMI Ports: 2
42	unit	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart 32 inch television, Smart Resolution: 1,366 x 768 HDMI Ports: 2 USB Ports: 1
42	unit	1	Washable HEPA filter Flexible extension tube Microwave Oven, Digital, Non-Inventer, 13 Power Levels 30 Liters capacity Grill and convection electronic control dual wave system 13 power levels 900W Non-Inventer Hot and Cold Table Top Water Dispenser Table top water dispenser Hot and cold Electronic type cooling Television, Smart 32 inch television, Smart Resolution: 1,366 x 768 HDMI Ports: 2



			0 (0) (11 (0) (14) (1 D) 700 0 (40) 0
			Set Size without Stand (WxHxD): 732.9 x 440.3 x
4.4		46	78.5 mm
44	unit	16	Cordless Kettle
			Electric Glass Kettle, Cordless
			HWK-118GI
			Power: 230V - 60Hz, 2000W
			Capacity: 1.8L
			360 degree rotary base, easy to use with high
			borosilicate glass body,
			Durable and stain resistant blue LED light
			indication when boiling Concealed stainless steel
			heating element Automatic one button cover starter boiling dry protection Automatically
			turns off when water boiled.
			Active Speaker, 12", 1000W peak two-way, full
45	unit	1	range
			-1000 watts(peak) 500 watts (program)
			-Superior DSP processing with component
			protection
			-12-inch woofers with 2.5-inch voice coils
			-1-inch HF compression drivers
			-90 x 60 deg. HF dispersion
			-Dual purpose full-range and wedge monitor
			speaker
			-Ultra-clear reproduction throughout the whole
			audio bandwidth
			-Recessed control panel
			-Master Level control with activity indicator (
			cabinet level adjustment)
			-3 performance modes, concert, club and monitor
			-Defeatable 3 channelmixer with lecel controls
			and clip indicators
			-Bluetooth input/streaming, not affected by mixer
			defeat
			-2 microphone inputs with level and phantom
			power
			-1/4-inch TRS Instrument and Line Inputs
			-18-inch AUX input for connecting or stereo audio
			sources
			-an XLR Main In & link output for easy connection
			and looping
			-Selectable Sub Filter (HPF) for connecting a
			subwoofer
46	unit	2	Wireless Microphone Mic System, 2.4G, 6 channels
			■2.4G wireless Microphone Mic System 6
			channels XLR Connection Built-in Rechargeable
			Lithium Battery



			© Compact size 2.4G wireless microphone
			system, XLR connection, easy to use
			eless than 4ms ultra-low latency, clear and
			stable signal transmission
			■32bit/48Khz high resolution audio quality
			■Built -in rechargeable lithium battery
47	unit	10	Shower Heater with Inverter Booster Pump
			Features
			Sleek and Stylish Casing
			Energy Saving Inverter DC Pump 50%
			Silent Below 35dB
			Double Layer 2K Spray Paint Finish with 3 Colour
			Options
			Stepless Electronic Power Control
			Accessories
			5 Spray Showerhead
			Slim and Chromed Slider Bar
			1/4 Turn Valve for turn On/Off Shower
			Durable, Safe and Hygienic Triple Reinforced
			Non-Conductive Hose
			Safety
			Thermostat with Safety Cut-Out
			Double Poles ELCB System with 10mA sensitivity
			Splash Proof IP25 Casing
			SVF Valve With Built-In Filter
			INNOVATIVE FEATURES
			Urban & Stylish Design
			Adjust To The
			Temperature You Desire
			Stepless Electronic Power Control System
			Desire Temperature
			Booster Power Icon
			Energy Saving & SilentPlus Technology
			Quiet Operation (Below 35dB)
			Inverter DC Pump Icon
			Turbo Charge Your Shower with Energy Saving
			Premium Colour Finish
			Premium & Long Lasting Colour Finish
			Double Layer 2K Spray Paint Finish
			(Colour models only)
			SAFETY FEATURES
			High Protection Against Water SplashWater
			Splash Icon High Protection Against
			High Protection Against Water Splash
			Comply with IEC 60529 (IP25) Standard
			ELCB System Icon



			T
			The Safest Protection
			Against Current Leakage
			Double Poles ELCB
			complete with accessories
48	set	2	Smart TVs, 50"
			Display Size: 50"
			Ports Input: OTHERS, HDMI, USB, Component
			in (Y/PB/Pr), RF in (Terrestrial/Cable Input),
			Digital Audio Out (Optical), Audio Out (Mini Jack),
			Ethernet (LAN), Composite in (AV)
			TV Features: Netflix, HDR, Cinema 3D ,Wireless
			Connectivity, Web Browser, Mobile Screen
			Mirroring, Youtube, DTS Audio, Bluetooth
			Connectivity
			TV Resolution: 4K UHD
			Smart TV OS: Android OS
49	unit	24	Stand Fan, 405 mm diameter, 220 volts
			■Durable High-performance motor
			■3-speed push button switch
			■Thermal fuse protection
			■Oscillation
			■ With height adjustment
50	unit	5	Exhaust Fan (Industrial wall exhaust fan, 12")
51	set	7	Wireless Microphone
			Carrier Frequency: UHF 613 - 870MHz
			Frequency Steadying: -0.002-
			Modulating Mode: FM
			Audio Dynamic Range: Over 70 dB
			Audio Frequency Responses: 100Hz - 15KHz
			Audio Output Level: 0 - 280mV
			S/N Ratio: Over 70bdB
			On Natio. Over robub
			T.H.D: -0.5-



Section VIII. Checklist of Technical and Financial Documents



Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE

Class "A" Documents

<u>Legal Do</u>	<u>cuments</u>
(a)	Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages);
<u>Technica</u>	<u>l Documents</u>
(b)	Statement of the prospective bidder of all its on-going government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid; and
(c)	Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid in the amount of <u>at least 50% of the ABC</u> or at least One Million Eight Hundred Seventy Five Thousand Pesos (PhP 1,875,000.00);
(d)	Statement of at least two (2) similar completed contracts, the aggregate amount of which should be equivalent to <u>at least 25% of the ABC</u> or at least One Million Eight Hundred Seventy Five Thousand Pesos (PhP 1,875,000.00) and the largest of these similar contracts must be equivalent to at least half of the said aggregate amount or at least Nine Hundred Thirty Seven Thousand Five Hundred Pesos (PhP 937,500.00) ; <u>and</u> Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission;
(e) (f) (g) (h)	or Original copy of Notarized Bid Securing Declaration; and Conformity with the Technical Specifications; and Schedule of Requirements/production and delivery schedule; and Manpower requirements; and After-sales service/parts; and
[] (i)	Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.
Financia.	The Supplier's audited financial statements, showing, among others, the Supplier's total and current assets and liabilities, stamped "received" by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission; and
(k)	The prospective bidder's computation of Net Financial Contracting Capacity (NFCC) – at least equal to ABC (PhP 3,750,000.00); or A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation (at least 10% of ABC or PhP 375,000.00).



II. FINANCIAL COMPONENT ENVELOPE

(a)	Original of duly signed and accomplished Financial Bid Form; and
(b)	Original of duly signed and accomplished Price Schedule(s).



Guidelines on the Preparation of Electronic Bid (e-Bid) (for bidders who prefer electronic bid submission)

- 1. Scan per file all documents into Portable Document Format (PDF) and should be printable.
- 2. Properly label all documents for prompt identification. Filename of documents, whichever are applicable to the bidder, should be as follows:

Document		Filename (in PDF form)
1.	PhilGEPS Certificate of Registration	PhilGEPS
	(Platinum)	
2.	Statement of On-Going Government	Statement of On-Going
	& Private Contracts	Contracts
3.	Statement of Bidder's Single Largest	SLCC
	Completed Contract	
4.	Statement of at least two (2) similar	Statement of Completed
	completed contracts	Contracts
5.	Bid Security	Bid Security
6.	Technical Specifications	Technical Specifications
7.	SCHEDULE of	Schedule of Requirements
	Requirements/Production and	
	delivery schedule	
8.	Manpower Requirements	Manpower Requirements
9.	After Sales service/parts	After Sales
10.	Omnibus Sworn Statement	Omnibus Sworn Statement
11.	Audited Financial Statements	Audited Financial Statements
12.	Net Financial Contracting Capacity	NFCC
13.	Committed Line of Credit	CLC
14.	Bid Form	Bid Form
15.	Price Schedule	Price Schedule

- 3. Create two (2) folders that are password-protected. The first folder should contain all requirements under Technical Component checklist as presented under Section VIII. The second folder should contain all requirements under Financial Component checklist.
- 4. Compress the two (2) folders and name as follows: a) first folder: **Technical Documents**, b) second folder: **Financial Documents**.
- 5. Email the 2 compressed folders to Ms. Jessamine C. Ecleo at **jessamine.ecleo@vsu.edu.ph** before the deadline (March 13, 2024; 8:30 AM).



