



**VISAYAS**  
STATE UNIVERSITY

# **PHILIPPINE BIDDING DOCUMENTS**

(As Harmonized with Development Partners)

## **Supply and Office Equipment (VSU-GOODS-24-03)**

*(early procurement)*

Government of the Republic of the Philippines

**November 8, 2023; 9:00 AM**  
**BAC Conference Room, VSU Market, Visca, Baybay City, Leyte**  
**and via Zoom**

**Sixth Edition**  
**July 2020**

# Table of Contents

<b>Glossary of Acronyms, Terms, and Abbreviations .....</b>	<b>3</b>
<b>Section I. Invitation to Bid.....</b>	<b>6</b>
<b>Section II. Instructions to Bidders.....</b>	<b>25</b>
1. Scope of Bid .....	26
2. Funding Information.....	26
3. Bidding Requirements .....	26
4. Corrupt, Fraudulent, Collusive, and Coercive Practices .....	26
5. Eligible Bidders.....	26
6. Origin of Goods .....	27
7. Subcontracts .....	27
8. Pre-Bid Conference .....	27
9. Clarification and Amendment of Bidding Documents .....	27
10. Documents comprising the Bid: Eligibility and Technical Components .....	27
11. Documents comprising the Bid: Financial Component .....	28
12. Bid Prices .....	28
13. Bid and Payment Currencies .....	29
14. Bid Security .....	29
15. Sealing and Marking of Bids .....	29
16. Deadline for Submission of Bids .....	29
17. Opening and Preliminary Examination of Bids .....	30
18. Domestic Preference .....	30
19. Detailed Evaluation and Comparison of Bids .....	30
20. Post-Qualification .....	31
21. Signing of the Contract .....	31
<b>Section III. Bid Data Sheet .....</b>	<b>32</b>
<b>Section IV. General Conditions of Contract .....</b>	<b>34</b>
1. Scope of Contract .....	35
2. Advance Payment and Terms of Payment .....	35
3. Performance Security .....	35
4. Inspection and Tests .....	35
5. Warranty .....	36
6. Liability of the Supplier .....	36
<b>Section V. Special Conditions of Contract .....</b>	<b>37</b>
<b>Section VI. Schedule of Requirements .....</b>	<b>42</b>
<b>Section VII. Technical Specifications .....</b>	<b>59</b>
<b>Section VIII. Checklist of Technical and Financial Documents .....</b>	<b>75</b>

# *Glossary of Acronyms, Terms, and Abbreviations*

**ABC** – Approved Budget for the Contract.

**BAC** – Bids and Awards Committee.

**Bid** – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

**Bidder** – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

**Bidding Documents** – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

**BIR** – Bureau of Internal Revenue.

**BSP** – Bangko Sentral ng Pilipinas.

**Consulting Services** – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

**CDA** - Cooperative Development Authority.

**Contract** – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

**CIF** – Cost Insurance and Freight.

**CIP** – Carriage and Insurance Paid.

**CPI** – Consumer Price Index.

**DDP** – Refers to the quoted price of the Goods, which means “delivered duty paid.”

**DTI** – Department of Trade and Industry.

**EXW** – Ex works.

**FCA** – “Free Carrier” shipping point.

**FOB** – “Free on Board” shipping point.

**Foreign-funded Procurement or Foreign-Assisted Project**– Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

**Framework Agreement** – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as “Call-Offs,” are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

**GFI** – Government Financial Institution.

**GOCC** – Government-owned and/or –controlled corporation.

**Goods** – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term “related” or “analogous services” shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

**GOP** – Government of the Philippines.

**GPPB** – Government Procurement Policy Board.

**INCOTERMS** – International Commercial Terms.

**Infrastructure Projects** – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

**LGUs** – Local Government Units.

**NFCC** – Net Financial Contracting Capacity.

**NGA** – National Government Agency.

**PhilGEPS** - Philippine Government Electronic Procurement System.

**Procurement Project** – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

**PSA** – Philippine Statistics Authority.

**SEC** – Securities and Exchange Commission.

**SLCC** – Single Largest Completed Contract.

**Supplier** – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

**UN** – United Nations.

***Section I. Invitation to Bid***



## INVITATION TO BID FOR SUPPLY AND DELIVERY OF OFFICE EQUIPMENT

- The *Visayas State University* through the *GF 2024* intends to apply the sum of *Four Million Seven Hundred Twenty Four Thousand One Hundred Pesos (PhP 4,724,100.00.00)* being the ABC to payments under the contract for *Supply and Delivery of Office Equipment (VSU-GOODS-24-03)*. Bids received in excess of the ABC shall be automatically rejected at bid opening.

The *Visayas State University*, through the *GF 2024* intends to apply the following ABC per item to payments under the contract for each item, to wit:

Item #	Description	Unit	Qty	Unit Price	Total Price
1	<b>1.5 hp Inverter Window-Type Air Conditioner</b>	unit	2	44,000.00	88,000.00
	Capacity : Capacity (Cooling, W)3380 W, Capacity (Cooling, kJ/h)12160 kJ/hW				
	Power Input (Nominal): Cooling1095 W				
	Current Input (Nominal): Cooling4.8 W				
	Power Input (Rated): Cooling1390 W				
	Current Input (Rated): Cooling7.5 W				
	Energy Efficiency:				
	EER (Cooling, W/W): 3.08 W/W				
	Permissible Excessive Operating Pressure for the Discharge Side: 4.3 Mpa				
	Maximum Allowable Pressure: 4.7 Mpa				
	Isolation: I				
	EER (Cooling, Btu/hW): 10.51 Btu/hW				
	Permissible Excessive Operating Pressure for the Suction Side: 2.5 Mpa				
	Climate Type: T1				
	Moisture Protection: IPX4				
	Noise Level				
	Sound Pressure Level (H/M/L, dBA): 54/51/50 dBA				
	Electrical Data				
	Power Source(Φ/V/Hz): 1 / 230 / 60				
	Physical specification				
	Package Dimension (WxHxD, mm*mm*mm): 623*425x806 mm				
	Gross Weight (kg): 48 kg				
	Loading Quantity (20' Container): 125				
	Loading Quantity (40' High Cube Container): 312				
	Net Dimension (WxHxD, mm*mm*mm): 560*375*708 mm				
	Net Weight(kg): 45 kg				

	Loading Quantity (40' Container): 260				
	Technical Information				
	Refrigerant (Type): R32				
	Low Ambient (Cooling, °C): 18~43 °C				
	Refrigerant (Charging, kg): 0.53 kg				
	Compressor Type: Rotary				
	Convenience: 24-Hour Timer (Yes)				
	Operating Mode: Auto Mode (Yes), Dehumidification (Yes), Good Sleep (Yes)				
<b>2</b>	<b>2 BURNER GAS STOVE</b>	<b>pc</b>	<b>2</b>	<b>2,000.00</b>	<b>4,000.00</b>
	☑ Heavy duty gas stove				
	☑ High quality fuel-efficient burner				
	☑ Durable metal gas ignition controls				
	☑ Stainless metal gasket and body				
	☑ Auto-ignition burner				
	☑ # of burners: 2				
	☑ Dimensions: (W x L X D ) 71 x 35.5 x 8.5cm   28 x 14 x 3.3 inches				
	☑ Burner diameter: 9cm   3.5 inches   Outer ring diameter: 22.5cm   8.9 inches				
	☑ Space in between outer rings: 20cm   7.9 inches				
	☑ Color: silver				
	☑ Warranty: 1 year				
<b>3</b>	<b>75 inch interactive display touchscreen Smart TV</b>	<b>unit</b>	<b>1</b>	<b>70,000.00</b>	<b>70,000.00</b>
	Specifications:				
	Picture Engine: Crystal Processor 4K				
	• Color: Dynamic Crystal Color				
	• Contrast: Mega Contrast				
	• Sound: Q-Symphony				
	• Smart: Tap-View				
	• Design: AirSlim				
	Specifications Detail				
	Product Type: LED				
	Series: 8				
	Display				
	• Screen Size: 75"				
	• Resolution: 3,840 x 2,160				
	• Screen Curvature: N/A				
	Video				
	• Picture Engine: Crystal Processor 4K				
	• PQI (Picture Quality Index): 2200				
	• HDR (High Dynamic Range): HDR				
	• HDR 10+: Support				
	• HLG (Hybrid Log Gamma): Yes				
	• Contrast: Mega Contrast				
	• Viewing Angle: N/A				
	• Color: Dynamic Crystal Color				
	• Micro Dimming: UHD Dimming				
	• Auto Depth Enhancer: N/A				
	• Contrast Enhancer: Yes				
	• Auto Motion Plus: Yes				



	• Film Mode: Yes				
	• Natural Mode Support: Yes				
	Audio				
	• Dolby Digital Plus: Yes				
	• Dolby 5.1 Decoder: N/A				
	• Object Tracking Sound: N/A				
	• Q-Symphony: Q-Symphony				
	• Audio Pre-selection Descriptor: N/A				
	• Hole Array Speaker: N/A				
	• Sound Output (RMS): 20W				
	• Speaker Type: 2CH				
	• Woofer: N/A				
	• Multiroom LinkYes				
	• Bluetooth Audio: Yes				
	Smart Service				
	• SMART TV: Smart				
	• Operating System: Tizen™				
	• Bixby: US English, UK English, India English, Korean, French, German, Italian, Spanish, Portuguese (features vary by language)				
	• Voice Interaction: N/A				
	• Far-Field Voice Interaction: N/A				
	• Alexa Built-in: N/A				
	• Google Assistant Built-in: N/A				
	• Works with Google Assistant: N/A				
	• Works With Alexa: N/A				
	• TV Plus: N/A				
	• Web Browser: Yes				
	• Gallery: Yes				
	Convergence				
	• TV to Mobile – Mirroring: N/A				
	• Mobile to TV - Mirroring, DLNA: Yes				
	• NFC on TV: N/A				
	• Tap View: Yes				
	• Digital Butler: N/A				
	• Multi-View: N/A				
	• Sound Wall: Yes				
	• Remote Access: Basic				
	• 360 Video Player: N/A				
	• 360 Camera Support: N/A				
	• Bluetooth Low Energy: Yes				
	• WiFi Direct: Yes				
	• TV Sound to Mobile: Yes				
	• Sound Mirroring: Yes				
	Differentiation				
	• Tune Station: N/A				
	• Auto Hotspot Connect: N/A				
	• S-Share: N/A				
	• Auto Data Backup: N/A				
	• Dongle Compatibility (3G / LTE / WiFi): N/A				
	• Analog Clean View: N/A				

	• Triple Protection: N/A				
	Tuner/Broadcasting				
	• Digital Broadcasting: ISDB-T				
	• Analog Tuner: Yes				
	• 2 Tuner: N/A				
	• CI (Common Interface): N/A				
	• Data Broadcasting: N/A				
	• TV Key Support: Yes				
	Connectivity				
	• HDMI: 3				
	• USB: 2				
	• Component In (Y/Pb/Pr): N/A				
	• Composite In (AV): 1				
	• Ethernet (LAN): Yes				
	• Audio Out (Mini Jack): N/A				
	• Digital Audio Out (Optical): 1				
	• RF In (Terrestrial / Cable input): 1/1(Common Use for Terrestrial)/0				
	• Ex-Link ( RS-232C ): N/A				
	• CI Slot: N/A				
	• HDMI A / Return Ch. Support: Yes				
	• eARC: Yes				
	• HDMI Quick Switch: Yes				
	• Wireless LAN Built-in: Yes (WiFi5)				
	• Bluetooth: Yes (BT5.2)				
	• Anynet+ (HDMI-CEC): Yes				
<b>4</b>	<b>Air Condition, Split type, Inverter, 2.5 HP</b>	<b>pc</b>	<b>7</b>	<b>65,000.00</b>	<b>455,000.00</b>
	Cooling capacity: at least 20,000 kj/hr				
	wall mounted				
	EER rating above 10				
	with remote control				
	with one year warranty on parts and services				
	with free installation with FREE atleast 10- feet copper tube and insulated wire, polyethylene tape, drain hose				
<b>5</b>	<b>Air Condition, Split type, Inverter, 1.5 HP</b>	<b>set</b>	<b>1</b>	<b>45,000.00</b>	<b>45,000.00</b>
	Wattage: 1250 Watts				
	EER Rating: 14.26				
	WindFree Technology				
	Digital Inverter Boost				
	Fast Cooling				
	Cooling capacity: at least 12,500 kj/hr				
	Easy Filter Plus				
	DuraFin				
	Triple Protector Plus				
	Quiet Mode				
	Single User Mode				
	R32 Refrigerant				
	12x Tapping Screw				
	4x Rubber Foot (Outdoor Package)				
	2x Remote Control Batteries				

	Mounting Bracket				
	wall mounted				
	EER rating above 10				
	with remote control				
	with one year warranty on parts and services				
	with free installation with FREE atleast 10- feet copper tube and insulated wire, polyethylene tape, drain hose				
<b>6</b>	<b>Air Condition, Split type, Inverter, 2.0 HP</b>	<b>set</b>	<b>4</b>	<b>55,000.00</b>	<b>220,000.00</b>
	☑Cooling capacity: at least 18,500 kj/h				
	☑wall mounted				
	☑EER rating above 10				
	☑with Quiet Mode				
	☑with remote control				
	☑with Anti bacterial air filter				
	☑with Micro Dust Filter				
	☑with at least 10 years compressor warranty				
	☑offer must be in the market for at least 10 years				
	☑with at least 10-Year Warranty on Compressor				
	☑with one year warranty on parts and services				
	with free installation with FREE atleast 10- feet copper tube and insulated wire, polyethylene tape, drain hose				
<b>7</b>	<b>Air condition, window type, Inverter, 2 HP (Manual), Standard size</b>	<b>unit</b>	<b>1</b>	<b>47,000.00</b>	<b>47,000.00</b>
	at least 12,000 kj/Hr				
	EER: at least 10.5				
	with three speed cooling switch and timer				
	Please add specs				
	Cooling Capacity 2HP				
	Power Input 860W				
	Noise Level Indoor (Low)46 dBA				
	Power Source230V a.c / 1 Phase- 60hz				
	Refrigerant R32				
	Unit Dimension(WxHxD) 560x346x655 mm				
	Packaging Dimension 670x481x728mm				
	Net Weight 38				
	Gross Weight 40				
<b>8</b>	<b>Air condition, Window type, Inverter, 2.5 HP, Standard Size</b>	<b>unit</b>	<b>4</b>	<b>50,000.00</b>	<b>200,000.00</b>
	at least at least 24,000 BTU				
	EER: at least 12.0				
	With remote Control				
<b>9</b>	<b>Air Conditioner, Window Type, 2.5 HP, Standard Size</b>	<b>unit</b>	<b>1</b>	<b>50,000.00</b>	<b>50,000.00</b>
	Cooling Capacity: 2.5 hp; 25,500 kJ/h				
	Power Input: 2,660 W				
	EER: 9.6 kJ/hW				
	Noise Level Indoor (Low): 52 dB A				
	Power Source: 230 V, 1Ø Phase - 60 Hz				
	Refrigerant: R32				

	<i>Unit Dimension (WxH xD): 660 x 428 x 800 mm</i>				
	<i>Warranty: Labor &amp; Parts - 1 Year; Compressor - 5 Years</i>				
<b>10</b>	<b>Aircon Split - type</b>	<b>pc</b>	<b>3</b>	<b>70,000.00</b>	<b>210,000.00</b>
	<i>nanoe-X technology-delete</i>				
	<i>HORSEPOWER: 2.5</i>				
	<i>power source: 230VAC, 60Hz</i>				
	<i>power input: 2300 watts</i>				
	<i>Mas Piping Length: 30 meters</i>				
	<i>Nanoe Technology (Nanoe-G and Nanoe X)</i>				
	<i>Premium Inverter</i>				
	<i>Shower Cooling Thru aerowings</i>				
	<i>I-auto X</i>				
	<i>R32 Eco-Refrigerant</i>				
	<i>Sleep Mode</i>				
	<i>Quiet Mode</i>				
	<i>Soft Dry Operation Mode</i>				
	<i>Personal Airflow Creation</i>				
	<i>Odor Removing</i>				
	<i>Removable Washing Panel</i>				
	<i>24-hour Dual On and Off Real Setting Timer</i>				
	<i>Self Diagnostic Function</i>				
	<i>Wireless LAN Remote Control for Internet Connection(Optional)</i>				
	<i>LCD Wireless Remote Control</i>				
	<i>Wired Remote Control</i>				
	<i>Random Auto Restart</i>				
	<i>Blue-Fin Condenser</i>				
	<i>Long Piping</i>				
	<i>Top Panel Maintenance Access</i>				
	<i>with free installation with FREE atleast 10- feet copper tube and insulated wire, polyethylene tape, drain hose</i>				
<b>11</b>	<b>Aircon Split Type (2 HP)</b>	<b>unit</b>	<b>1</b>	<b>50,000.00</b>	<b>50,000.00</b>
	<i>Capacity: 2.HP</i>				
	<i>Power Supply: 220,230,60,1 V, Hz, Ph</i>				
	<i>Cooling Capacity: 18,000 Btu/h</i>				
	<i>Cooling Input: 1552W</i>				
	<i>Cooling Current: 6.75A</i>				
	<i>EER: 12.24</i>				
	<i>Air Flow ( Hi/Mi/Lo): 848x796x626m3/h</i>				
	<i>Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)</i>				
	<i>Weight (Gross) 10.9kg</i>				
	<i>Refrigerant Type: R32</i>				
	<i>Compressor Type: Rotary</i>				
	<i>Weight (Gross): 31.7kg</i>				
	<i>Application Area: 23-33 sqm</i>				
	<i>One (1) year warranty on parts and service &amp; compressor</i>				
	<i>with free installation with FREE atleast 10- feet copper tube and insulated wire, polyethylene tape,</i>				

	drain hose				
12	<b>Aircon Split Type 2.5 HP Inverter , With Installation</b>	unit	1	58,000.00	58,000.00
	Capacity: 2.5HP				
	Power Supply: 220,230,60,1 V, Hz, Ph				
	Cooling Capacity: 24,000 Btu/h				
	Cooling Input: 2,000W				
	Cooling Current: 8.7A				
	EER: 12.7				
	Indoor Unit				
	Air Flow ( Hi/Mi/Lo): 1063x955x759 m3/h				
	Noise Level (Hi/Mi?Lo): 50/-/40 dB (A)				
	Unit Dimension ( W*D*H) : 1080x336x326mm (Indoor Unit)				
	Weight ( Net/Gross) 13.7/17.4 kg				
	Outdoor Unit				
	Refrigerant Type: R32/1120				
	Compressor Type: Rotary				
	Unit Dimension ( W*D*H) : 845x363x702mm ( outdoor unit)				
	Weight ( Net/Gross): 49.1/52.4kg				
	Application Area: 29-43sqm				
	One (1) year warranty on parts and service five (5) years on compressor provided that the unit is installed by accredited installation team				
13	<b>Aircon, Split Type, 1HP (Inverter)</b>	unit	2	44,000.00	88,000.00
	Features:				
	* High-density Dust Filter				
	* Smooth Frequency Control				
	* Gold Fin Protection				
	* Silver Ion Filter				
	* Sleep Mode				
	* Turbo Mode				
	* Louver Position Memory				
	* Fast Cooling				
	*with remote control				
	Specifications:				
	* 1.0HP Inverter				
	* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)				
	* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)				
	* 700 (290-990) Power Input (W)				
	* 4.32 CSPF				
	* R32 Refrigerant				
	* 39.5/34/32 dB (A) Sound Level (H/M/L)				
	1 year warranty				
	with free installation				
14	<b>Aircon, Window Type, 1.0HP (Inverter)</b>	unit	1	35,000.00	35,000.00
	1HP Inverter, 8-in-1 Filter, R410A				
	Energy Savings Feature:				
	24-hour Timer				
	Energy Saving Plug				

	<i>Econo and Sleep Mode</i>				
	<i>EER Rating: 11.6 (10.8 - 10.7)</i>				
	<i>Sleek, Modern Aesthetic</i>				
	<i>Remote Control</i>				
	<i>2 x AAA Batteries</i>				
	<i>With Free Installation</i>				
	<i>220V, 1 PHASE</i>				
	<i>1 year warranty</i>				
<b>15</b>	<b>Bread Toaster, 4 slots</b>	<b>unit</b>	<b>1</b>	<b>3,200.00</b>	<b>3,200.00</b>
	<i>4-slice Stainless Steel Toaster</i>				
	<i>Stainless Steel Body•Variable</i>				
	<i>Toast Control•Defrost &amp; Reheat Functions</i>				
	<i>Slide-out Crumb Tray</i>				
<b>16</b>	<b>Conference Microphone, Gooseneck</b>	<b>unit</b>	<b>2</b>	<b>5,000.00</b>	<b>10,000.00</b>
	▣ <i>Acoustic Principle: Condenser Polar</i>				
	▣ <i>Pattern: Cardioid</i>				
	▣ <i>Frequency Response: 50-16000Hz</i>				
	▣ <i>Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)</i>				
	▣ <i>Signal to Noise Ratio: 80dB</i>				
	▣ <i>Output connector: XLR Connector</i>				
	▣ <i>Power requirement: 48V Phantom Power</i>				
	▣ <i>Built-in LED indicator shows Talk/Mute</i>				
	▣ <i>Foam windscreen included</i>				
<b>17</b>	<b>copier machine</b>	<b>unit</b>	<b>1</b>	<b>78,000.00</b>	<b>78,000.00</b>
	<i>Paper Size: A4. Short, Long; Make : photocopy</i>				
	<i>Staus : Used Copier Machine</i>				
	<i>Color : Color MachinePrint Speed : 35ppm</i>				
	<i>Scanning Resolution : 600*600dpi</i>				
	<i>Zoom Range : 25-400%</i>				
	<i>First Copy Time : 3.6 seconds or less</i>				
	<i>Warm-up Time : 30 seconds or less</i>				
	<i>Scan Resolution: 300dpi, ADF</i>				
	<i>Capacity: 50 sheets and up</i>				
	<i>Function Type: Print, Copy, Scan &amp; Fax</i>				
	<i>Features: Built in ADF, 40 ppm, duplex print scan</i>				
	<i>Copy Fax, Direct USB scan/Print</i>				
	<i>Tray Capacity: 250# sheets</i>				
	<i>Type: Mono-Multi-Functional</i>				
	<i>Connectivity Type: Air Print, USB, wifi</i>				
<b>18</b>	<b>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</b>	<b>unit</b>	<b>1</b>	<b>150,000.00</b>	<b>150,000.00</b>
	<i>Max printing size: 25*30cm</i>				
	<i>Max printing thickness: 3cm</i>				
	<i>Max printing speed: 2cm - 5cm/s</i>				
	<i>Resolution: 300dpi</i>				
	<i>Printing method: Thermal printing</i>				
	<i>Voltage: AC110-240V 50/60Hz</i>				
	<i>Power: 150W</i>				
	<i>Computer system requirement: Windows</i>				
	<i>Software requirement: Most of softwares, Coreldraw,</i>				

	<i>photoshop, adobe illustrator, office word</i>				
	<i>Temperature requirement: 5°C to 40°C</i>				
	<i>Printer weight: 23kg</i>				
	<i>Printer size: 60cm*50cm*30cm</i>				
	<i>Warranty: 1year excluded printing head unless quality problem</i>				
<b>19</b>	<b>Digital Color Multifunction (3in1) Copy, Print &amp; Scan Photocopier Machine</b>	<b>unit</b>	<b>1</b>	<b>200,000.00</b>	<b>200,000.00</b>
	Digital Color Multifunction (3in1) Copy, Print & Scan Photocopier Machine				
	Print/Copy Speed: Color/Mono Speed: 25 ppm				
	Print resolution: 1200 x 2400 dpi				
	Memory Capacity: 4GB				
	Storage Device Capacity: 128GB				
	Colour Capability: Full Color				
	Magnificationzoom: 25 to 400% (Reduce/Enlarger)				
	Original Size: Maximum of 297 x 432 mm (A3, 11x17") For both Sheet and Book				
	Paper Size: Letter, A4, Legal, Long, Max.: A3, 11x17" Min.:A5 [Postcard (100x148mm)				
	Paper Weight: 60 to 256 gsm				
	Paper Tray: Tray 1: 500 sheets Tray 2: 500 sheets & Bypass Tray: 100 sheets				
	Duplex: Automatic Document Feeder, automatic Back to Back Electronic Sorting				
	Interface: Standard ethernet 1000BASE-T/100BASE-TX/10BASE-T, USB2.0, Network Ready				
	Inclusion: Pre-installed CMYK Toner Initial (10,000 copies)				
	Metal Pedestal Drawer w/ Wheels				
	Power cords, CD's Installer & User Manual				
	Manufacturer Certificate				
	USB Port Cable				
	Free Delivery & Installation Onsite				
	Warranty: 1 Year Parts Warranty				
	Lifetime Free Service with Regular Monthly				
	Preventive Maintenance Check-up Onsite				
<b>20</b>	<b>Digital Duplicator Machine, Copy printer, 300x600 DPI printing</b>	<b>set</b>	<b>1</b>	<b>150,000.00</b>	<b>150,000.00</b>
	Master Making/Printing Methods: High-speed digital master-making/Fully automatic printing				
	Scanning: 600 dpi × 600 dpi				
	Printing: 300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi				
	Maximum Scanning Area: 297 mm × 432 mm				
	Print Paper Weight: 46 gsm to 157 gsm				
	Print Paper Size: 100 mm × 148 mm to 310 mm × 432 mm				
	Maximum Printing Area: 210 mm × 357 mm				
	Paper Feed Tray Stacking Capacity: 1000 sheets*2, stacking height of 110 mm or lower				
	Paper Receiving Tray Stacking Capacity: 1000				

	sheets*2, stacking height of 110 mm or lower				
	Print Speed: 5 levels: 60, 80, 100, 120 and 130 ppm				
	Functions: Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto*3, Speed, Density, Print Position, Program A/B, Job Separation*3, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System				
	Ink Supply: Full automatic (1000 ml/cartridge)				
<b>21</b>	<b>Electric fan</b>	<b>unit</b>	<b>3</b>	<b>2,500.00</b>	<b>7,500.00</b>
	■Stand fan 16" metal blade				
	■Adjustable height				
	■three speed controller				
<b>22</b>	<b>Electric Floor Polisher, Vaccum Cleaner and Lawn Mower, Sound System</b>	<b>lot</b>	<b>1</b>	<b>86,000.00</b>	<b>86,000.00</b>
	Item Specification				
	1.Wet and Dry Vacuum Cleaner				
	Item Specification				
	Super Suction Power				
	Wet and Dry Vacuuming				
	Blower Function				
	Accessory Storage				
	Energy Efficient				
	SKU: 110361712_PH-7448394060				
	Vacuum Cleaner Features: Bagged, Blower, Wheels				
	Model: WD 3				
	Warranty Type:Local Supplier Warranty				
	Warranty Period:1 Year				
	Actual suction power* (Air watts) 200				
	Energy use (W) 1000				
	Container capacity (l) 17				
	Container material Stainless steel				
	Power cable (m) 4				
	Standard accessory ID (mm) 35				
	Supply voltage (V/Hz) 220 - 240 / 50 - 60				
	Weight without accessories (kg) 5,8				
	Weight incl. packaging (kg) 8,2				
	Dimensions (L x W x H) (mm) 388 x 340 x 525				
	1xSuction hose, 2 m, 35 mm; 2x Suction tubes, 0.5 m, 35 mm; 1x Wet and dry floor nozzle, Clips; 1x Cartridge filter, Standard; 1x Crevice nozzle; 1x Paper filter bag				
	3. Electric Floor Polisher				
	Item Specification:				
	>Speed Switch-Speed Selection low (175 RPM) and High (320 RPM)				
	>Handle Tube-All Chrome 1-1/2 inch				
	>Power Cord- 50ft. UL Listed 14/3 STW-A. Comes with cord strain relief				
	>Transport Wheels- 5 inch non-marking self				



	lubricated wheels				
	>All Metal Housing-provides long lasting durability				
	4. Sound System				
	Item Specification				
	The Behringer Europort PPA500BT-delete				
	Specs				
	Type:Portable PA System				
	Speaker Drivers:1 x 8" woofer, 1.35" compression driver				
	Number of Mixer Channels:6				
	Number of Mic Preamps:2				
	EQ:Treble, Bass, 5-band Graphic				
	Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in)				
	Outputs:2 x 1/4" (speaker out)				
	USB:1 x Type A (ULM wireless ready)				
	Bluetooth:Yes				
	Total Power:500W				
	Frequency Response:50Hz-22kHz				
	Microphone:1 x Behringer XM1800S				
	Power Source:Standard IEC AC cable				
	Height:25.9"				
	Width:13.9"				
	Depth:34.8"				
	Weight:44.7 lbs.				
<b>23</b>	<b>Exhaust Fan</b>	<b>unit</b>	<b>1</b>	<b>2,000.00</b>	<b>2,000.00</b>
	☐Exhause Fan 12 inch				
	☐power input: 50w				
	☐12 inch plastic blade				
	☐wall-mounted				
	☐reversible motor for desired air flow (Exhaust/Blower)				
	☐with pull cord switch				
	☐detachable plastic panel & front grill				
	☐metal shutters				
	☐Air volume: 28.47/ 19.10 CMM				
	☐Unit dimension: 39cm x 17cmx39cm				
	☐Mounting Dimension: 35cm x 35cm				
<b>24</b>	<b>Floor Aircon</b>	<b>pcs</b>	<b>8</b>	<b>151,000.00</b>	<b>1,208,000.00</b>
	6HP, 5TR, DC INVERTER, R32 REFRIGERANT, ENERGY SAVING, SIDE AIR INTAKE, DIGITAL LED DISPLAL, AUTO LOUVER, SELFDIAGNOSIS AND WITH REMOTE HOLDER, EER RATING: 11.3 KJ/H with Installation				
<b>25</b>	<b>Floor Mounted Inverter Airconditioner, 3TR</b>	<b>unit</b>	<b>3</b>	<b>136,000.00</b>	<b>408,000.00</b>
	R410A Refrigerant				
	Sleep Mode				
	Self diagnosis				
	Auto-swing				
	Lock function				
	Technical Specifications				

	Cooling Capacity (Min-Max): 37,000 (9,970-37,300) Btu/h; 39,035 kJ/h				
	Power Supply: 230/60/1 V/Hz/Ph				
	Rated Power (Min-Max): 3,600 (850-4,350) W				
	Rated Current (Min-Max): 16.0 (3.61-19.1) A				
	EER: 10.3 Btu/hW; 10.8 kJ/hW				
	CSPF: 4.2				
	Refrigerant: R410A				
	Operation Temperature (Min-Max): 17-30°C				
	Airflow Volume (Hi/Med/Low): 1,850 CMH				
	Noise Level (Low): 52.0 dB(A)				
	with installation				
<b>26</b>	<b>Heavy Duty Combo Binding Machine</b>	<b>unit</b>	<b>1</b>	<b>18,000.00</b>	<b>18,000.00</b>
	☐Maximum Punching Sheets: 25				
	☐Max Size: LS, F4, A4, Extra Long				
	☐Selectable Punching Pins: 24 slots				
	☐Net Weight: 12.5kgs				
<b>27</b>	<b>Hot &amp; Cold water dispenser</b>	<b>unit</b>	<b>1</b>	<b>14,500.00</b>	<b>14,500.00</b>
	☐Bottom load water dispenser				
	☐3 Faucets: Hot, Cold and Normal water function				
	☐3-Push Button dispensing control				
	☐Anti-scald safety lock switch				
	☐Child Lock Safety feature on Hot Water Faucet				
	☐Floater indicator to avoid water overflow				
	☐Capacity: Hot - 1.2 Liters, Cold - 3.5 liters, Power Rating: Hot - 420 watts, Cold - 100 watts, R134a				
<b>28</b>	<b>Laminator Machine, A3</b>	<b>unit</b>	<b>4</b>	<b>5,000.00</b>	<b>20,000.00</b>
	☐Heavy Duty, for A3 & A4 size, infrared heating system and adjustable temperature control with overheating protection				
<b>29</b>	<b>Megaphone</b>	<b>unit</b>	<b>1</b>	<b>3,000.00</b>	<b>3,000.00</b>
	☐Bullhorn				
	☐1000 yard range				
	☐For indoor and outdoor use				
	☐Built-in siren				
	☐40 W amplifier				
	☐Built-in mic				
	☐10 seconds recording function				
<b>30</b>	<b>Paper shredder machine, heavy duty</b>	<b>unit</b>	<b>3</b>	<b>12,000.00</b>	<b>36,000.00</b>
	☐Shred Type: Cross Cut				
	☐Maximum Sheet capacity(70gsm) : 10 Sheets				
	☐Waste Container capacity: 21 Liters				
	☐Power Source: 220 - 240 VAC				
<b>31</b>	<b>Portable Trolley 15" Speaker with wireless microphone</b>	<b>unit</b>	<b>4</b>	<b>10,000.00</b>	<b>40,000.00</b>
	☐15" 2 Way 480 Watts Powered Portable Sound System				
	☐Plastic Cabinet				
	☐AC220V or DC12V (With built-in Rechargeable Batteries)				
	☐With 2 Wireless Microphone				

	☑With 2 Mic Input (1 XLR, 1 PL55)				
	☑With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port				
	☑With 5 Band Equalizer and LCD Display				
	☑With Aux / Line In and Line Out				
	☑With Remote Control, Handle and Wheel				
<b>32</b>	<b>Sliding Paper Cutter</b>	<b>unit</b>	<b>4</b>	<b>2,550.00</b>	<b>10,200.00</b>
	Working Area: A3 and A4				
	Cutting Capacity: 16 sheets				
	Packing Weight: 5 kg				
	Material: Metal				
	Available Size: A3 and A4				
	Packing Measurement: 56x34x11 cm				
	Other Specifications: Heavy duty for Vinyl, Cardboard Paper				
<b>33</b>	<b>Smart TV 75 inches</b>	<b>piece</b>	<b>2</b>	<b>70,000.00</b>	<b>140,000.00</b>
	with wall bracket;				
	Resolution: 4K Ultra HD				
	Screen Size: 75"				
	Connectivity: 3x HDMI 2.1				
	2X USB				
	WIFI				
	BLUETOOTH				
	HDMI Ports: 3x HDMI 2.1				
	Voltage: AC100-240V - 59/69Hz				
<b>34</b>	<b>Sound System, Speaker</b>	<b>unit</b>	<b>3</b>	<b>50,000.00</b>	<b>150,000.00</b>
	All-in-one PA system with 10-channel powered mixer and full-range speakers				
	Bluetooth audio streaming				
	Sub output with automatic high-pass filter for powered subwoofer use				
	with 2 microphone				
<b>35</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>	<b>pc</b>	<b>1</b>	<b>1,500.00</b>	<b>1,500.00</b>
	☑Power Output : rms 4.5w×2 sw: 12w				
	☑Signal to noise ratio : 80dba				
	☑Frequency Response : 80hz~20khz (±6db)				
	☑R/I: 300±50mv sw: 100 ± 20mv				
	☑Aux/USB/SD card				
	☑Bass driver :4 inch				
	☑Treble driver :2 3/4 inch				
<b>36</b>	<b>Surge suppressor 6 outlets</b>	<b>unit</b>	<b>2</b>	<b>600.00</b>	<b>1,200.00</b>
	☑Maximum capacity: 2500W				
	☑Voltage Surge Protector (protects appliances from voltage spikes)				
	☑6 Neon Switch				
	☑1 Circuit Breaker (protects appliance from overload or short circuit)				
	☑3 Two-Prong Outlets				
	☑3 Three-Prong Outlets w/ Grounding				
	☑90 degree outlet orientation				
	☑With line/noise filter				

	■Royal Cord #16/3 (5.00 meters)				
	■Metal casing				
<b>37</b>	<b>Television, UHD, Smart TV</b>	<b>unit</b>	<b>1</b>	<b>25,000.00</b>	<b>25,000.00</b>
	Display Size: 50"				
	Ports Input: OTHERS, HDMI, USB, Component in (Y/PB/Pr), RF in (Terrestrial/Cable Input), Digital Audio Out (Optical), Audio Out (Mini Jack), Ethernet (LAN), Composite in (AV)				
	TV Features: Netflix, HDR, Cinema 3D ,Wireless Connectivity, Web Browser, Mobile Screen Mirroring, Youtube, DTS Audio, Bluetooth Connectivity				
	TV Resolution: 4K UHD				
	Smart TV OS: Android OS				
<b>38</b>	<b>Water Dispenser (top loading), with fridge</b>	<b>unit</b>	<b>1</b>	<b>15,000.00</b>	<b>15,000.00</b>
	Fridge cabinet to cool additional drinks.				
	Three water spouts: hot, room temperature, cold.				
	LED indicators add to ease of use.				
	Durable/ good quality				
	Size & Capacity				
	Gross weight (Kg): 17				
	Net weight (Kg): 15.46				
	Fridge cabinet capacity (L):19				
	Type & Setup				
	Type: Top load water dispensers				
	Control type: Manual				
	Product installation: Freestanding				
	Product dimensions				
	Depth: 372 mm				
	Height: 1003 mm				
	Width: 318 mm				
	Depth packed: 386 mm				
	Height packed: 1050 mm				
	Width packed: 358 mm				
	Power Supply				
	Voltage (V): 220-240				
	Total wattage (W): 520				
<b>39</b>	<b>Wireless Dual Handheld Microphone</b>	<b>set</b>	<b>1</b>	<b>20,000.00</b>	<b>20,000.00</b>
	Receiver				
	Power Consumption: 12w (Max)				
	Receiver Sensitivity: -95dbm				
	Mixing Output Socket: ø6.3mm Socket				
	Balanced Output Socket: XLR Socket				
	Transmitter				
	Carrier Frequency: Depends on regional frequency band				
	Transmit Power: 10dBm (±2dBm)				
	Microphone Capsule: Dynamic				
	Polar Pattern: Super Cardioid				
	Impedance: 600				
	Frequency Response: 80~12000Hz				
	Current Consumption: 120mA				

	Battery: Size AA x 2pcs				
	Operation Range: 90 meters (in open area)				
	Battery Life: Approximately 12 hours (uses alkaline batteries)				
	Each microphone has 100 selectable channels and independent volume controls.				
	This UHF system features 6-axis gyroscope to automatically enter mute mode when idling for 5~10 seconds.				
<b>40</b>	<b>Water Dispenser, Cabinet type</b>	<b>units</b>	<b>2</b>	<b>10,000.00</b>	<b>20,000.00</b>
	☑Floor standing				
	☑Hot and cold function				
	☑plastic body,high efficiency compressor				
	☑thermally protected				
<b>41</b>	<b>Floor Standing Mounted Airconditioner</b>	<b>unit</b>	<b>1</b>	<b>80,000.00</b>	<b>80,000.00</b>
	☑At least 4.0HP				
	☑Energy Saving Compressor, 3D Air Delivery System				
	☑with Sleep Mode				
	☑with Auto On / Off Timer				
	☑with High Efficiency Air Filter				
	☑with Remote Control				
	☑Air Conditioner Rated Capacity (BTUs) at least 2.5				
<b>42</b>	<b>Inverter Digital Wall Mounted Split Type Air Condition</b>	<b>unit</b>	<b>2</b>	<b>50,000.00</b>	<b>100,000.00</b>
	Capacity (Cooling, kJ/h) - 23400 kJ/hW				
	Capacity (Cooling, Min - Max, kJ/h) - 5,000 ~ 27,000 kJ/hW				
	Noise Level (Indoor, High/Low, dBA) - 45 / 30 dBA				
	Noise Level (Outdoor, High/Low, dBA) - 52 dBA				
	Power Source(Φ/V/Hz) - 1 / 220~240 / 60				
	Power Consumption(Cooling, W) - 2000 W				
	Operating Current(Cooling, A) - 8.8 A				
	Net Dimension (Indoor, WxHxD, mm) - 1055x299x215 mm				
	Net Dimension (Outdoor, WxHxD, mm) - 880x638x310 mm				
	Net Weight (Indoor, kg) - 11.5 kg				
	Net Weight (Outdoor, kg) - 35.3 kg				
	Piping Length (Max, m) - 30 m				
	Piping Height (Max, m) - 15 m				
	SVC Valve (Liquid (ODxL)) - 6.35				
	SVC Valve (Gas (ODxL)) - 15.88				
	Moisture Removal (l/hr) - 2.5 l/hr				
	Air Circulation (Cooling, m <sup>3</sup> /min) - 18.6 m <sup>3</sup> /min				
	Refrigerant (Type) - R32				
	Low Ambient (Cooling, °C) - 16~46 °C				
	Outdoor Unit (Compressor Type) - BLDC				
	Outdoor Unit (Anti-Corrosion Fin) - Yes				
	Air Direction Control (Up/Down) - Auto				
	Air Direction Control (Left/Right) - Auto				
	Air Flow Control Step (Cool/Fan) - 5/4				

	Easy Filter Plus (Anti-Bacteria) - Yes				
	Auto Clean (Self Cleaning) - Yes				
	Beep On/Off - Yes				
	24-Hour Timer - Yes				
	Auto Restart - Yes				
	Auto Mode - Yes				
	Fast Cool - Yes				
	Good Sleep - Yes				
	Eco Mode - Yes				
	Dehumidification - Yes				
	Fan Mode - Yes				
	Quiet - Yes				
	Free Installation				
<b>43</b>	<b>Aircon, Split Type, 1.5HP (Inverter)</b>	<b>unit</b>	<b>2</b>	<b>49,000.00</b>	<b>98,000.00</b>
	Features				
	* High-density Dust Filter				
	* Smooth Frequency Control				
	* Gold Fin Protection				
	* Silver Ion Filter				
	* Sleep Mode				
	* Turbo Mode				
	* Louver Position Memory				
	* Fast Cooling				
	*with remote control				
	Specifications:				
	* 1.5HP Inverter				
	* 12,700 (3,100-13,200) Cooling Capacity (kJ/hr)				
	* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)				
	* 1,030 (290-1,210) Power Input (W)				
	* 4.5 CSPF				
	* R32 Refrigerant				
	* 37/34.5/32.5 dB (A) Sound Level (H/M/L)				
	* L 21 x W 72.6 x H 29.1 (cm) Dimension				
	1 year warranty				
	with free installation				
<b>44</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>	<b>pc</b>	<b>1</b>	<b>4,000.00</b>	<b>4,000.00</b>
	☐Power Output : rms 4.5w×2 sw: 12w				
	☐Signal to noise ratio : 80dba				
	☐Frequency Response : 80hz~20khz (±6db)				
	☐R/I: 300±50mv sw: 100 ± 20mv				
	☐Aux/USB/SD card				
	☐Bass driver :4 inch				
	☐Treble driver :2 3/4 inch				
<b>45</b>	<b>Stand Fan, banana type 18" banana blade</b>	<b>unit</b>	<b>2</b>	<b>2,500.00</b>	<b>5,000.00</b>
				<b>TOTAL:</b>	<b>4,724,100.00</b>

Bids received in excess of the ABC for each item shall be automatically rejected at bid opening.

- The *Visayas State University* now invites bids for the above Procurement Project. Delivery of the Goods is required by *Forty-Five (45) calendar days upon receipt of*

*Notice to Proceed (NTP)*. Bidders should have completed, within *two (2) years* from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).

3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary “*pass/fail*” criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.

Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.

4. Prospective Bidders may obtain further information from *Visayas State University* and inspect the Bidding Documents at the address given below during *Mondays - Fridays (8:00 AM-5:00 PM)*.
5. A complete set of Bidding Documents may be acquired by interested Bidders on *03 October – 24 October 2023 until 8:30 AM* from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Five Thousand Pesos (PhP 5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person, by facsimile, or through electronic means.
6. The *Visayas State University* will hold a Pre-Bid Conference on **October 25, 2023; 9:00 AM** at the *BAC Conference Room, VSU Market, Visca, Baybay City, Leyte* and through video conferencing *via Zoom*, which shall be open to prospective bidders.

Bidders are advised to contact the BAC Secretariat before the scheduled Pre-Bid Conference for the Zoom meeting details.

7. Bids must be duly received by the BAC Secretariat through (i) manual submission at the office address indicated below, (ii) online or electronic submission as indicated below, or (iii) both on or before **08 November 2023 until 8:30 AM**. Late bids shall not be accepted.
8. For bidders who opt to submit their bids electronically, a hardcopy (original) of the bid must be sent to the BAC through preferred couriers. A proof (e.g. courier receipt/waybill, etc.) that a hardcopy of the bid is on transit must be presented upon submission of the electronic bid.
9. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in **ITB** Clause 14.
10. Bid opening shall be on **08 November 2023 until 9:00 AM** at the *BAC Conference Room, VSU Market, Visca, Baybay City, Leyte* and through video conferencing *via Zoom*. Bids will be opened in the presence of the bidders’ representatives who choose to attend the activity.

Bidders are advised to contact the BAC Secretariat before the scheduled Bid Opening for the Zoom meeting details.

11. This procurement project is part of the early procurement activities (EPA) of VSU for 20243 projects. Procurement activities from advertisement until recommendation of award to the HoPE shall be conducted in 2023 but issuance of award to the winning bidders shall be done in 2024 upon the release of 2024 VSU General Appropriations Act from DBM.
12. The *Visayas State University* reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
13. For further information, please refer to:

**Mr. Leopoldo S. Escala Jr. (BAC Secretariat)**  
*Office of the Head for Procurement,*  
*VSU-Main, Visca, Baybay City, Leyte*  
*Mobile: 053 565 0600 local 1093 or 09639629709*  
*Email: [leopoldo.escala@vsu.edu.ph](mailto:leopoldo.escala@vsu.edu.ph)*

**or**

**Mr. Toni Marc L. Dargantes (BAC Secretariat)**  
*Office of the VP for Planning, Resource Generation & Auxiliary Services*  
*VSU-Main, Visca, Baybay City, Leyte*  
*Mobile: 0977 7186594*  
*Email: [tmdargantes@vsu.edu.ph](mailto:tmdargantes@vsu.edu.ph)*

14. You may visit the following websites:

For downloading of Bidding Documents: <https://www.vsu.edu.ph/philgeps-opportunities>

October 16, 2023



**DILBERTO O. FERRAREN**  
*Chairperson, VSU BAC*



## ***Section II. Instructions to Bidders***

## **1. Scope of Bid**

The Procuring Entity, *Visayas State University*, wishes to receive Bids for the *Supply and Delivery of Office Equipment*, with identification number *VSU-GOODS-24-03*.

The Procurement Project (referred to herein as “Project”) is composed of *52 items*, the details of which are described in Section VII (Technical Specifications).

## **2. Funding Information**

2.1. The GOP through the source of funding as indicated below for 2024 in the amount of *Four Million Seven Hundred Twenty Four Thousand One Hundred Pesos (PhP 4,724,100.00.00)*.

2.2. The source of funding is: NGA, the General Appropriations Act 2024.

## **3. Bidding Requirements**

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

## **4. Corrupt, Fraudulent, Collusive, and Coercive Practices**

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex “I” of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

## **5. Eligible Bidders**

5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.

5.2. Foreign ownership limited to those allowed under the rules may participate in this Project.

- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:

Bidder should comply with the following requirements:

- i. Completed at least two (2) similar contracts, the aggregate amount of which should be equivalent to at least *fifty percent (50%)* of the ABC for this Project; and
- ii. The largest of these similar contracts must be equivalent to at least half of the percentage of the ABC as required above.

- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

## **6. Origin of Goods**

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

## **7. Subcontracts**

- 7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that: **Subcontracting is not allowed.**

## **8. Pre-Bid Conference**

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address and/or through videoconferencing/webcasting as indicated in paragraph 6 of the **IB**.

## **9. Clarification and Amendment of Bidding Documents**

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

## **10. Documents comprising the Bid: Eligibility and Technical Components**

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII (Checklist of Technical and Financial Documents)**.

- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within **two (2 years)** prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

## **11. Documents comprising the Bid: Financial Component**

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in **Section VIII (Checklist of Technical and Financial Documents)**.
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

## **12. Bid Prices**

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
  - a. For Goods offered from within the Procuring Entity's country:
    - i. The price of the Goods quoted EXW (ex-works, ex-factory, ex-warehouse, ex-showroom, or off-the-shelf, as applicable);
    - ii. The cost of all customs duties and sales and other taxes already paid or payable;
    - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
    - iv. The price of other (incidental) services, if any, listed in e.
  - b. For Goods offered from abroad:

- i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
- ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications)**.

### **13. Bid and Payment Currencies**

13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.

13.2. Payment of the contract price shall be made in: Philippine Pesos.

### **14. Bid Security**

14.1. The Bidder shall submit a Bid Securing Declaration or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.

14.2. The Bid and bid security shall be valid until *March 08, 2024*. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

### **15. Sealing and Marking of Bids**

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

### **16. Deadline for Submission of Bids**

16.1. The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the **IB**.

## 17. Opening and Preliminary Examination of Bids

- 17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

- 17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

## 18. Domestic Preference

- 18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

## 19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "*passed*," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII (Technical Specifications)**, although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows: One Project having several items, which shall be awarded as separate contracts per item.
- 19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

## **20. Post-Qualification**

- 20.1. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**.

## **21. Signing of the Contract**

- 21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

## ***Section III. Bid Data Sheet***



# Bid Data Sheet

ITB Clause	
5.3	For this purpose, contracts similar to the Project shall be: <ul style="list-style-type: none"> <li>a. <i>Office Equipment</i></li> <li>b. completed within two (2) years prior to the deadline for the submission and receipt of bids.</li> </ul>
7.1	Subcontracting is not allowed.
12	The price of the Goods shall be quoted DDP <i>VSU Main, Visca, Baybay City, Leyte</i> or the applicable International Commercial Terms (INCOTERMS) for this Project.
14.1	The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: <ul style="list-style-type: none"> <li>a. The amount of not less than <i>Ninety Four Thousand Four hundred Eighty Two Pesos (PhP 94,482.00)</i> or two percent (2%) of ABC, if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or</li> <li>b. The amount of not less than <i>Two Hundred Thirty Six Thousand Two Hundred Five Pesos (PhP 236,205.00)</i> or five percent (5%) of ABC if bid security is in Surety Bond.</li> </ul>
15	Bidders are requested to submit two (2) more copies of its bid (Copy 1 and Copy 2) in addition to the required original hardcopy.  For filing purposes, the bidders are urged to use <b>Orange</b> envelopes for its Technical and Financial Component envelopes, including the Mother (outer) Envelope.
19.3	<i>See Section I. Invitation to Bid (Item 1) for the list of items and their corresponding total Approved Budget for the Contract (ABC) per item.</i>
20.2	Bidders are required to submit its updated Mayor's/Business Permit during post-qualification.
21.2	<i>Not Applicable.</i>

## ***Section IV. General Conditions of Contract***

## 1. **Scope of Contract**

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC)**.

## 2. **Advance Payment and Terms of Payment**

2.1. Advance payment of the contract amount is provided under Annex “D” of the revised 2016 IRR of RA No. 9184.

2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

## 3. **Performance Security**

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

## 4. **Inspection and Tests**

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the **SCC, Section IV (Technical Specifications)** shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

## **5. Warranty**

- 6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

## **6. Liability of the Supplier**

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

## *Section V. Special Conditions of Contract*

## Special Conditions of Contract

GCC Clause	
1	<p><b>Delivery and Documents –</b></p> <p>For purposes of the Contract, “EXW,” “FOB,” “FCA,” “CIF,” “CIP,” “DDP” and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:</p> <p>The delivery term applicable to this Contract is delivered <i>VSU Main Campus, Visca, Baybay City, Leyte</i>. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination.</p> <p>Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).</p> <p>For purposes of this Clause the Procuring Entity’s Representative at the Project Site is:</p> <p style="padding-left: 40px;"><b><u>Vivian V. Balbarino</u></b>  <i>Head, Supply and Property Management Office</i>  <i>VSU-Main, Visca, Baybay City, Leyte</i>  <i>Contact #: 053 565 0600 local 1082/ 09175518871</i>  <a href="mailto:sppmo@vsu.edu.ph">sppmo@vsu.edu.ph</a></p> <ul style="list-style-type: none"> <li>• <b>Additional Instruction: The Supplier should notify the Head of Supply and Property Management Office atleast 1 week before the scheduled delivery.</b></li> </ul> <p><b>Incidental Services –</b></p> <p>The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements:</p> <ol style="list-style-type: none"> <li>a. performance r supervision of on-site assembly and/or start-up of the supplied Goods;</li> <li>b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;</li> <li>c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;</li> <li>d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and</li> <li>e. training of the Procuring Entity’s personnel, at the Supplier’s plant</li> </ol>

	<p>and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.</p>
	<p>The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.</p> <p><b>Spare Parts –</b></p> <p>The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:</p> <ul style="list-style-type: none"> <li>a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and</li> <li>b. in the event of termination of production of the spare parts: <ul style="list-style-type: none"> <li>i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and</li> <li>ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.</li> </ul> </li> </ul> <p>The spare parts and other components required are listed in <b>Section VI (Schedule of Requirements)</b> and the cost thereof are included in the contract price.</p> <p>The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of 3 years.</p> <p>Spare parts or components shall be supplied as promptly as possible, but in any case, within 1 month of placing the order.</p>
	<p><b>Packaging –</b></p> <p>The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods’ final destination and the absence of heavy handling facilities at all points in transit.</p>

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

- Name of the Procuring Entity
- Name of the Supplier
- Contract Description
- Final Destination
- Gross weight
- Any special lifting instructions
- Any special handling instructions
- Any relevant HAZCHEM classifications

A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging.

**Transportation –**

Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.

Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.

Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure.

The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until



	<p>their receipt and final acceptance at the final destination.</p> <p><b>Intellectual Property Rights –</b></p> <p>The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof.</p>
2.2	<p>Payment of staggered deliveries shall be allowed. Payment shall be on “as per cost of the items delivered” subject to inspection and acceptance.</p>
4	<p>The inspections and tests that will be conducted will be specified by the appropriate technical team of VSU to confirm conformity to the contract specifications at no extra cost to VSU.</p>

## *Section VI. Schedule of Requirements*

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item #	Qty	Unit	Description	Delivered, Weeks/Months
1	2	unit	<b>1.5 hp Inverter Window-Type Air Conditioner</b>	All Items Should Be Delivered to VSU Main Campus, Visca, Baybay City, Leyte within <b>45 calendar days</b> from receipt of Notice To Proceed (NTP), Purchase Order
			Capacity : Capacity (Cooling, W)3380 W, Capacity (Cooling, kJ/h)12160 kJ/hW	
			Power Input (Nominal): Cooling1095 W	
			Current Input (Nominal): Cooling4.8 W	
			Power Input (Rated): Cooling1390 W	
			Current Input (Rated): Cooling7.5 W	
			Energy Efficiency:	
			EER (Cooling, W/W): 3.08 W/W	
			Permissible Excessive Operating Pressure for the Discharge Side: 4.3 Mpa	
			Maximum Allowable Pressure: 4.7 Mpa	
			Isolation: I	
			EER (Cooling, Btu/hW): 10.51 Btu/hW	
			Permissible Excessive Operating Pressure for the Suction Side: 2.5 Mpa	
			Climate Type: T1	
			Moisture Protection: IPX4	
			Noise Level	
			Sound Pressure Level (H/M/L, dBA): 54/51/50 dBA	
			Electrical Data	
			Power Source(Φ/V/Hz): 1 / 230 / 60	
			Physical specification	
			Package Dimension (WxHxD, mm*mm*mm): 623×425×806 mm	
			Gross Weight (kg): 48 kg	
			Loading Quantity (20' Container): 125	
			Loading Quantity (40' High Cube Container): 312	
			Net Dimension (WxHxD, mm*mm*mm): 560×375×708 mm	
			Net Weight(kg): 45 kg	
			Loading Quantity (40' Container): 260	
			Technical Information	
			Refrigerant (Type): R32	
			Low Ambient (Cooling, °C): 18~43 °C	
			Refrigerant (Charging, kg): 0.53 kg	
			Compressor Type: Rotary	
			Convenience: 24-Hour Timer (Yes)	
			Operating Mode: Auto Mode (Yes), Dehumidification (Yes), Good Sleep (Yes)	
2	2	pc	<b>2 BURNER GAS STOVE</b>	
			■Heavy duty gas stove	
			■High quality fuel-efficient burner	
			■Durable metal gas ignition controls	

			<ul style="list-style-type: none"> <li>☑Stainless metal gasket and body</li> </ul>
			<ul style="list-style-type: none"> <li>☑Auto-ignition burner</li> </ul>
			<ul style="list-style-type: none"> <li>☑# of burners: 2</li> </ul>
			<ul style="list-style-type: none"> <li>☑Dimensions: (W x L X D ) 71 x 35.5 x 8.5cm   28 x 14 x 3.3 inches</li> </ul>
			<ul style="list-style-type: none"> <li>☑Burner diameter: 9cm   3.5 inches   Outer ring diameter: 22.5cm   8.9 inches</li> </ul>
			<ul style="list-style-type: none"> <li>☑Space in between outer rings: 20cm   7.9 inches</li> </ul>
			<ul style="list-style-type: none"> <li>☑Color: silver</li> </ul>
			<ul style="list-style-type: none"> <li>☑Warranty: 1 year</li> </ul>
<b>3</b>	<b>1</b>	<b>unit</b>	<ul style="list-style-type: none"> <li>☑<b>75 inch interactive display touchscreen Smart TV</b></li> </ul>
			Specifications:
			Picture Engine: Crystal Processor 4K
			<ul style="list-style-type: none"> <li>• Color: Dynamic Crystal Color</li> </ul>
			<ul style="list-style-type: none"> <li>• Contrast: Mega Contrast</li> </ul>
			<ul style="list-style-type: none"> <li>• Sound: Q-Symphony</li> </ul>
			<ul style="list-style-type: none"> <li>• Smart: Tap-View</li> </ul>
			<ul style="list-style-type: none"> <li>• Design: AirSlim</li> </ul>
			Specifications Detail
			Product Type: LED
			Series: 8
			Display
			<ul style="list-style-type: none"> <li>• Screen Size: 75"</li> </ul>
			<ul style="list-style-type: none"> <li>• Resolution: 3,840 x 2,160</li> </ul>
			<ul style="list-style-type: none"> <li>• Screen Curvature: N/A</li> </ul>
			Video
			<ul style="list-style-type: none"> <li>• Picture Engine: Crystal Processor 4K</li> </ul>
			<ul style="list-style-type: none"> <li>• PQI (Picture Quality Index): 2200</li> </ul>
			<ul style="list-style-type: none"> <li>• HDR (High Dynamic Range): HDR</li> </ul>
			<ul style="list-style-type: none"> <li>• HDR 10+: Support</li> </ul>
			<ul style="list-style-type: none"> <li>• HLG (Hybrid Log Gamma): Yes</li> </ul>
			<ul style="list-style-type: none"> <li>• Contrast: Mega Contrast</li> </ul>
			<ul style="list-style-type: none"> <li>• Viewing Angle: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Color: Dynamic Crystal Color</li> </ul>
			<ul style="list-style-type: none"> <li>• Micro Dimming: UHD Dimming</li> </ul>
			<ul style="list-style-type: none"> <li>• Auto Depth Enhancer: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Contrast Enhancer: Yes</li> </ul>
			<ul style="list-style-type: none"> <li>• Auto Motion Plus: Yes</li> </ul>
			<ul style="list-style-type: none"> <li>• Film Mode: Yes</li> </ul>
			<ul style="list-style-type: none"> <li>• Natural Mode Support: Yes</li> </ul>
			Audio
			<ul style="list-style-type: none"> <li>• Dolby Digital Plus: Yes</li> </ul>
			<ul style="list-style-type: none"> <li>• Dolby 5.1 Decoder: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Object Tracking Sound: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Q-Symphony: Q-Symphony</li> </ul>
			<ul style="list-style-type: none"> <li>• Audio Pre-selection Descriptor: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Hole Array Speaker: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Sound Output (RMS): 20W</li> </ul>
			<ul style="list-style-type: none"> <li>• Speaker Type: 2CH</li> </ul>
			<ul style="list-style-type: none"> <li>• Woofer: N/A</li> </ul>
			<ul style="list-style-type: none"> <li>• Multiroom LinkYes</li> </ul>

			• Bluetooth Audio: Yes
			Smart Service
			• SMART TV: Smart
			• Operating System: Tizen™
			• Bixby: US English, UK English, India English, Korean, French, German, Italian, Spanish, Portuguese (features vary by language)
			• Voice Interaction: N/A
			• Far-Field Voice Interaction: N/A
			• Alexa Built-in: N/A
			• Google Assistant Built-in: N/A
			• Works with Google Assistant: N/A
			• Works With Alexa: N/A
			• TV Plus: N/A
			• Web Browser: Yes
			• Gallery: Yes
			Convergence
			• TV to Mobile – Mirroring: N/A
			• Mobile to TV - Mirroring, DLNA: Yes
			• NFC on TV: N/A
			• Tap View: Yes
			• Digital Butler: N/A
			• Multi-View: N/A
			• Sound Wall: Yes
			• Remote Access: Basic
			• 360 Video Player: N/A
			• 360 Camera Support: N/A
			• Bluetooth Low Energy: Yes
			• WiFi Direct: Yes
			• TV Sound to Mobile: Yes
			• Sound Mirroring: Yes
			Differentiation
			• Tune Station: N/A
			• Auto Hotspot Connect: N/A
			• S-Share: N/A
			• Auto Data Backup: N/A
			• Dongle Compatibility (3G / LTE / WiFi): N/A
			• Analog Clean View: N/A
			• Triple Protection: N/A
			Tuner/Broadcasting
			• Digital Broadcasting: ISDB-T
			• Analog Tuner: Yes
			• 2 Tuner: N/A
			• CI (Common Interface): N/A
			• Data Broadcasting: N/A
			• TV Key Support: Yes
			Connectivity
			• HDMI: 3
			• USB: 2
			• Component In (Y/Pb/Pr): N/A
			• Composite In (AV): 1

			• Ethernet (LAN): Yes
			• Audio Out (Mini Jack): N/A
			• Digital Audio Out (Optical): 1
			• RF In (Terrestrial / Cable input): 1/1(Common Use for Terrestrial)/0
			• Ex-Link ( RS-232C ): N/A
			• CI Slot: N/A
			• HDMI A / Return Ch. Support: Yes
			• eARC: Yes
			• HDMI Quick Switch: Yes
			• Wireless LAN Built-in: Yes (WiFi5)
			• Bluetooth: Yes (BT5.2)
			• Anynet+ (HDMI-CEC): Yes
<b>4</b>	<b>7</b>	<b>pc</b>	<b>Air Condition, Split type, Inverter, 2.5 HP</b>
			Cooling capacity: at least 20,000 kj/hr
			wall mounted
			EER rating above 10
			with remote control
			with one year warranty on parts and services
			with free installation
<b>5</b>	<b>1</b>	<b>set</b>	<b>Air Condition, Split type, Inverter, 1.5 HP</b>
			Wattage: 1250 Watts
			EER Rating: 14.26
			WindFree Technology
			Digital Inverter Boost
			Fast Cooling
			Cooling capacity: at least 12,500 kj/hr
			Easy Filter Plus
			DuraFin
			Triple Protector Plus
			Quiet Mode
			Single User Mode
			R32 Refrigerant
			12x Tapping Screw
			4x Rubber Foot (Outdoor Package)
			2x Remote Control Batteries
			Mounting Bracket
			wall mounted
			EER rating above 10
			with remote control
			with one year warranty on parts and services
			with free installation
<b>6</b>	<b>4</b>	<b>set</b>	<b>Air Condition, Split type, Inverter, 2.0 HP</b>
			☑Cooling capacity: at least 18,500 kj/h
			☑wall mounted
			☑EER rating above 10
			☑with Quiet Mode
			☑with remote control
			☑with Anti bacterial air filter
			☑with Micro Dust Filter
			☑with at least 10 years compressor warranty

			<ul style="list-style-type: none"> <li>☑offer must be in the market for at least 10 years</li> <li>☑with at least 10-Year Warranty on Compressor</li> <li>☑with one year warranty on parts and services</li> <li>☑with free installation</li> </ul>
7	1	unit	<b>Air condition, window type, Inverter, 2 HP (Manual), Standard size</b> at least 12,000 kJ/Hr EER: at least 10.5 with three speed cooling switch and timer Please add specs Cooling Capacity 2HP Power Input 860W Noise Level Indoor (Low)46 dBA Power Source230V a.c / 1 Phase- 60hz Refrigerant R32 Unit Dimension(WxHxD) 560x346x655 mm Packaging Dimension 670x481x728mm Net Weight 38 Gross Weight 40
8	4	unit	<b>Air condition, Window type, Inverter, 2.5 HP, Standard Size</b> at least at least 24,000 BTU EER: at least 12.0 With remote Control
9	1	unit	<b>Air Conditioner, Window Type, 2.5 HP, Standard Size</b> Cooling Capacity: 2.5 hp; 25,500 kJ/h Power Input: 2,660 W EER: 9.6 kJ/hW Noise Level Indoor (Low): 52 dB A Power Source: 230 V, 1Ø Phase - 60 Hz Refrigerant: R32 Unit Dimension (WxH xD): 660 x 428 x 800 mm Warranty: Labor & Parts - 1 Year; Compressor - 5 Years
10	3	pc	<b>Aircon Split - type</b> nanoe-X technology-delete HORSEPOWER: 2.5 power source: 230VAC, 60Hz power input: 2300 watts Mas Piping Length: 30 meters Nanoe Technology (Nanoe-G and Nanoe X) Premium Inverter Shower Cooling Thru aerowings I-auto X R32 Eco-Refrigerant Sleep Mode Quiet Mode Soft Dry Operation Mode Personal Airflow Creation Odor Removing

			Removable Washing Panel
			24-hour Dual On and Off Real Setting Timer
			Self Diagnostic Function
			Wireless LAN Remote Control for Internet Connection(Optional)
			LCD Wireless Remote Control
			Wired Remote Control
			Random Auto Restart
			Blue-Fin Condenser
			Long Piping
			Top Panel Maintenance Access
			free installation
<b>11</b>	<b>1</b>	<b>unit</b>	<b>Aircon Split Type (2 HP)</b>
			Capacity: 2.HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 18,000 Btu/h
			Cooling Input: 1552W
			Cooling Current: 6.75A
			EER: 12.24
			Air Flow ( Hi/Mi/Lo): 848x796x626m3/h
			Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)
			Unit Dimension ( W*D*H) : 965x203x323mm (Indoor Unit)
			Weight (Gross) 10.9kg
			Refrigerant Type: R32
			Compressor Type: Rotary
			Unit Dimension ( W*D*H) : 914x343x546mm ( outdoor unit)
			Weight (Gross): 31.7kg
			Application Area: 23-33 sqm
			Accesories such as breaker, bracket and copper tubing not included
			One (1) year warranty on parts and service & compressor
			free installation
<b>12</b>	<b>1</b>	<b>unit</b>	<b>Aircon Split Type 2.5 HP Inverter , With Installation</b>
			Capacity: 2.5HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 24,000 Btu/h
			Cooling Input: 2,000W
			Cooling Current: 8.7A
			EER: 12.7
			Indoor Unit
			Air Flow ( Hi/Mi/Lo): 1063x955x759 m3/h
			Noise Level (Hi/Mi?Lo): 50/-/40 dB (A)
			Unit Dimension ( W*D*H) : 1080x336x326mm (Indoor Unit)
			Weight ( Net/Gross) 13.7/17.4 kg
			Outdoor Unit
			Refrigerant Type: R32/1120
			Compressor Type: Rotary

			Unit Dimension ( W*D*H) : 845x363x702mm ( outdoor unit)
			Weight ( Net/Gross): 49.1/52.4kg
			Application Area: 29-43sqm
			One (1) year warranty on parts and service five (5) years on compressor provided that the unit is installed by accredited installation team
<b>13</b>	<b>2</b>	<b>unit</b>	<b>Aircon, Split Type, 1HP (Inverter)</b>
			Features:
			* High-density Dust Filter
			* Smooth Frequency Control
			* Gold Fin Protection
			* Silver Ion Filter
			* Sleep Mode
			* Turbo Mode
			* Louver Position Memory
			* Fast Cooling
			*with remote control
			Specifications:
			* 1.0HP Inverter
			* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)
			* 700 (290-990) Power Input (W)
			* 4.32 CSPF
			* R32 Refrigerant
			* 39.5/34/32 dB (A) Sound Level (H/M/L)
			1 year warranty with free installation
<b>14</b>	<b>1</b>	<b>unit</b>	<b>Aircon, Window Type, 1.0HP (Inverter)</b>
			1HP Inverter, 8-in-1 Filter, R410A
			Energy Savings Feature:
			24-hour Timer
			Energy Saving Plug
			Econo and Sleep Mode
			EER Rating: 11.6 (10.8 - 10.7)
			Sleek, Modern Aesthetic
			Remote Control
			2 x AAA Batteries
			With Free Installation
			220V, 1 PHASE
			1 year warranty
<b>15</b>	<b>1</b>	<b>unit</b>	<b>Bread Toaster, 4 slots</b>
			4-slice Stainless Steel Toaster
			Stainless Steel Body•Variable
			Toast Control•Defrost & Reheat Functions
			Slide-out Crumb Tray
<b>16</b>	<b>2</b>	<b>unit</b>	<b>Conference Microphone, Gooseneck</b>
			■Acoustic Principle: Condenser Polar
			■Pattern: Cardioid
			■Frequency Response: 50-16000Hz
			■Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)



			<ul style="list-style-type: none"> <li>☑Signal to Noise Ratio: 80dB</li> <li>☑Output connector: XLR Connector</li> <li>☑Power requirement: 48V Phantom Power</li> <li>☑Built-in LED indicator shows Talk/Mute</li> <li>☑Foam windscreen included</li> </ul>
17	1	unit	<p><b>copier machine</b></p> <p>Paper Size: A4. Short, Long; Make : photocopy</p> <p>Staus : Used Copier Machine</p> <p>Color : Color MachinePrint Speed : 35ppm</p> <p>Scanning Resolution : 600*600dpi</p> <p>Zoom Range : 25-400%</p> <p>First Copy Time : 3.6 seconds or less</p> <p>Warm-up Time : 30 seconds or less</p> <p>Scan Resolution: 300dpi, ADF</p> <p>Capacity: 50 sheets and up</p> <p>Function Type: Print, Copy, Scan &amp; Fax</p> <p>Features: Built in ADF, 40 ppm, duplex print scan</p> <p>Copy Fax, Direct USB scan/Print</p> <p>Tray Capacity: 250# sheets</p> <p>Type: Mono-Multi-Functional</p> <p>Connectivity Type: Air Print, USB, wifi</p>
18	1	unit	<p><b>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</b></p> <p>Max printing size: 25*30cm</p> <p>Max printing thickness: 3cm</p> <p>Max printing speed: 2cm - 5cm/s</p> <p>Resolution: 300dpi</p> <p>Printing method: Thermal printing</p> <p>Voltage: AC110-240V 50/60Hz</p> <p>Power: 150W</p> <p>Computer system requirement: Windows</p> <p>Software requirement: Most of softwares, Coreldraw, photoshop, adobe illustrator, office word</p> <p>Temperature requirement: 5°C to 40°C</p> <p>Printer weight: 23kg</p> <p>Printer size: 60cm*50cm*30cm</p> <p>Warranty: 1year excluded printing head unless quality problem</p>
19	1	unit	<p><b>Digital Color Multifunction (3in1) Copy, Print &amp; Scan Photocopier Machine</b></p> <p>Digital Color Multifunction (3in1) Copy, Print &amp; Scan Photocopier Machine</p> <p>Print/Copy Speed: Color/Mono Speed: 25 ppm</p> <p>Print resolution: 1200 x 2400 dpi</p> <p>Memory Capacity: 4GB</p> <p>Storage Device Capacity: 128GB</p> <p>Colour Capability: Full Color</p> <p>Magnificationzoom: 25 to 400% (Reduce/Enlarger)</p> <p>Original Size: Maximum of 297 x 432 mm (A3, 11x17")</p> <p>For both Sheet and Book</p>

			Paper Size: Letter, A4, Legal, Long, Max.: A3, 11x17" Min.:A5 [Postcard (100x148mm)]
			Paper Weight: 60 to 256 gsm
			Paper Tray: Tray 1: 500 sheets Tray 2: 500 sheets & Bypass Tray: 100 sheets
			Duplex: Automatic Document Feeder, automatic Back to Back Electronic Sorting
			Interface: Standard ethernet 1000BASE-T/100BASE- TX/10BASE-T, USB2.0, Network Ready
			Inclusion: Pre-installed CMYK Toner Initial (10,000 copies)
			Metal Pedestal Drawer w/ Wheels
			Power cords, CD's Installer & User Manual
			Manufacturer Certificate
			USB Port Cable
			Free Delivery & Installation Onsite
			Warranty: 1 Year Parts Warranty
			Lifetime Free Service with Regular Monthly
			Preventive Maintenance Check-up Onsite
20	1	set	<b>Digital Duplicator Machine, Copy printer, 300x600 DPI printing</b>
			Master Making/Printing Methods: High-speed digital master-making/Fully automatic printing
			Scanning: 600 dpi × 600 dpi
			Printing: 300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
			Maximum Scanning Area: 297 mm × 432 mm
			Print Paper Weight: 46 gsm to 157 gsm
			Print Paper Size: 100 mm × 148 mm to 310 mm × 432 mm
			Maximum Printing Area: 210 mm × 357 mm
			Paper Feed Tray Stacking Capacity: 1000 sheets*2, stacking height of 110 mm or lower
			Paper Receiving Tray Stacking Capacity: 1000 sheets*2, stacking height of 110 mm or lower
			Print Speed: 5 levels: 60, 80, 100, 120 and 130 ppm
			Functions: Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto*3, Speed, Density, Print Position, Program A/B, Job Separation*3, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via- Printing, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System
			Ink Supply: Full automatic (1000 ml/cartridge)
21	3	unit	<b>Electric fan</b>
			■Stand fan 16" metal blade
			■Adjustable height
			■three speed controller
22	1	lot	<b>Electric Floor Polisher, Vaccum Cleaner and Lawn Mower, Sound System</b>
			Item Specification

			1.Wet and Dry Vacuum Cleaner
			Item Specification
			Super Suction Power
			Wet and Dry Vacuuming
			Blower Function
			Accessory Storage
			Energy Efficient
			SKU: 110361712_PH-7448394060
			Vacuum Cleaner Features: Bagged, Blower, Wheels
			Model: WD 3
			Warranty Type:Local Supplier Warranty
			Warranty Period:1 Year
			Actual suction power* (Air watts) 200
			Energy use (W) 1000
			Container capacity (l) 17
			Container material Stainless steel
			Power cable (m) 4
			Standard accessory ID (mm) 35
			Supply voltage (V/Hz) 220 - 240 / 50 - 60
			Weight without accessories (kg) 5,8
			Weight incl. packaging (kg) 8,2
			Dimensions (L x W x H) (mm) 388 x 340 x 525
			1xSuction hose, 2 m, 35 mm; 2x Suction tubes, 0.5 m, 35 mm; 1x Wet and dry floor nozzle, Clips; 1x Cartridge filter, Standard; 1x Crevice nozzle; 1x Paper filter bag
			3. Electric Floor Polisher
			Item Specification:
			>Speed Switch-Speed Selection low (175 RPM) and High (320 RPM)
			>Handle Tube-All Chrome 1-1/2 inch
			>Power Cord- 50ft. UL Listed 14/3 STW-A. Comes with cord strain relief
			>Transport Wheels- 5 inch non-marking self lubricated wheels
			>All Metal Housing-provides long lasting durability
			4. Sound System
			Item Specification
			The Behringer Europort PPA500BT-delete
			Specs
			Type:Portable PA System
			Speaker Drivers:1 x 8" woofer, 1.35" compression driver
			Number of Mixer Channels:6
			Number of Mic Preamps:2
			EQ:Treble, Bass, 5-band Graphic
			Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in)
			Outputs:2 x 1/4" (speaker out)
			USB:1 x Type A (ULM wireless ready)
			Bluetooth:Yes
			Total Power:500W

			Frequency Response:50Hz-22kHz
			Microphone:1 x Behringer XM1800S
			Power Source:Standard IEC AC cable
			Height:25.9"
			Width:13.9"
			Depth:34.8"
			Weight:44.7 lbs.
<b>23</b>	<b>1</b>	<b>unit</b>	<b>Exhaust Fan</b>
			☐Exhaust Fan 12 inch
			☐power input: 50w
			☐12 inch plastic blade
			☐wall-mounted
			☐reversible motor for desired air flow (Exhaust/Blower)
			☐with pull cord switch
			☐detachable plastic panel & front grill
			☐metal shutters
			☐Air volume: 28.47/ 19.10 CMM
			☐Unit dimension: 39cm x 17cmx39cm
			☐Mounting Dimension: 35cm x 35cm
<b>24</b>	<b>8</b>	<b>pcs</b>	<b>Floor Aircon</b>
			6HP, 5TR, DC INVERTER, R32 REFRIGERANT, ENERGY SAVING, SIDE AIR INTAKE, DIGITAL LED DISPLAY, AUTO LOUVER, SELF DIAGNOSIS AND WITH REMOTE HOLDER, EER RATING: 11.3 KJ/H with Installation
<b>25</b>	<b>3</b>	<b>unit</b>	<b>Floor Mounted Inverter Airconditioner, 3TR</b>
			R410A Refrigerant
			Sleep Mode
			Self diagnosis
			Auto-swing
			Lock function
			Technical Specifications
			Cooling Capacity (Min-Max): 37,000 (9,970-37,300) Btu/h; 39,035 kJ/h
			Power Supply: 230/60/1 V/Hz/Ph
			Rated Power (Min-Max): 3,600 (850-4,350) W
			Rated Current (Min-Max): 16.0 (3.61-19.1) A
			EER: 10.3 Btu/hW; 10.8 kJ/hW
			CSPF: 4.2
			Refrigerant: R410A
			Operation Temperature (Min-Max): 17-30°C
			Airflow Volume (Hi/Med/Low): 1,850 CMH
			Noise Level (Low): 52.0 dB(A)
			with installation
<b>26</b>	<b>1</b>	<b>unit</b>	<b>Heavy Duty Combo Binding Machine</b>
			☐Maximum Punching Sheets: 25
			☐Max Size: LS, F4, A4, Extra Long
			☐Selectable Punching Pins: 24 slots
			☐Net Weight: 12.5kgs
<b>27</b>	<b>1</b>	<b>unit</b>	<b>Hot &amp; Cold water dispenser</b>
			☐Bottom load water dispenser

			☑3 Faucets: Hot, Cold and Normal water function
			☑3-Push Button dispensing control
			☑Anti-scald safety lock switch
			☑Child Lock Safety feature on Hot Water Faucet
			☑Floater indicator to avoid water overflow
			☑Capacity: Hot - 1.2 Liters, Cold - 3.5 liters, Power Rating: Hot - 420 watts, Cold - 100 watts, R134a
<b>28</b>	<b>4</b>	<b>unit</b>	<b>Laminator Machine, A3</b>
			☑Heavy Duty, for A3 & A4 size, infrared heating system and adjustable temperature control with overheating protection
<b>29</b>	<b>1</b>	<b>unit</b>	<b>Megaphone</b>
			☑Bullhorn
			☑1000 yard range
			☑For indoor and outdoor use
			☑Built-in siren
			☑40 W amplifier
			☑Built-in mic
			☑10 seconds recording function
<b>30</b>	<b>3</b>	<b>unit</b>	<b>Paper shredder machine, heavy duty</b>
			☑Shred Type: Cross Cut
			☑Maximum Sheet capacity(70gsm) : 10 Sheets
			☑Waste Container capacity: 21 Liters
			☑Power Source: 220 - 240 VAC
<b>31</b>	<b>4</b>	<b>unit</b>	<b>Portable Trolley 15" Speaker with wireless microphone</b>
			☑15" 2 Way 480 Watts Powered Portable Sound System
			☑Plastic Cabinet
			☑AC220V or DC12V (With built-in Rechargeable Batteries)
			☑With 2 Wireless Microphone
			☑With 2 Mic Input (1 XLR, 1 PL55)
			☑With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port
			☑With 5 Band Equalizer and LCD Display
			☑With Aux / Line In and Line Out
			☑With Remote Control, Handle and Wheel
<b>32</b>	<b>4</b>	<b>unit</b>	<b>Sliding Paper Cutter</b>
			Working Area: A3 and A4
			Cutting Capacity: 16 sheets
			Packing Weight: 5 kg
			Material: Metal
			Available Size: A3 and A4
			Packing Measurement: 56x34x11 cm
			Other Specifications: Heavy duty for Vinyl, Cardboard Paper
<b>33</b>	<b>2</b>	<b>piece</b>	<b>Smart TV 75 inches</b>
			with wall bracket;
			Resolution: 4K Ultra HD
			Screen Size: 75"

			Connectivity: 3x HDMI 2.1
			2X USB
			WIFI
			BLUETOOTH
			HDMI Ports: 3x HDMI 2.1
			Voltage: AC100-240V - 59/69Hz
<b>34</b>	<b>3</b>	<b>unit</b>	<b>Sound System, Speaker</b>
			All-in-one PA system with 10-channel powered mixer and full-range speakers
			Bluetooth audio streaming
			Sub output with automatic high-pass filter for powered subwoofer use
			with 2 microphone
<b>35</b>	<b>1</b>	<b>pc</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>
			☑Power Output : rms 4.5w×2 sw: 12w
			☑Signal to noise ratio : 80dba
			☑Frequency Response : 80hz~20khz (±6db)
			☑R/I: 300±50mv sw: 100 ± 20mv
			☑Aux/USB/SD card
			☑Bass driver :4 inch
			☑Treble driver :2 3/4 inch
<b>36</b>	<b>2</b>	<b>unit</b>	<b>Surge suppressor 6 outlets</b>
			☑Maximum capacity: 2500W
			☑Voltage Surge Protector (protects appliances from voltage spikes)
			☑6 Neon Switch
			☑1 Circuit Breaker (protects appliance from overload or short circuit)
			☑3 Two-Prong Outlets
			☑3 Three-Prong Outlets w/ Grounding
			☑90 degree outlet orientation
			☑With line/noise filter
			☑Royal Cord #16/3 (5.00 meters)
			☑Metal casing
<b>37</b>	<b>1</b>	<b>unit</b>	<b>Television, UHD, Smart TV</b>
			Display Size: 50"
			Ports Input: OTHERS, HDMI, USB, Component in (Y/PB/Pr), RF in (Terrestrial/Cable Input), Digital Audio Out (Optical), Audio Out (Mini Jack), Ethernet (LAN), Composite in (AV)
			TV Features: Netflix, HDR, Cinema 3D ,Wireless Connectivity, Web Browser, Mobile Screen Mirroring, Youtube, DTS Audio, Bluetooth Connectivity
			TV Resolution: 4K UHD
			Smart TV OS: Android OS
<b>38</b>	<b>1</b>	<b>unit</b>	<b>Water Dispenser (top loading), with fridge</b>
			Fridge cabinet to cool additional drinks.
			Three water spouts: hot, room temperature, cold.
			LED indicators add to ease of use.
			Durable/ good quality
			Size & Capacity

			Gross weight (Kg): 17
			Net weight (Kg): 15.46
			Fridge cabinet capacity (L):19
			Type & Setup
			Type: Top load water dispensers
			Control type: Manual
			Product installation: Freestanding
			Product dimensions
			Depth: 372 mm
			Height: 1003 mm
			Width: 318 mm
			Depth packed: 386 mm
			Height packed: 1050 mm
			Width packed: 358 mm
			Power Supply
			Voltage (V): 220-240
			Total wattage (W): 520
<b>39</b>	<b>1</b>	<b>set</b>	<b>Wireless Dual Handheld Microphone</b>
			Receiver
			Power Consumption: 12w (Max)
			Receiver Sensitivity: -95dbm
			Mixing Output Socket: ø6.3mm Socket
			Balanced Output Socket: XLR Socket
			Transmitter
			Carrier Frequency: Depends on regional frequency band
			Transmit Power: 10dBm (±2dBm)
			Microphone Capsule: Dynamic
			Polar Pattern: Super Cardioid
			Impedance: 600
			Frequency Response: 80~12000Hz
			Current Consumption: 120mA
			Battery: Size AA x 2pcs
			Operation Range: 90 meters (in open area)
			Battery Life: Approximately 12 hours (uses alkaline batteries)
			Each microphone has 100 selectable channels and independent volume controls.
			This UHF system features 6-axis gyroscope to automatically enter mute mode when idling for 5~10 seconds.
<b>40</b>	<b>2</b>	<b>units</b>	<b>Water Dispenser, Cabinet type</b>
			☑Floor standing
			☑Hot and cold function
			☑plastic body,high efficiency compressor
			☑thermally protected
<b>41</b>	<b>1</b>	<b>unit</b>	<b>Floor Standing Mounted Airconditioner</b>
			☑At least 4.0HP
			☑Energy Saving Compressor, 3D Air Delivery System
			☑with Sleep Mode
			☑with Auto On / Off Timer

			with High Efficiency Air Filter
			with Remote Control
			Air Conditioner Rated Capacity (BTUs) at least 2.5
42	2	unit	<b>Inverter Digital Wall Mounted Split Type Air Condition</b>
			Capacity (Cooling, kJ/h) - 23400 kJ/hW
			Capacity (Cooling, Min - Max, kJ/h) - 5,000 ~ 27,000 kJ/hW
			Noise Level (Indoor, High/Low, dBA) - 45 / 30 dBA
			Noise Level (Outdoor, High/Low, dBA) - 52 dBA
			Power Source( $\Phi$ /V/Hz) - 1 / 220~240 / 60
			Power Consumption(Cooling, W) - 2000 W
			Operating Current(Cooling, A) - 8.8 A
			Net Dimension (Indoor, WxHxD, mm) - 1055x299x215 mm
			Net Dimension (Outdoor, WxHxD, mm) - 880x638x310 mm
			Net Weight (Indoor, kg) - 11.5 kg
			Net Weight (Outdoor, kg) - 35.3 kg
			Piping Length (Max, m) - 30 m
			Piping Height (Max, m) - 15 m
			SVC Valve (Liquid (ODxL)) - 6.35
			SVC Valve (Gas (ODxL)) - 15.88
			Moisture Removal (l/hr) - 2.5 l/hr
			Air Circulation (Cooling, m <sup>3</sup> /min) - 18.6 m <sup>3</sup> /min
			Refrigerant (Type) - R32
			Low Ambient (Cooling, °C) - 16~46 °C
			Outdoor Unit (Compressor Type) - BLDC
			Outdoor Unit (Anti-Corrosion Fin) - Yes
			Air Direction Control (Up/Down) - Auto
			Air Direction Control (Left/Right) - Auto
			Air Flow Control Step (Cool/Fan) - 5/4
			Easy Filter Plus (Anti-Bacteria) - Yes
			Auto Clean (Self Cleaning) - Yes
			Beep On/Off - Yes
			24-Hour Timer - Yes
			Auto Restart - Yes
			Auto Mode - Yes
			Fast Cool - Yes
			Good Sleep - Yes
			Eco Mode - Yes
			Dehumidification - Yes
			Fan Mode - Yes
			Quiet - Yes
			Free Installation
43	2	unit	<b>Aircon, Split Type, 1.5HP (Inverter)</b>
			Features
			* High-density Dust Filter
			* Smooth Frequency Control
			* Gold Fin Protection
			* Silver Ion Filter



			* Sleep Mode	
			* Turbo Mode	
			* Louver Position Memory	
			* Fast Cooling	
			*with remote control	
			Specifications:	
			* 1.5HP Inverter	
			* 12,700 (3,100-13,200) Cooling Capacity (kJ/hr)	
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)	
			* 1,030 (290-1,210) Power Input (W)	
			* 4.5 CSPF	
			* R32 Refrigerant	
			* 37/34.5/32.5 dB (A) Sound Level (H/M/L)	
			* L 21 x W 72.6 x H 29.1 (cm) Dimension	
			1 year warranty	
			with free installation	
<b>44</b>	<b>1</b>	<b>pc</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>	
			☐Power Output : rms 4.5w×2 sw: 12w	
			☐Signal to noise ratio : 80dba	
			☐Frequency Response : 80hz~20khz (±6db)	
			☐R/I: 300±50mv sw: 100 ± 20mv	
			☐Aux/USB/SD card	
			☐Bass driver :4 inch	
			☐Treble driver :2 3/4 inch	
<b>45</b>	<b>2</b>	<b>unit</b>	<b>Stand Fan, banana type 18" banana blade</b>	

## ***Section VII. Technical Specifications***

# Technical Specifications

Item #	Qty	Unit	Description	Statement of Compliance
1	2	unit	<b>1.5 hp Inverter Window-Type Air Conditioner</b>	[Bidders must state here either “Comply” or “Not Comply” against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of “Comply” or “Not Comply” must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer’s un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder’s statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
			Capacity : Capacity (Cooling, W)3380 W, Capacity (Cooling, kJ/h)12160 kJ/hW	
			Power Input (Nominal): Cooling1095 W	
			Current Input (Nominal): Cooling4.8 W	
			Power Input (Rated): Cooling1390 W	
			Current Input (Rated): Cooling7.5 W	
			Energy Efficiency:	
			EER (Cooling, W/W): 3.08 W/W	
			Permissible Excessive Operating Pressure for the Discharge Side: 4.3 Mpa	
			Maximum Allowable Pressure: 4.7 Mpa	
			Isolation: I	
			EER (Cooling, Btu/hW): 10.51 Btu/hW	
			Permissible Excessive Operating Pressure for the Suction Side: 2.5 Mpa	
			Climate Type: T1	
			Moisture Protection: IPX4	
			Noise Level	
			Sound Pressure Level (H/M/L, dBA): 54/51/50 dBA	
			Electrical Data	
			Power Source(Φ/V/Hz): 1 / 230 / 60	
			Physical specification	
			Package Dimension (WxHxD, mm*mm*mm): 623×425×806 mm	
			Gross Weight (kg): 48 kg	
			Loading Quantity (20’ Container): 125	
			Loading Quantity (40’ High Cube Container): 312	
			Net Dimension (WxHxD, mm*mm*mm): 560×375×708 mm	
			Net Weight(kg): 45 kg	
			Loading Quantity (40’ Container): 260	
			Technical Information	
			Refrigerant (Type): R32	
			Low Ambient (Cooling, °C): 18~43 °C	
			Refrigerant (Charging, kg): 0.53 kg	
			Compressor Type: Rotary	
			Convenience: 24-Hour Timer (Yes)	
			Operating Mode: Auto Mode (Yes), Dehumidification (Yes), Good Sleep (Yes)	
2	2	pc	<b>2 BURNER GAS STOVE</b>	
			☑Heavy duty gas stove	
			☑High quality fuel-efficient burner	
			☑Durable metal gas ignition controls	
			☑Stainless metal gasket and body	
			☑Auto-ignition burner	

			☑# of burners: 2
			☑Dimensions: (W x L X D ) 71 x 35.5 x 8.5cm   28 x 14 x 3.3 inches
			☑Burner diameter: 9cm   3.5 inches   Outer ring diameter: 22.5cm   8.9 inches
			☑Space in between outer rings: 20cm   7.9 inches
			☑Color: silver
			☑Warranty: 1 year
<b>3</b>	<b>1</b>	<b>unit</b>	<b>75 inch interactive display touchscreen Smart TV</b>
			Specifications:
			Picture Engine: Crystal Processor 4K
			• Color: Dynamic Crystal Color
			• Contrast: Mega Contrast
			• Sound: Q-Symphony
			• Smart: Tap-View
			• Design: AirSlim
			Specifications Detail
			Product Type: LED
			Series: 8
			Display
			• Screen Size: 75"
			• Resolution: 3,840 x 2,160
			• Screen Curvature: N/A
			Video
			• Picture Engine: Crystal Processor 4K
			• PQI (Picture Quality Index): 2200
			• HDR (High Dynamic Range): HDR
			• HDR 10+: Support
			• HLG (Hybrid Log Gamma): Yes
			• Contrast: Mega Contrast
			• Viewing Angle: N/A
			• Color: Dynamic Crystal Color
			• Micro Dimming: UHD Dimming
			• Auto Depth Enhancer: N/A
			• Contrast Enhancer: Yes
			• Auto Motion Plus: Yes
			• Film Mode: Yes
			• Natural Mode Support: Yes
			Audio
			• Dolby Digital Plus: Yes
			• Dolby 5.1 Decoder: N/A
			• Object Tracking Sound: N/A
			• Q-Symphony: Q-Symphony
			• Audio Pre-selection Descriptor: N/A
			• Hole Array Speaker: N/A
			• Sound Output (RMS): 20W
			• Speaker Type: 2CH
			• Woofer: N/A
			• Multiroom Link: Yes
			• Bluetooth Audio: Yes
			Smart Service

			• SMART TV: Smart
			• Operating System: Tizen™
			• Bixby: US English, UK English, India English, Korean, French, German, Italian, Spanish, Portuguese (features vary by language)
			• Voice Interaction: N/A
			• Far-Field Voice Interaction: N/A
			• Alexa Built-in: N/A
			• Google Assistant Built-in: N/A
			• Works with Google Assistant: N/A
			• Works With Alexa: N/A
			• TV Plus: N/A
			• Web Browser: Yes
			• Gallery: Yes
			Convergence
			• TV to Mobile – Mirroring: N/A
			• Mobile to TV - Mirroring, DLNA: Yes
			• NFC on TV: N/A
			• Tap View: Yes
			• Digital Butler: N/A
			• Multi-View: N/A
			• Sound Wall: Yes
			• Remote Access: Basic
			• 360 Video Player: N/A
			• 360 Camera Support: N/A
			• Bluetooth Low Energy: Yes
			• WiFi Direct: Yes
			• TV Sound to Mobile: Yes
			• Sound Mirroring: Yes
			Differentiation
			• Tune Station: N/A
			• Auto Hotspot Connect: N/A
			• S-Share: N/A
			• Auto Data Backup: N/A
			• Dongle Compatibility (3G / LTE / WiFi): N/A
			• Analog Clean View: N/A
			• Triple Protection: N/A
			Tuner/Broadcasting
			• Digital Broadcasting: ISDB-T
			• Analog Tuner: Yes
			• 2 Tuner: N/A
			• CI (Common Interface): N/A
			• Data Broadcasting: N/A
			• TV Key Support: Yes
			Connectivity
			• HDMI: 3
			• USB: 2
			• Component In (Y/Pb/Pr): N/A
			• Composite In (AV): 1
			• Ethernet (LAN): Yes
			• Audio Out (Mini Jack): N/A

			• Digital Audio Out (Optical): 1
			• RF In (Terrestrial / Cable input): 1/1(Common Use for Terrestrial)/0
			• Ex-Link ( RS-232C ): N/A
			• CI Slot: N/A
			• HDMI A / Return Ch. Support: Yes
			• eARC: Yes
			• HDMI Quick Switch: Yes
			• Wireless LAN Built-in: Yes (WiFi5)
			• Bluetooth: Yes (BT5.2)
			• Anynet+ (HDMI-CEC): Yes
<b>4</b>	<b>7</b>	<b>pc</b>	<b>Air Condition, Split type, Inverter, 2.5 HP</b>
			Cooling capacity: at least 20,000 kj/hr
			wall mounted
			EER rating above 10
			with remote control
			with one year warranty on parts and services
			with free installation
<b>5</b>	<b>1</b>	<b>set</b>	<b>Air Condition, Split type, Inverter, 1.5 HP</b>
			Wattage: 1250 Watts
			EER Rating: 14.26
			WindFree Technology
			Digital Inverter Boost
			Fast Cooling
			Cooling capacity: at least 12,500 kj/hr
			Easy Filter Plus
			DuraFin
			Triple Protector Plus
			Quiet Mode
			Single User Mode
			R32 Refrigerant
			12x Tapping Screw
			4x Rubber Foot (Outdoor Package)
			2x Remote Control Batteries
			Mounting Bracket
			wall mounted
			EER rating above 10
			with remote control
			with one year warranty on parts and services
			with free installation
<b>6</b>	<b>4</b>	<b>set</b>	<b>Air Condition, Split type, Inverter, 2.0 HP</b>
			☑Cooling capacity: at least 18,500 kj/h
			☑wall mounted
			☑EER rating above 10
			☑with Quiet Mode
			☑with remote control
			☑with Anti bacterial air filter
			☑with Micro Dust Filter
			☑with at least 10 years compressor warranty
			☑offer must be in the market for at least 10 years
			☑with at least 10-Year Warranty on Compressor

			with one year warranty on parts and services
			with free installation
7	1	unit	<b>Air condition, window type, Inverter, 2 HP (Manual), Standard size</b>
			at least 12,000 kj/Hr
			EER: at least 10.5
			with three speed cooling switch and timer
			Please add specs
			Cooling Capacity 2HP
			Power Input 860W
			Noise Level Indoor (Low)46 dBA
			Power Source230V a.c / 1 Phase- 60hz
			Refrigerant R32
			Unit Dimension(WxHxD) 560x346x655 mm
			Packaging Dimension 670x481x728mm
			Net Weight 38
			Gross Weight 40
8	4	unit	<b>Air condition, Window type, Inverter, 2.5 HP, Standard Size</b>
			at least at least 24,000 BTU
			EER: at least 12.0
			With remote Control
9	1	unit	<b>Air Conditioner, Window Type, 2.5 HP, Standard Size</b>
			Cooling Capacity: 2.5 hp; 25,500 kJ/h
			Power Input: 2,660 W
			EER: 9.6 kJ/hW
			Noise Level Indoor (Low): 52 dB A
			Power Source: 230 V, 1Ø Phase - 60 Hz
			Refrigerant: R32
			Unit Dimension (WxH xD): 660 x 428 x 800 mm
			Warranty: Labor & Parts - 1 Year; Compressor - 5 Years
10	3	pc	<b>Aircon Split - type</b>
			nanoe-X technology-delete
			HORSEPOWER: 2.5
			power source: 230VAC, 60Hz
			power input: 2300 watts
			Mas Piping Length: 30 meters
			Nanoe Technology (Nanoe-G and Nanoe X)
			Premium Inverter
			Shower Cooling Thru aerowings
			I-auto X
			R32 Eco-Refrigerant
			Sleep Mode
			Quiet Mode
			Soft Dry Operation Mode
			Personal Airflow Creation
			Odor Removing
			Removable Washing Panel
			24-hour Dual On and Off Real Setting Timer

			Self Diagnostic Function
			Wireless LAN Remote Control for Internet Connection(Optional)
			LCD Wireless Remote Control
			Wired Remote Control
			Random Auto Restart
			Blue-Fin Condenser
			Long Piping
			Top Panel Maintenance Access
			free installation
11	1	unit	<b>Aircon Split Type (2 HP)</b>
			Capacity: 2.HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 18,000 Btu/h
			Cooling Input: 1552W
			Cooling Current: 6.75A
			EER: 12.24
			Air Flow ( Hi/Mi/Lo): 848x796x626m3/h
			Noise Level (Hi/Mi?Lo): 45/39/33 dB (A)
			Unit Dimension ( W*D*H) : 965x203x323mm (Indoor Unit)
			Weight (Gross) 10.9kg
			Refrigerant Type: R32
			Compressor Type: Rotary
			Unit Dimension ( W*D*H) : 914x343x546mm ( outdoor unit)
			Weight (Gross): 31.7kg
			Application Area: 23-33 sqm
			Accessories such as breaker, bracket and copper tubing not included
			One (1) year warranty on parts and service & compressor
			free installation
12	1	unit	<b>Aircon Split Type 2.5 HP Inverter , With Installation</b>
			Capacity: 2.5HP
			Power Supply: 220,230,60,1 V, Hz, Ph
			Cooling Capacity: 24,000 Btu/h
			Cooling Input: 2,000W
			Cooling Current: 8.7A
			EER: 12.7
			Indoor Unit
			Air Flow ( Hi/Mi/Lo): 1063x955x759 m3/h
			Noise Level (Hi/Mi?Lo): 50/-/40 dB (A)
			Unit Dimension ( W*D*H) : 1080x336x326mm (Indoor Unit)
			Weight ( Net/Gross) 13.7/17.4 kg
			Outdoor Unit
			Refrigerant Type: R32/1120
			Compressor Type: Rotary
			Unit Dimension ( W*D*H) : 845x363x702mm ( outdoor unit)



			Weight ( Net/Gross): 49.1/52.4kg
			Application Area: 29-43sqm
			One (1) year warranty on parts and service five (5) years on compressor provided that the unit is installed by accredited installation team
<b>13</b>	<b>2</b>	<b>unit</b>	<b>Aircon, Split Type, 1HP (Inverter)</b>
			Features:
			* High-density Dust Filter
			* Smooth Frequency Control
			* Gold Fin Protection
			* Silver Ion Filter
			* Sleep Mode
			* Turbo Mode
			* Louver Position Memory
			* Fast Cooling
			*with remote control
			Specifications:
			* 1.0HP Inverter
			* 9,500 (2,900-11,000) Cooling Capacity (kJ/hr)
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)
			* 700 (290-990) Power Input (W)
			* 4.32 CSPF
			* R32 Refrigerant
			* 39.5/34/32 dB (A) Sound Level (H/M/L)
			1 year warranty
			with free installation
<b>14</b>	<b>1</b>	<b>unit</b>	<b>Aircon, Window Type, 1.0HP (Inverter)</b>
			1HP Inverter, 8-in-1 Filter, R410A
			Energy Savings Feature:
			24-hour Timer
			Energy Saving Plug
			Econo and Sleep Mode
			EER Rating: 11.6 (10.8 - 10.7)
			Sleek, Modern Aesthetic
			Remote Control
			2 x AAA Batteries
			With Free Installation
			220V, 1 PHASE
			1 year warranty
<b>15</b>	<b>1</b>	<b>unit</b>	<b>Bread Toaster, 4 slots</b>
			4-slice Stainless Steel Toaster
			Stainless Steel Body•Variable
			Toast Control•Defrost & Reheat Functions
			Slide-out Crumb Tray
<b>16</b>	<b>2</b>	<b>unit</b>	<b>Conference Microphone, Gooseneck</b>
			☐Acoustic Principle: Condenser Polar
			☐Pattern: Cardioid
			☐Frequency Response: 50-16000Hz
			☐Sensitivity: -35±2dB(0dB=1V/Pa @ 1KHz)
			☐Signal to Noise Ratio: 80dB
			☐Output connector: XLR Connector

			☑Power requirement: 48V Phantom Power
			☑Built-in LED indicator shows Talk/Mute
			☑Foam windscreen included
17	1	unit	<b>copier machine</b>
			Paper Size: A4. Short, Long; Make : photocopy
			Staus : Used Copier Machine
			Color : Color MachinePrint Speed : 35ppm
			Scanning Resolution : 600*600dpi
			Zoom Range : 25-400%
			First Copy Time : 3.6 seconds or less
			Warm-up Time : 30 seconds or less
			Scan Resolution: 300dpi, ADF
			Capacity: 50 sheets and up
			Function Type: Print, Copy, Scan & Fax
			Features: Built in ADF, 40 ppm, duplex print scan
			Copy Fax, Direct USB scan/Print
			Tray Capacity: 250# sheets
			Type: Mono-Multi-Functional
			Connectivity Type: Air Print, USB, wifi
18	1	unit	<b>Digital Automatic Flatbed Printer; Foil printing hot stamping machine for A3 and A4</b>
			Max printing size: 25*30cm
			Max printing thickness: 3cm
			Max printing speed: 2cm - 5cm/s
			Resolution: 300dpi
			Printing method: Thermal printing
			Voltage: AC110-240V 50/60Hz
			Power: 150W
			Computer system requirement: Windows
			Software requirement: Most of softwares, Coreldraw, photoshop, adobe illustrator, office word
			Temperature requirement: 5°C to 40°C
			Printer weight: 23kg
			Printer size: 60cm*50cm*30cm
			Warranty: 1year excluded printing head unless quality problem
19	1	unit	<b>Digital Color Multifunction (3in1) Copy, Print &amp; Scan Photocopier Machine</b>
			Digital Color Multifunction (3in1) Copy, Print & Scan Photocopier Machine
			Print/Copy Speed: Color/Mono Speed: 25 ppm
			Print resolution: 1200 x 2400 dpi
			Memory Capacity: 4GB
			Storage Device Capacity: 128GB
			Colour Capability: Full Color
			Magnificationzoom: 25 to 400% (Reduce/Enlarger)
			Original Size: Maximum of 297 x 432 mm (A3, 11x17") For both Sheet and Book
			Paper Size: Letter, A4, Legal, Long, Max.: A3, 11x17" Min.:A5 [Postcard (100x148mm)

			Paper Weight: 60 to 256 gsm
			Paper Tray: Tray 1: 500 sheets Tray 2: 500 sheets & Bypass Tray: 100 sheets
			Duplex: Automatic Document Feeder, automatic Back to Back Electronic Sorting
			Interface: Standard ethernet 1000BASE-T/100BASE-TX/10BASE-T, USB2.0, Network Ready
			Inclusion: Pre-installed CMYK Toner Initial (10,000 copies)
			Metal Pedestal Drawer w/ Wheels
			Power cords, CD's Installer & User Manual
			Manufacturer Certificate
			USB Port Cable
			Free Delivery & Installation Onsite
			Warranty: 1 Year Parts Warranty
			Lifetime Free Service with Regular Monthly Preventive Maintenance Check-up Onsite
20	1	set	<b>Digital Duplicator Machine, Copy printer, 300x600 DPI printing</b>
			Master Making/Printing Methods: High-speed digital master-making/Fully automatic printing
			Scanning: 600 dpi × 600 dpi
			Printing: 300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
			Maximum Scanning Area: 297 mm × 432 mm
			Print Paper Weight: 46 gsm to 157 gsm
			Print Paper Size: 100 mm × 148 mm to 310 mm × 432 mm
			Maximum Printing Area: 210 mm × 357 mm
			Paper Feed Tray Stacking Capacity: 1000 sheets*2, stacking height of 110 mm or lower
			Paper Receiving Tray Stacking Capacity: 1000 sheets*2, stacking height of 110 mm or lower
			Print Speed: 5 levels: 60, 80, 100, 120 and 130 ppm
			Functions: Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto*3, Speed, Density, Print Position, Program A/B, Job Separation*3, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System
			Ink Supply: Full automatic (1000 ml/cartridge)
21	3	unit	<b>Electric fan</b>
			■Stand fan 16" metal blade
			■Adjustable height
			■three speed controller
22	1	lot	<b>Electric Floor Polisher, Vacuum Cleaner and Lawn Mower, Sound System</b>
			Item Specification
			1.Wet and Dry Vacuum Cleaner
			Item Specification

		Super Suction Power
		Wet and Dry Vacuuming
		Blower Function
		Accessory Storage
		Energy Efficient
		SKU: 110361712_PH-7448394060
		Vacuum Cleaner Features: Bagged, Blower, Wheels
		Model: WD 3
		Warranty Type:Local Supplier Warranty
		Warranty Period:1 Year
		Actual suction power* (Air watts) 200
		Energy use (W) 1000
		Container capacity (l) 17
		Container material Stainless steel
		Power cable (m) 4
		Standard accessory ID (mm) 35
		Supply voltage (V/Hz) 220 - 240 / 50 - 60
		Weight without accessories (kg) 5,8
		Weight incl. packaging (kg) 8,2
		Dimensions (L x W x H) (mm) 388 x 340 x 525
		1xSuction hose, 2 m, 35 mm; 2x Suction tubes, 0.5 m, 35 mm; 1x Wet and dry floor nozzle, Clips; 1x Cartridge filter, Standard; 1x Crevice nozzle; 1x Paper filter bag
		3. Electric Floor Polisher
		Item Specification:
		>Speed Switch-Speed Selection low (175 RPM) and High (320 RPM)
		>Handle Tube-All Chrome 1-1/2 inch
		>Power Cord- 50ft. UL Listed 14/3 STW-A. Comes with cord strain relief
		>Transport Wheels- 5 inch non-marking self lubricated wheels
		>All Metal Housing-provides long lasting durability
		4. Sound System
		Item Specification
		The Behringer Europort PPA500BT-delete
		Specs
		Type:Portable PA System
		Speaker Drivers:1 x 8" woofer, 1.35" compression driver
		Number of Mixer Channels:6
		Number of Mic Preamps:2
		EQ:Treble, Bass, 5-band Graphic
		Inputs:2 x XLR (mic), 2 x 1/4" (line), 6 x 1/4" (3 x stereo pair), 2 x stereo RCA, 1 x 1/8" (aux in)
		Outputs:2 x 1/4" (speaker out)
		USB:1 x Type A (ULM wireless ready)
		Bluetooth:Yes
		Total Power:500W
		Frequency Response:50Hz-22kHz
		Microphone:1 x Behringer XM1800S

			Power Source:Standard IEC AC cable
			Height:25.9"
			Width:13.9"
			Depth:34.8"
			Weight:44.7 lbs.
<b>23</b>	<b>1</b>	<b>unit</b>	<b>Exhaust Fan</b>
			☐Exhaust Fan 12 inch
			☐power input: 50w
			☐12 inch plastic blade
			☐wall-mounted
			☐reversible motor for desired air flow (Exhaust/Blower)
			☐with pull cord switch
			☐detachable plastic panel & front grill
			☐metal shutters
			☐Air volume: 28.47/ 19.10 CMM
			☐Unit dimension: 39cm x 17cmx39cm
			☐Mounting Dimension: 35cm x 35cm
<b>24</b>	<b>8</b>	<b>pcs</b>	<b>Floor Aircon</b>
			6HP, 5TR, DC INVERTER, R32 REFRIGERANT, ENERGY SAVING, SIDE AIR INTAKE, DIGITAL LED DISPLAY, AUTO LOUVER, SELF DIAGNOSIS AND WITH REMOTE HOLDER, EER RATING: 11.3 KJ/H with Installation
<b>25</b>	<b>3</b>	<b>unit</b>	<b>Floor Mounted Inverter Airconditioner, 3TR</b>
			R410A Refrigerant
			Sleep Mode
			Self diagnosis
			Auto-swing
			Lock function
			Technical Specifications
			Cooling Capacity (Min-Max): 37,000 (9,970-37,300) Btu/h; 39,035 kJ/h
			Power Supply: 230/60/1 V/Hz/Ph
			Rated Power (Min-Max): 3,600 (850-4,350) W
			Rated Current (Min-Max): 16.0 (3.61-19.1) A
			EER: 10.3 Btu/hW; 10.8 kJ/hW
			CSPF: 4.2
			Refrigerant: R410A
			Operation Temperature (Min-Max): 17-30°C
			Airflow Volume (Hi/Med/Low): 1,850 CMH
			Noise Level (Low): 52.0 dB(A)
			with installation
<b>26</b>	<b>1</b>	<b>unit</b>	<b>Heavy Duty Combo Binding Machine</b>
			☐Maximum Punching Sheets: 25
			☐Max Size: LS, F4, A4, Extra Long
			☐Selectable Punching Pins: 24 slots
			☐Net Weight: 12.5kgs
<b>27</b>	<b>1</b>	<b>unit</b>	<b>Hot &amp; Cold water dispenser</b>
			☐Bottom load water dispenser
			☐3 Faucets: Hot, Cold and Normal water function
			☐3-Push Button dispensing control

			☑Anti-scald safety lock switch
			☑Child Lock Safety feature on Hot Water Faucet
			☑Floater indicator to avoid water overflow
			☑Capacity: Hot - 1.2 Liters, Cold - 3.5 liters, Power Rating: Hot - 420 watts, Cold - 100 watts, R134a
28	4	unit	<b>Laminator Machine, A3</b>
			☑Heavy Duty, for A3 & A4 size, infrared heating system and adjustable temperature control with overheating protection
29	1	unit	<b>Megaphone</b>
			☑Bullhorn
			☑1000 yard range
			☑For indoor and outdoor use
			☑Built-in siren
			☑40 W amplifier
			☑Built-in mic
			☑10 seconds recording function
30	3	unit	<b>Paper shredder machine, heavy duty</b>
			☑Shred Type: Cross Cut
			☑Maximum Sheet capacity(70gsm) : 10 Sheets
			☑Waste Container capacity: 21 Liters
			☑Power Source: 220 - 240 VAC
31	4	unit	<b>Portable Trolley 15" Speaker with wireless microphone</b>
			☑15" 2 Way 480 Watts Powered Portable Sound System
			☑Plastic Cabinet
			☑AC220V or DC12V (With built-in Rechargeable Batteries)
			☑With 2 Wireless Microphone
			☑With 2 Mic Input (1 XLR, 1 PL55)
			☑With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port
			☑With 5 Band Equalizer and LCD Display
			☑With Aux / Line In and Line Out
			☑With Remote Control, Handle and Wheel
32	4	unit	<b>Sliding Paper Cutter</b>
			Working Area: A3 and A4
			Cutting Capacity: 16 sheets
			Packing Weight: 5 kg
			Material: Metal
			Available Size: A3 and A4
			Packing Measurement: 56x34x11 cm
			Other Specifications: Heavy duty for Vinyl, Cardboard Paper
33	2	piece	<b>Smart TV 75 inches</b>
			with wall bracket;
			Resolution: 4K Ultra HD
			Screen Size: 75"
			Connectivity: 3x HDMI 2.1
			2X USB

			WIFI
			BLUETOOTH
			HDMI Ports: 3x HDMI 2.1
			Voltage: AC100-240V - 59/69Hz
<b>34</b>	<b>3</b>	<b>unit</b>	<b>Sound System, Speaker</b>
			All-in-one PA system with 10-channel powered mixer and full-range speakers
			Bluetooth audio streaming
			Sub output with automatic high-pass filter for powered subwoofer use
			with 2 microphone
<b>35</b>	<b>1</b>	<b>pc</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>
			☑Power Output : rms 4.5w×2 sw: 12w
			☑Signal to noise ratio : 80dba
			☑Frequency Response : 80hz~20khz (±6db)
			☑R/I: 300±50mv sw: 100 ± 20mv
			☑Aux/USB/SD card
			☑Bass driver :4 inch
			☑Treble driver :2 3/4 inch
<b>36</b>	<b>2</b>	<b>unit</b>	<b>Surge suppressor 6 outlets</b>
			☑Maximum capacity: 2500W
			☑Voltage Surge Protector (protects appliances from voltage spikes)
			☑6 Neon Switch
			☑1 Circuit Breaker (protects appliance from overload or short circuit)
			☑3 Two-Prong Outlets
			☑3 Three-Prong Outlets w/ Grounding
			☑90 degree outlet orientation
			☑With line/noise filter
			☑Royal Cord #16/3 (5.00 meters)
			☑Metal casing
<b>37</b>	<b>1</b>	<b>unit</b>	<b>Television, UHD, Smart TV</b>
			Display Size: 50"
			Ports Input: OTHERS, HDMI, USB, Component in (Y/PB/Pr), RF in (Terrestrial/Cable Input), Digital Audio Out (Optical), Audio Out (Mini Jack), Ethernet (LAN), Composite in (AV)
			TV Features: Netflix, HDR, Cinema 3D ,Wireless Connectivity, Web Browser, Mobile Screen Mirroring, Youtube, DTS Audio, Bluetooth Connectivity
			TV Resolution: 4K UHD
			Smart TV OS: Android OS
<b>38</b>	<b>1</b>	<b>unit</b>	<b>Water Dispenser (top loading), with fridge</b>
			Fridge cabinet to cool additional drinks.
			Three water spouts: hot, room temperature, cold.
			LED indicators add to ease of use.
			Durable/ good quality
			Size & Capacity
			Gross weight (Kg): 17
			Net weight (Kg): 15.46

			Fridge cabinet capacity (L):19
			Type & Setup
			Type: Top load water dispensers
			Control type: Manual
			Product installation: Freestanding
			Product dimensions
			Depth: 372 mm
			Height: 1003 mm
			Width: 318 mm
			Depth packed: 386 mm
			Height packed: 1050 mm
			Width packed: 358 mm
			Power Supply
			Voltage (V): 220-240
			Total wattage (W): 520
<b>39</b>	<b>1</b>	<b>set</b>	<b>Wireless Dual Handheld Microphone</b>
			Receiver
			Power Consumption: 12w (Max)
			Receiver Sensitivity: -95dbm
			Mixing Output Socket: ø6.3mm Socket
			Balanced Output Socket: XLR Socket
			Transmitter
			Carrier Frequency: Depends on regional frequency band
			Transmit Power: 10dBm (±2dBm)
			Microphone Capsule: Dynamic
			Polar Pattern: Super Cardioid
			Impedance: 600
			Frequency Response: 80~12000Hz
			Current Consumption: 120mA
			Battery: Size AA x 2pcs
			Operation Range: 90 meters (in open area)
			Battery Life: Approximately 12 hours (uses alkaline batteries)
			Each microphone has 100 selectable channels and independent volume controls.
			This UHF system features 6-axis gyroscope to automatically enter mute mode when idling for 5~10 seconds.
<b>40</b>	<b>2</b>	<b>units</b>	<b>Water Dispenser, Cabinet type</b>
			☑Floor standing
			☑Hot and cold function
			☑plastic body,high efficiency compressor
			☑thermally protected
<b>41</b>	<b>1</b>	<b>unit</b>	<b>Floor Standing Mounted Airconditioner</b>
			☑At least 4.0HP
			☑Energy Saving Compressor, 3D Air Delivery System
			☑with Sleep Mode
			☑with Auto On / Off Timer
			☑with High Efficiency Air Filter
			☑with Remote Control



			■Air Conditioner Rated Capacity (BTUs) at least 2.5
42	2	unit	<b>Inverter Digital Wall Mounted Split Type Air Condition</b>
			Capacity (Cooling, kJ/h) - 23400 kJ/hW
			Capacity (Cooling, Min - Max, kJ/h) - 5,000 ~ 27,000 kJ/hW
			Noise Level (Indoor, High/Low, dBA) - 45 / 30 dBA
			Noise Level (Outdoor, High/Low, dBA) - 52 dBA
			Power Source(Φ/V/Hz) - 1 / 220~240 / 60
			Power Consumption(Cooling, W) - 2000 W
			Operating Current(Cooling, A) - 8.8 A
			Net Dimension (Indoor, WxHxD, mm) - 1055x299x215 mm
			Net Dimension (Outdoor, WxHxD, mm) - 880x638x310 mm
			Net Weight (Indoor, kg) - 11.5 kg
			Net Weight (Outdoor, kg) - 35.3 kg
			Piping Length (Max, m) - 30 m
			Piping Height (Max, m) - 15 m
			SVC Valve (Liquid (ODxL)) - 6.35
			SVC Valve (Gas (ODxL)) - 15.88
			Moisture Removal (l/hr) - 2.5 l/hr
			Air Circulation (Cooling, m <sup>3</sup> /min) - 18.6 m <sup>3</sup> /min
			Refrigerant (Type) - R32
			Low Ambient (Cooling, °C) - 16~46 °C
			Outdoor Unit (Compressor Type) - BLDC
			Outdoor Unit (Anti-Corrosion Fin) - Yes
			Air Direction Control (Up/Down) - Auto
			Air Direction Control (Left/Right) - Auto
			Air Flow Control Step (Cool/Fan) - 5/4
			Easy Filter Plus (Anti-Bacteria) - Yes
			Auto Clean (Self Cleaning) - Yes
			Beep On/Off - Yes
			24-Hour Timer - Yes
			Auto Restart - Yes
			Auto Mode - Yes
			Fast Cool - Yes
			Good Sleep - Yes
			Eco Mode - Yes
			Dehumidification - Yes
			Fan Mode - Yes
			Quiet - Yes
			Free Installation
43	2	unit	<b>Aircon, Split Type, 1.5HP (Inverter)</b>
			Features
			* High-density Dust Filter
			* Smooth Frequency Control
			* Gold Fin Protection
			* Silver Ion Filter
			* Sleep Mode
			* Turbo Mode

			* Louver Position Memory	
			* Fast Cooling	
			*with remote control	
			Specifications:	
			* 1.5HP Inverter	
			* 12,700 (3,100-13,200) Cooling Capacity (kJ/hr)	
			* 230V, 1Ph, 60Hz Power Supply (V-Ph-Hz)	
			* 1,030 (290-1,210) Power Input (W)	
			* 4.5 CSPF	
			* R32 Refrigerant	
			* 37/34.5/32.5 dB (A) Sound Level (H/M/L)	
			* L 21 x W 72.6 x H 29.1 (cm) Dimension	
			1 year warranty	
			with free installation	
<b>44</b>	<b>1</b>	<b>pc</b>	<b>Speaker, for PC, 2.1 (Speaker with Subwoofer)</b>	
			☐Power Output : rms 4.5w×2 sw: 12w	
			☐Signal to noise ratio : 80dba	
			☐Frequency Response : 80hz~20khz (±6db)	
			☐R/I: 300±50mv sw: 100 ± 20mv	
			☐Aux/USB/SD card	
			☐Bass driver :4 inch	
			☐Treble driver :2 3/4 inch	
<b>45</b>	<b>2</b>	<b>unit</b>	<b>Stand Fan, banana type 18" banana blade</b>	

***Section VIII. Checklist of Technical and  
Financial Documents***

# Checklist of Technical and Financial Documents

## I. TECHNICAL COMPONENT ENVELOPE

### *Class “A” Documents*

#### Legal Documents

- (a) Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages);

#### Technical Documents

- (f) Statement of the prospective bidder of all its ongoing government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid; **and**
- (g) Statement of the bidder’s Single Largest Completed Contract (SLCC) similar to the contract to be bid in the amount of *at least 50% of the ABC or at least Two Million Three Hundred Sixty Two Thousand and Fifty Pesos (PhP 2,362,050.00)*;  
**or**  
Statement of at least two (2) similar completed contracts, the aggregate amount of which should be equivalent to *at least 50% of the ABC or at least Two Million Three Hundred Sixty Two Thousand and Fifty Pesos (PhP 2,362,050.00)* and the largest of these similar contracts must be equivalent to at least half of the said aggregate amount or *at least One Million One Hundred Eighty One Thousand and Twenty Five Pesos (PhP 1,181,025.00)*; **and**
- (h) Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission;  
**or**  
Original copy of Notarized Bid Securing Declaration; **and**
- (i) Conformity with the Technical Specifications; **and**
- (j) Schedule of Requirements/production and delivery schedule; **and**
- (k) Manpower requirements; **and**
- (l) After-sales service/parts; **and**
- (m) Original duly signed Omnibus Sworn Statement (OSS); **and** if applicable, Original Notarized Secretary’s Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.

#### Financial Documents

- (n) The Supplier’s audited financial statements, showing, among others, the Supplier’s total and current assets and liabilities, stamped “received” by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission; **and**
- (o) The prospective bidder’s computation of Net Financial Contracting Capacity (NFCC) – at least equal to ABC (**PhP 4,724,100.00**);  
**or**

A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation (at least 10% of ABC or **PhP 472,410.00**).

**II. FINANCIAL COMPONENT ENVELOPE**

- (a) Original of duly signed and accomplished Financial Bid Form; **and**
- (b) Original of duly signed and accomplished Price Schedule(s).

**Guidelines on the Preparation of Electronic Bid (e-Bid)**  
**(for bidders who prefer electronic bid submission)**

1. Convert all documents into Portable Document Format (PDF) and should be printable.
2. Properly label all documents for prompt identification. Filename of documents, whichever are applicable to the bidder, should be as follows:

<b>Document</b>	<b>Filename (in PDF form)</b>
1. PhilGEPS Certificate of Registration (Platinum)	PhilGEPS
2. Statement of On-Going Government & Private Contracts	Statement of On-Going Contracts
3. Statement of Bidder's Single Largest Completed Contract	SLCC
4. Statement of at least two (2) similar completed contracts	Statement of Completed Contracts
5. Bid Security	Bid Security
6. Technical Specifications	Technical Specifications
7. SCHEDULE of Requirements/Production and delivery schedule	Schedule of Requirements
8. Manpower Requirements	Manpower Requirements
9. After Sales service/parts	After Sales
10. Omnibus Sworn Statement	Omnibus Sworn Statement
11. Audited Financial Statements	Audited Financial Statements
12. Net Financial Contracting Capacity	NFCC
13. Committed Line of Credit	CLC
14. Bid Form	Bid Form
15. Price Schedule	Price Schedule

3. Create two (2) folders that are password-protected. The first folder should contain all requirements under Technical Component checklist as presented under Section VIII. The second folder should contain all requirements under Financial Component checklist.
4. Compress the two (2) folders and name as follows: a) first folder: **Technical Documents**, b) second folder: **Financial Documents**.
5. Email the 2 compressed folders to Mr. Leopoldo Escala at [leopoldo.escala@vsu.edu.ph](mailto:leopoldo.escala@vsu.edu.ph) before the deadline (October 24, 2023; 8:30 AM)



**VISAYAS**  
STATE UNIVERSITY

